

The Scala Language Specification

Version 2.6

DRAFT
November 30, 2007

Martin Odersky

PROGRAMMING METHODS LABORATORY
EPFL
SWITZERLAND

Contents

1	Lexical Syntax	3
1.1	Identifiers	4
1.2	Newline Characters	5
1.3	Literals	8
1.3.1	Integer Literals	9
1.3.2	Floating Point Literals	9
1.3.3	Boolean Literals	10
1.3.4	Character Literals	10
1.3.5	String Literals	10
1.3.6	Escape Sequences	11
1.3.7	Symbol literals	12
1.4	Whitespace and Comments	12
1.5	XML mode	13
2	Identifiers, Names and Scopes	15
3	Types	17
3.1	Paths	18
3.2	Value Types	18
3.2.1	Singleton Types	19
3.2.2	Type Projection	19
3.2.3	Type Designators	19
3.2.4	Parameterized Types	20
3.2.5	Tuple Types	20
3.2.6	Annotated Types	21
3.2.7	Compound Types	21
3.2.8	Infix Types	22
3.2.9	Function Types	23

3.2.10	Existential Types	23
3.2.11	Primitive Types Defined in <i>Predef</i>	26
3.3	Non-Value Types	26
3.3.1	Method Types	26
3.3.2	Polymorphic Method Types	27
3.3.3	Type Constructors	27
3.4	Base Types and Member Definitions	27
3.5	Relations between types	29
3.5.1	Type Equivalence	29
3.5.2	Conformance	30
3.6	Type Erasure	32
4	Basic Declarations and Definitions	35
4.1	Value Declarations and Definitions	35
4.2	Variable Declarations and Definitions	37
4.3	Type Declarations and Type Aliases	39
4.4	Type Parameters	40
4.5	Variance Annotations	42
4.6	Function Declarations and Definitions	44
4.6.1	By-Name Parameters	45
4.6.2	Repeated Parameters	45
4.6.3	Procedures	46
4.6.4	Method Return Type Inference	47
4.7	Import Clauses	47
5	Classes and Objects	49
5.1	Templates	49
5.1.1	Constructor Invocations	51
5.1.2	Class Linearization	52
5.1.3	Class Members	53
5.1.4	Overriding	54
5.1.5	Inheritance Closure	55
5.1.6	Early Definitions	55
5.2	Modifiers	56

5.3	Class Definitions	59
5.3.1	Constructor Definitions	61
5.3.2	Case Classes	62
5.3.3	Traits	64
5.4	Object Definitions	66
6	Expressions	69
6.1	Expression Typing	70
6.2	Literals	70
6.3	The <i>Null</i> Value	71
6.4	Designators	71
6.5	This and Super	72
6.6	Function Applications	73
6.7	Method Values	74
6.8	Type Applications	75
6.9	Tuples	75
6.10	Instance Creation Expressions	76
6.11	Blocks	76
6.12	Prefix, Infix, and Postfix Operations	77
6.12.1	Prefix Operations	78
6.12.2	Postfix Operations	78
6.12.3	Infix Operations	78
6.12.4	Assignment Operators	79
6.13	Typed Expressions	80
6.14	Annotated Expressions	80
6.15	Assignments	80
6.16	Conditional Expressions	82
6.17	While Loop Expressions	82
6.18	Do Loop Expressions	82
6.19	For-Comprehensions	83
6.20	Return Expressions	85
6.21	Throw Expressions	85
6.22	Try Expressions	86

6.23 Anonymous Functions	86
6.24 Statements	88
6.25 Implicit Conversions	89
6.25.1 Value Conversions	89
6.25.2 Method Conversions	90
6.25.3 Overloading Resolution	90
6.25.4 Local Type Inference	91
6.25.5 Eta Expansion	94
7 Implicit Parameters and Views	97
7.1 The Implicit Modifier	97
7.2 Implicit Parameters	98
7.3 Views	100
7.4 View Bounds	101
8 Pattern Matching	103
8.1 Patterns	103
8.1.1 Variable Patterns	104
8.1.2 Typed Patterns	104
8.1.3 Literal Patterns	104
8.1.4 Stable Identifier Patterns	105
8.1.5 Constructor Patterns	105
8.1.6 Tuple Patterns	106
8.1.7 Extractor Patterns	106
8.1.8 Pattern Sequences	107
8.1.9 Infix Operation Patterns	107
8.1.10 Pattern Alternatives	107
8.1.11 XML Patterns	107
8.1.12 Regular Expression Patterns	108
8.1.13 Irrefutable Patterns	108
8.2 Type Patterns	108
8.3 Type Parameter Inference in Patterns	109
8.4 Pattern Matching Expressions	111
8.5 Pattern Matching Anonymous Functions	113

9	Top-Level Definitions	117
9.1	Compilation Units	117
9.2	Packagings	117
9.3	Package References	118
9.4	Programs	119
10	XML expressions and patterns	121
10.1	XML expressions	121
10.2	XML patterns	123
11	User-Defined Annotations	125
12	The Scala Standard Library	129
12.1	Root Classes	129
12.2	Value Classes	131
12.2.1	Numeric Value Types	131
12.2.2	Class <code>Boolean</code>	134
12.2.3	Class <code>Unit</code>	135
12.3	Standard Reference Classes	135
12.3.1	Class <code>String</code>	135
12.3.2	The Tuple classes	136
12.3.3	The Function Classes	136
12.3.4	Class <code>Array</code>	136
12.4	Class <code>Node</code>	139
12.5	The <code>Predef</code> Object	142
A	Scala Syntax Summary	149
B	Change Log	157

Preface

Scala is a Java-like programming language which unifies object-oriented and functional programming. It is a pure object-oriented language in the sense that every value is an object. Types and behavior of objects are described by classes. Classes can be composed using mixin composition. Scala is designed to work seamlessly with two less pure but mainstream object-oriented languages – Java and C#.

Scala is a functional language in the sense that every function is a value. Nesting of function definitions and higher-order functions are naturally supported. Scala also supports a general notion of pattern matching which can model the algebraic types used in many functional languages.

Scala has been designed to interoperate seamlessly with Java (an alternative implementation of Scala also works for .NET). Scala classes can call Java methods, create Java objects, inherit from Java classes and implement Java interfaces. None of this requires interface definitions or glue code.

Scala has been developed from 2001 in the programming methods laboratory at EPFL. Version 1.0 was released in November 2003. This document describes the second version of the language, which was released in March 2006. It acts a reference for the language definition and some core library modules. It is not intended to teach Scala or its concepts; for this there are other documents [Oa04, Ode06, OZ05b, OCRZ03, OZ05a].

Scala has been a collective effort of many people. The design and the implementation of version 1.0 was completed by Philippe Altherr, Vincent Cremet, Gilles Dubochet, Burak Emir, Stéphane Micheloud, Nikolay Mihaylov, Michel Schinz, Erik Stenman, Matthias Zenger, and the author. Iulian Dragos, Gilles Dubochet, Philipp Haller, Sean McDirmid and Lex Spoon joined in the effort to develop the second version of the language and tools. Gilad Bracha, Craig Chambers, Erik Ernst, Matthias Felleisen, Shriram Krishnamurti, Gary Leavens, Sebastian Maneth, Erik Meijer, Klaus Ostermann, Didier Rémy, Mads Torgersen, and Philip Wadler have shaped the design of the language through lively and inspiring discussions and comments on previous versions of this document. The contributors to the Scala mailing list have also given very useful feedback that helped us improve the language and its tools.

Chapter 1

Lexical Syntax

Scala programs are written using the Unicode character set. This chapter defines the two modes of Scala's lexical syntax, the Scala mode and the XML mode. If not otherwise mentioned, the following descriptions of Scala tokens refer to Scala mode, and literal characters 'c' refer to the ASCII fragment \u0000-\u007F.

In Scala mode, *Unicode escapes* are replaced by the corresponding Unicode character with the given hexadecimal code.

```
UnicodeEscape ::= {\{\}\u{u} hexDigit hexDigit hexDigit hexDigit
hexDigit      ::= '0' | ... | '9' | 'A' | ... | 'F' | 'a' | ... | 'f' |
```

To construct tokens, characters are distinguished according to the following classes (Unicode general category given in parentheses):

1. Whitespace characters. \u0020 | \u0009 | \u000D | \u000A
2. Letters, which include lower case letters(Ll), upper case letters(Lu), title-case letters(Lt), other letters(Lo), letter numerals(Nl) and the two characters \u0024 '\$' and \u005F '_', which both count as upper case letters
3. Digits '0' | ... | '9'.
4. Parentheses '(' | ')' | '[' | ']' | '{' | '}'.
5. Delimiter characters '' | '' | "" | '.' | ';' | ','.
6. Operator characters. These consist of all printable ASCII characters \u0020-\u007F. which are in none of the sets above, mathematical symbols(Sm) and other symbols(So).

1.1 Identifiers

Syntax:

```

op      ::= opchar {opchar}
varid   ::= lower idrest
plainid ::= upper idrest
        | varid
        | op
id      ::= plainid
        | '\\' stringLit '\\'
idrest  ::= {letter | digit} ['_' op]

```

There are three ways to form an identifier. First, an identifier can start with a letter which can be followed by an arbitrary sequence of letters and digits. This may be followed by underscore ‘_’ characters and another string composed of either letters and digits or of operator characters. Second, an identifier can start with an operator character followed by an arbitrary sequence of operator characters. The preceding two forms are called *plain* identifiers. Finally, an identifier may also be formed by an arbitrary string between back-quotes (host systems may impose some restrictions on which strings are legal for identifiers). The identifier then is composed of all characters excluding the backquotes themselves.

As usual, a longest match rule applies. For instance, the string

```
big_bob++='def'
```

decomposes into the three identifiers `big_bob`, `++=`, and `def`. The rules for pattern matching further distinguish between *variable identifiers*, which start with a lower case letter, and *constant identifiers*, which do not.

The ‘\$’ character is reserved for compiler-synthesized identifiers. User programs should not define identifiers which contain ‘\$’ characters.

The following names are reserved words instead of being members of the syntactic class `id` of lexical identifiers.

abstract	case	catch	class	def
do	else	extends	false	final
finally	for	forSome	if	implicit
import	lazy	match	new	null
object	override	package	private	protected
requires	return	sealed	super	this
throw	trait	try	true	type
val	var	while	with	yield
_	:	=	=>	<-
			<:	<%
			>:	#
				@

The Unicode operator \u21D2 ‘⇒’, which has the ASCII equivalent ‘=>’, is also re-

served.

Example 1.1.1 Here are examples of identifiers:

x	Object	maxIndex	p2p	empty_?
+	'yield'	$\alpha\rho\epsilon\tau\eta$	_y	dot_product_*
__system	_MAX_LEN_			

Example 1.1.2 Backquote-enclosed strings are a solution when one needs to access Java identifiers that are reserved words in Scala. For instance, the statement `Thread.yield()` is illegal, since **yield** is a reserved word in Scala. However, here's a work-around:

```
Thread.`yield`()
```

1.2 Newline Characters

Syntax:

```
semi ::= ';' | nl {nl}
```

Scala is a line-oriented language where statements may be terminated by semicolons or newlines. A newline in a Scala source text is treated as the special token "nl" if the three following criteria are satisfied:

1. The token immediately preceding the newline can terminate a statement.
2. The token immediately following the newline can begin a statement.
3. The token appears in a region where multiple statements are allowed.

The tokens that can terminate a statement are: literals, identifiers and the following delimiters and reserved words:

this	null	true	false	return	type	<xml-start>
_)]	}			

The tokens that can begin a statement are all Scala tokens *except* the following delimiters and reserved words:

catch	else	extends	finally	forSome	match	requires
with	yield	,	.	;	:	_
>:	#	[)]	}	
					=	=>
					<-	<:
						<%

A **case** token can begin a statement only if followed by a **class** or **object** token.

Multiple statements are allowed in:

1. all of a Scala source file, except for nested regions where newlines are suppressed, and
2. the interval between matching { and } brace tokens, except for nested regions where newlines are suppressed.

Multiple statements are disabled in:

1. the interval between matching (and) parenthesis tokens, except for nested regions where newlines are enabled, and
2. the interval between matching [and] bracket tokens, except for nested regions where newlines are enabled.
3. The interval between a **case** token and its matching => token, except for nested regions where newlines are enabled.
4. Any regions analyzed in XML mode (§1.5).

Note that the brace characters of { . . . } escapes in XML and string literals are not tokens, and therefore do not enclose a region where newlines are enabled.

Normally, only a single nl token is inserted between two consecutive non-newline tokens which are on different lines, even if there are multiple lines between the two tokens. However, if two tokens are separated by at least one completely blank line (i.e a line which contains no printable characters), then two nl tokens are inserted.

The Scala grammar (given in full in Appendix A) contains productions where optional nl tokens, but not semicolons, are accepted. This has the effect that a newline in one of these positions does not terminate an expression or statement. These positions can be summarized as follows:

Multiple newline tokens are accepted in the following places (note that a semicolon in place of the newline would be illegal in every one of these cases):

- between the condition of an conditional expression (§6.16) or while loop (§6.17) and the next following expression,
- between the enumerators of a for-comprehension (§6.19) and the next following expression, and
- after the initial **type** keyword in a type definition or declaration (§4.3).

A single new line token is accepted

- in front of an opening brace "{", if that brace is a legal continuation of the current statement or expression,
- after an infix operator, if the first token on the next line can start an expression (§6.12),

- in front of a parameter clause (§4.6), and
- after an annotation (§11).

Example 1.2.1 The following code contains four well-formed statements, each on two lines. The newline tokens between the two lines are not treated as statement separators.

```
if (x > 0)
  x = x - 1

while (x > 0)
  x = x / 2

for (x <- 1 to 10)
  println(x)

type
  IntList = List[Int]
```

Example 1.2.2 The following code designates an anonymous class

```
new Iterator[Int]
{
  private var x = 0
  def hasNext = true
  def next = { x += 1; x }
}
```

With an additional newline character, the same code is interpreted as an object creation followed by a local block:

```
new Iterator[Int]

{
  private var x = 0
  def hasNext = true
  def next = { x += 1; x }
}
```

Example 1.2.3 The following code designates a single expression:

```
x < 0 ||
x > 10
```

With an additional newline character, the same code is interpreted as two expressions:

```
x < 0 ||
```

```
x > 10
```

Example 1.2.4 The following code designates a single, curried function definition:

```
def func(x: Int)
    (y: Int) = x + y
```

With an additional newline character, the same code is interpreted as an abstract function definition and a syntactically illegal statement:

```
def func(x: Int)

    (y: Int) = x + y
```

Example 1.2.5 The following code designates an attributed definition:

```
@serializable
protected class Data { ... }
```

With an additional newline character, the same code is interpreted as an attribute and a separate statement (which is syntactically illegal).

```
@serializable

protected class Data { ... }
```

1.3 Literals

There are literals for integer numbers, floating point numbers, characters, booleans, symbols, strings. The syntax of these literals is in each case as in Java.

Syntax:

```
Literal ::= integerLiteral
         | floatingPointLiteral
         | booleanLiteral
         | characterLiteral
         | stringLiteral
         | symbolLiteral
         | 'null'
```


1.3.1 Integer Literals

Syntax:

```

integerLiteral ::= (decimalNumeral | hexadecimal | octalNumeral) ['L' | 'l']
decimalNumeral ::= '0' | nonZeroDigit {digit}
hexadecimal    ::= '0' 'x' hexDigit {hexDigit}
octalNumeral   ::= '0' octalDigit {octalDigit}
digit          ::= '0' | nonZeroDigit
nonZeroDigit   ::= '1' | ... | '9'
octalDigit     ::= '0' | ... | '7'

```

Integer literals are usually of type `Int`, or of type `Long` when followed by a `L` or `l` suffix. Values of type `Int` are all integer numbers between -2^{31} and $2^{31} - 1$, inclusive. Values of type `Long` are all integer numbers between -2^{63} and $2^{63} - 1$, inclusive. A compile-time error occurs if an integer literal denotes a number outside these ranges.

However, if the expected type *pt* (§6.1) of a literal in an expression is either `Byte`, `Short`, or `Char` and the integer number fits in the numeric range defined by the type, then the number is converted to type *pt* and the literal's type is *pt*. The numeric ranges given by these types are:

<code>Byte</code>	-2^7 to $2^7 - 1$
<code>Short</code>	-2^{15} to $2^{15} - 1$
<code>Char</code>	0 to $2^{16} - 1$

Example 1.3.1 Here are some integer literals:

```
0          21          0xFFFFFFFF          0777L
```

1.3.2 Floating Point Literals

Syntax:

```

floatingPointLiteral ::= digit {digit} '.' {digit} [exponentPart] [floatType]
                    | '.' digit {digit} [exponentPart] [floatType]
                    | digit {digit} exponentPart [floatType]
                    | digit {digit} [exponentPart] floatType
exponentPart         ::= ('E' | 'e') ['+' | '-'] digit {digit}
floatType             ::= 'F' | 'f' | 'D' | 'd'

```

Floating point literals are of type `Float` when followed by a floating point type suffix `F` or `f`, and are of type `Double` otherwise. The type `Float` consists of all IEEE 754 32-bit single-precision binary floating point values, whereas the type `Double` consists of all IEEE 754 64-bit double-precision binary floating point values.

Example 1.3.2 Here are some floating point literals:

0.0 1e30f 3.14159f 1.0e-100 .1

1.3.3 Boolean Literals

Syntax:

```
booleanLiteral ::= 'true' | 'false'
```

The boolean literals **true** and **false** are members of type `Boolean`.

1.3.4 Character Literals

Syntax:

```
characterLiteral ::= '\'' printableChar '\''
                  | '\'' charEscapeSeq '\''
```

A character literal is a single character enclosed in quotes. The character is either a printable unicode character or is described by an escape sequence (§1.3.6).

Example 1.3.3 Here are some character literals:

'a' '\u0041' '\n' '\t'

Note that `'\u000A'` is *not* a valid character literal because Unicode conversion is done before literal parsing and the Unicode character `\u000A` (line feed), and is not a printable character. One can use instead the escape sequence `'\n'` or the octal escape `'\12'` (§1.3.6).

1.3.5 String Literals

Syntax:

```
stringLiteral ::= '"' {stringElement} '"'
stringElement ::= printableCharNoDoubleQuote | charEscapeSeq
```

A string literal is a sequence of characters in double quotes. The characters are either printable unicode character or are described by escape sequences (§1.3.6). If the string literal contains a double quote character, it must be escaped, i.e. `\"`. The value of a string literal is an instance of class `String`.

Example 1.3.4 Here are some string literals:

```
"Hello,\nWorld!"
"This string contains a \" character."
```

Multi-Line String Literals

Syntax:

```
stringLiteral ::= '""' multiLineChars '""'
multiLineChars ::= {[''''] [''''] charNoDoubleQuote}
```

A multi-line string literal is a sequence of characters enclosed in triple quotes `""" ... """`. The sequence of characters is arbitrary, except that it may not contain a triple quote. Characters must not necessarily be printable; newlines or other control characters are also permitted. Unicode escapes work as everywhere else, but none of the escape sequences in (§1.3.6) is interpreted.

Example 1.3.5 Here is a multi-line string literal:

```
"""the present string
   spans three
   lines."""
```

This would produce the string:

```
the present string
  spans three
  lines.
```

The Scala library contains a utility method `stripMargin` which can be used to strip leading whitespace from multi-line strings. The expression

```
"""the present string
 |spans three
 |lines.""".stripMargin
```

evaluates to

```
the present string
spans three
lines.
```

Method `stripMargin` is defined in class `scala.runtime.RichString`. Because there is a predefined implicit conversion (§6.25) from `String` to `RichString`, the method is applicable to all strings.

1.3.6 Escape Sequences

The following escape sequences are recognized in character and string literals.

<code>\b</code>	<code>\u0008</code> : backspace BS
<code>\t</code>	<code>\u0009</code> : horizontal tab HT
<code>\n</code>	<code>\u000a</code> : linefeed LF
<code>\f</code>	<code>\u000c</code> : form feed FF
<code>\r</code>	<code>\u000d</code> : carriage return CR
<code>\"</code>	<code>\u0022</code> : double quote "
<code>\'</code>	<code>\u0027</code> : single quote '
<code>\\</code>	<code>\u005c</code> : backslash \

A character with Unicode between 0 and 255 may also be represented by an octal escape, i.e. a backslash `\` followed by a sequence of up to three octal characters.

It is a compile time error if a backslash character in a character or string literal does not start a valid escape sequence.

1.3.7 Symbol literals

Syntax:

```
symbolLiteral ::= ''' idrest
```

A symbol literal `'x'` is a shorthand for the expression `scala.Symbol("x").intern`. `Symbol` is a case class (§5.3.2), which is defined as follows.

```
package scala
final case class Symbol(name: String) {
  override def toString: String = "'" + name
  def intern: Symbol = ...
}
```

The `intern` method turns symbols into unique references: If two interned symbols have the same name, then they must be the same object.

1.4 Whitespace and Comments

Tokens may be separated by whitespace characters and/or comments. Comments come in two forms:

A single-line comment is a sequence of characters which starts with `//` and extends to the end of the line.

A multi-line comment is a sequence of characters between `/*` and `*/`. Multi-line comments may be nested.

1.5 XML mode

In order to allow literal inclusion of XML fragments, lexical analysis switches from Scala mode to XML mode when encountering an opening angle bracket '`<`' in the following circumstance: The '`<`' must be preceded either by whitespace, an opening parenthesis or an opening brace and immediately followed by a character starting an XML name.

Syntax:

```
( whitespace | '(' | '{' ) '<' (XNameStart | '!' | '?')
```

```
XNameStart ::= '_' | BaseChar | Ideographic (as in W3C XML, but without ':'
```

The scanner switches from XML mode to Scala mode if either

- the XML expression or the XML pattern started by the initial '`<`' has been successfully parsed, or if
- the parser encounters an embedded Scala expression or pattern and forces the Scanner back to normal mode, until the Scala expression or pattern is successfully parsed. In this case, since code and XML fragments can be nested, the parser has to maintain a stack that reflects the nesting of XML and Scala expressions adequately.

Note that no Scala tokens are constructed in XML mode, and that comments are interpreted as text.

Example 1.5.1 The following value definition uses an XML literal with two embedded Scala expressions

```
val b = <book>
  <title>The Scala Language Specification</title>
  <version>{scalaBook.version}</version>
  <authors>{scalaBook.authors.mkList("", " ", " ")}</authors>
</book>
```


Chapter 2

Identifiers, Names and Scopes

Names in Scala identify types, values, methods, and classes which are collectively called *entities*. Names are introduced by local definitions and declarations (§4), inheritance (§5.1.3), import clauses (§4.7), or package clauses (§9.2) which are collectively called *bindings*.

Bindings of different kinds have a precedence defined on them: Definitions (local or inherited) have highest precedence, followed by explicit imports, followed by wildcard imports, followed by package members, which have lowest precedence.

There are two different name spaces, one for types (§3) and one for terms (§6). The same name may designate a type and a term, depending on the context where the name is used.

A binding has a *scope* in which the entity defined by a single name can be accessed using a simple name. Scopes are nested. A binding in some inner scope *shadows* bindings of lower precedence in the same scope as well as bindings of the same or lower precedence in outer scopes.

Note that shadowing is only a partial order. In a situation like

```
val x = 1;
{ import p.x;
  x }
```

neither binding of *x* shadows the other. Consequently, the reference to *x* in the third line above would be ambiguous.

A reference to an unqualified (type- or term-) identifier *x* is bound by the unique binding, which

- defines an entity with name *x* in the same namespace as the identifier, and
- shadows all other bindings that define entities with name *x* in that namespace.

It is an error if no such binding exists. If x is bound by an import clause, then the simple name x is taken to be equivalent to the qualified name to which x is mapped by the import clause. If x is bound by a definition or declaration, then x refers to the entity introduced by that binding. In that case, the type of x is the type of the referenced entity.

Example 2.0.2 Assume the following two definitions of a objects named X in packages P and Q .

```
package P {
  object X { val x = 1; val y = 2 }
}

package Q {
  object X { val x = true; val y = "" }
}
```

The following program illustrates different kinds of bindings and precedences between them.

```
package P {                                     // 'X' bound by package clause
import Console._                               // 'println' bound by wildcard import
object A {
  println("L4: "+X)                             // 'X' refers to 'P.X' here
  object B {
    import Q._                                  // 'X' bound by wildcard import
    println("L7: "+X)                           // 'X' refers to 'Q.X' here
    import X._                                  // 'x' and 'y' bound by wildcard import
    println("L8: "+x)                           // 'x' refers to 'Q.X.x' here
    object C {
      val x = 3                                 // 'x' bound by local definition
      println("L12: "+x)                       // 'x' refers to constant '3' here
      { import Q.X._                           // 'x' and 'y' bound by wildcard import
//      println("L14: "+x)                     // reference to 'x' is ambiguous here
      import X.y                               // 'y' bound by explicit import
      println("L16: "+y)                       // 'y' refers to 'Q.X.y' here
      { val x = "abc"                          // 'x' bound by local definition
      import P.X._                            // 'x' and 'y' bound by wildcard import
//      println("L19: "+y)                     // reference to 'y' is ambiguous here
      println("L20: "+x)                      // 'x' refers to string "abc" here
      }}}}}
}}}}}}
```

A reference to a qualified (type- or term-) identifier $e.x$ refers to the member of the type T of e which has the name x in the same namespace as the identifier. It is an error if T is not a value type (§3.2). The type of $e.x$ is the member type of the referenced entity in T .

Chapter 3

Types

Syntax:

```
Type          ::= InfixType '=>' Type
                | '(' ['=>' Type] ')' '=>' Type
                | InfixType [ExistentialClause]
ExistentialClause ::= 'forSome' '{' ExistentialDcl {semi ExistentialDcl} '}'
ExistentialDcl   ::= 'type' TypeDcl
                | 'val' ValDcl
InfixType        ::= CompoundType {id [nl] CompoundType}
CompoundType     ::= AnnotType {'with' AnnotType} [Refinement]
                | Refinement
AnnotType        ::= {Annotation} SimpleType
SimpleType       ::= SimpleType TypeArgs
                | SimpleType '#' id
                | StableId
                | Path '.' 'type'
                | '(' Types [' ',''] ')'
TypeArgs         ::= '[' Types '[' ']'
Types            ::= Type {' ','' Type}
```

We distinguish between first-order types and type constructors, which take type parameters and yield types. A subset of first-order types called *value types* represents sets of (first-class) values. Value types are either *concrete* or *abstract*.

Every concrete value type can be represented as a *class type*, i.e. a type designator (§3.2.3) that refers to a class¹ (§5.3), or as a *compound type* (§3.2.7) representing an intersection of types, possibly with a refinement (§3.2.7) that further constrains the types of its members. Abstract value types are introduced by type parameters (§4.4) and abstract type bindings (§4.3). Parentheses in types are used for grouping.

¹We assume that objects and packages also implicitly define a class (of the same name as the object or package, but inaccessible to user programs).

Non-value types capture properties of identifiers that are not values (§3.3). For example, a type constructor (§3.3.3) does not directly specify the type of values. However, when a type constructor is applied to the correct type arguments, it yields a first-order type, which may be a value type.

Non-value types are expressed indirectly in Scala. E.g., a method type is described by writing down a method signature, which in itself is not a real type, although it gives rise to a corresponding function type (§3.3.1). Type constructors are another example, as one can write **type** `Swap[m[_], a, b] = m[b, a]`, but there is **no** syntax to write the corresponding anonymous type function directly.

3.1 Paths

Syntax:

```

Path          ::= StableId
                | [id '.' ] this
StableId      ::= id
                | Path '.' id
                | [id '.' ] 'super' [ClassQualifier] '.' id
ClassQualifier ::= '[' id '[' ]'

```

Paths are not types themselves, but they can be a part of named types and in that function form a central role in Scala's type system.

A path is one of the following.

- The empty path ϵ (which cannot be written explicitly in user programs).
- `C.this`, where `C` references a class. The path **this** is taken as a shorthand for `C.this` where `C` is the name of the class directly enclosing the reference.
- `p.x` where `p` is a path and `x` is a stable member of `p`. *Stable members* are members introduced by value or object definitions, as well as packages.
- `C.super.x` or `C.super[M].x` where `C` references a class and `x` references a stable member of the super class or designated parent class `M` of `C`. The prefix **super** is taken as a shorthand for `C.super` where `C` is the name of the class directly enclosing the reference.

A *stable identifier* is a path which ends in an identifier.

3.2 Value Types

Every value in Scala has a type which is of one of the following forms.

3.2.1 Singleton Types

Syntax:

`SimpleType ::= Path '.' type`

A singleton type is of the form $p.\mathbf{type}$, where p is a path pointing to a value expected to conform (§6.1) to `scala.AnyRef`. The type denotes the set of values consisting of `null` and the value denoted by p .

All singleton types conform to the type `scala.Singleton`. A *stable type* is either a singleton type or a type equivalent to `scala.Singleton`.

3.2.2 Type Projection

Syntax:

`SimpleType ::= SimpleType '#' id`

A type projection $T\#x$ references the type member named x of type T . If x references an abstract type member, then T must be a stable type (§3.2.1).

3.2.3 Type Designators

Syntax:

`SimpleType ::= StableId`

A type designator refers to a named value type. It can be simple or qualified. All such type designators are shorthands for type projections.

Specifically, the unqualified type name t where t is bound in some class, object, or package C is taken as a shorthand for $C.\mathbf{this.type}\#t$. If t is not bound in a class, object, or package, then t is taken as a shorthand for $\epsilon.\mathbf{type}\#t$.

A qualified type designator has the form $p.t$ where p is a path (§3.1) and t is a type name. Such a type designator is equivalent to the type projection $p.\mathbf{type}\#x$.

Example 3.2.1 Some type designators and their expansions are listed below. We assume a local type parameter t , a value maintable with a type member `Node` and the standard class `scala.Int`,

t	$\epsilon.\mathbf{type}\#t$
<code>Int</code>	<code>scala.type\#Int</code>
<code>scala.Int</code>	<code>scala.type\#Int</code>
<code>data.maintable.Node</code>	<code>data.maintable.type\#Node</code>

3.2.4 Parameterized Types

Syntax:

```
SimpleType      ::= SimpleType TypeArgs
TypeArgs        ::= '[' Types '['
```

A parameterized type $T[U_1, \dots, U_n]$ consists of a type designator T and type parameters U_1, \dots, U_n where $n \geq 1$. T must refer to a type constructor which takes n type parameters a_1, \dots, a_n .

Say the type parameters have lower bounds L_1, \dots, L_n and upper bounds U_1, \dots, U_n . The parameterized type is well-formed if each actual type parameter *conforms to its bounds*, i.e. $\sigma L_i <: T_i <: \sigma U_i$ where σ is the substitution $[a_1 := T_1, \dots, a_n := T_n]$.

Example 3.2.2 Given the partial type definitions:

```
class TreeMap[A <: Comparable[A], B] { ... }
class List[A] { ... }
class I extends Comparable[I] { ... }
```

the following parameterized types are well formed:

```
TreeMap[I, String]
List[I]
List[List[Boolean]]
```

Example 3.2.3 Given the type definitions of Example 3.2.2, the following types are ill-formed:

```
TreeMap[I] // illegal: wrong number of parameters
TreeMap[List[I], Boolean] // illegal: type parameter not within bound
```

3.2.5 Tuple Types

Syntax:

```
SimpleType      ::= '(' Types '[' , ' ] ')'
```

A tuple type (T_1, \dots, T_n) is an alias for the class `scala.Tuplen[T_1, \dots, T_n]`, where $n \geq 2$. The type may also be written with a trailing comma, i.e. $(T_1, \dots, T_n,)$. The unary tuple type `scala.Tuple1[T]` can be written in tuple syntax only by using a trailing comma, i.e. $(T,)$.

Tuple classes are case classes whose fields can be accessed using selectors `_1, ..., _n`. Their functionality is abstracted in a corresponding `Product` trait. The n -ary tuple class and product trait are defined at least as follows in the standard Scala library (they might also add other methods and implement other traits).

```

case class Tuplen[+T1, ..., +Tn](_1: T1, ..., _n: Tn)
extends Productn[T1, ..., Tn] {}

trait Productn[+T1, +T2, +Tn] {
  override def arity = n
  def _1: T1
  ...
  def _n:Tn
}

```

3.2.6 Annotated Types

Syntax:

```
AnnotType ::= SimpleType {Annotation}
```

An annotated type $T \ a_1 \dots a_n$ attaches annotations a_1, \dots, a_n to the type T (§11).

3.2.7 Compound Types

Syntax:

```

CompoundType ::= AnnotType {'with' AnnotType} [Refinement]
                | Refinement
Refinement    ::= [nl] '{' RefineStat {semi RefineStat} '}'
RefineStat    ::= Dcl
                | 'type' TypeDef
                |

```

A compound type $T_1 \text{ with } \dots \text{ with } T_n \{R\}$ represents objects with members as given in the component types T_1, \dots, T_n and the refinement $\{R\}$. A refinement $\{R\}$ contains declarations and type definitions. If a declaration or definition overrides a declaration or definition in one of the component types T_1, \dots, T_n , the usual rules for overriding (§5.1.4) apply; otherwise the declaration or definition is said to be “structural”². Within a method declaraton in a structural refinement, the type of any value parameter may only refer to type parameters or abstract types that are contained inside the refinement. That is, it must refer either to a type parameter of the function itself, or to a type definition within the refinement. This restriction does not apply to the function’s result type.

If no refinement is given, the empty refinement is implicitly added, i.e. $T_1 \text{ with } \dots \text{ with } T_n$ is a shorthand for $T_1 \text{ with } \dots \text{ with } T_n \{\}$.

A compound type may also consist of just a refinement $\{R\}$ with no preceding component types. Such a type is equivalent to $\text{AnyRef}\{R\}$.

²A reference to a structurally defined member (method call or access to a value or variable) may generate binary code that is significantly slower than an equivalent code to a non-structural member.

Example 3.2.4 The following example shows how to declare and use a function which parameter's type contains a refinement with structural declarations.

```

case class Bird (val name: String) extends Object {
  def fly(height: Int) = ...
  ...
}
case class Plane (val callsign: String) extends Object {
  def fly(height: Int) = ...
  ...
}
def takeoff(
  runway: Int,
  r: { val callsign: String; def fly(height: Int) }) = {
  tower.print(r.callsign + " requests take-off on runway " + runway)
  tower.read(r.callsign + " is clear for take-off")
  r.fly(1000)
}
val bird = new Bird("Polly the parrot"){ val callsign = name }
val a380 = new Plane("TZ-987")
takeoff(42, bird)
takeoff(89, a380)

```

Although `Bird` and `Plane` do not share any parent class other than `Object`, the parameter `r` of function `takeoff` is defined using a refinement with structural declarations to accept any object that declares a value `callsign` and a `fly` function.

3.2.8 Infix Types

Syntax:

$$\text{InfixType} \quad ::= \quad \text{CompoundType} \{ \text{id} \text{ [nl] CompoundType} \}$$

An infix type $T_1 \text{ op } T_2$ consists of an infix operator op which gets applied to two type operands T_1 and T_2 . The type is equivalent to the type application $\text{op}[T_1, T_2]$. The infix operator op may be an arbitrary identifier, except for $*$, which is reserved as a postfix modifier denoting a repeated parameter type (§4.6.2).

All type infix operators have the same precedence; parentheses have to be used for grouping. The associativity (§6.12) of a type operator is determined as for term operators: type operators ending in a colon `:` are right-associative; all other operators are left-associative.

In a sequence of consecutive type infix operations $t_0 \text{ op}_1 t_1 \text{ op}_2 \dots \text{op}_n t_n$, all operators $\text{op}_1, \dots, \text{op}_n$ must have the same associativity. If they are all left-associative, the sequence is interpreted as $(\dots (t_0 \text{ op}_1 t_1) \text{ op}_2 \dots) \text{op}_n t_n$, otherwise it is interpreted as $t_0 \text{ op}_1 (t_1 \text{ op}_2 (\dots \text{op}_n t_n) \dots)$.

3.2.9 Function Types

Syntax:

```
Type ::= InfixType '=>' Type
      | '(' ['=>' Type] ')' '=>' Type
```

The type $(T_1, \dots, T_n) \Rightarrow U$ represents the set of function values that take arguments of types T_1, \dots, T_n and yield results of type U . In the case of exactly one argument type $T \Rightarrow U$ is a shorthand for $(T) \Rightarrow U$. The type $(\Rightarrow T) \Rightarrow U$ represents functions with call-by-name parameters (§4.6.1) of type T which yield results of type U . Function types associate to the right, e.g. $S \Rightarrow T \Rightarrow U$ is the same as $S \Rightarrow (T \Rightarrow U)$.

Function types are shorthands for class types that define apply functions. Specifically, the n -ary function type $(T_1, \dots, T_n) \Rightarrow U$ is a shorthand for the class type `Functionn[T1, ..., Tn, U]`. Such class types are defined in the Scala library for n between 0 and 9 as follows.

```
package scala
trait Functionn[-T1, ..., -Tn, +R] {
  def apply(x1: T1, ..., xn: Tn): R
  override def toString = "<function>"
}
```

Hence, function types are covariant (§4.5) in their result type and contravariant in their argument types.

A call-by-name function type $(\Rightarrow T) \Rightarrow U$ is a shorthand for the class type `ByNameFunction[T, U]`, which is defined as follows.

```
package scala
trait ByNameFunction[-T, +R] {
  def apply(x: => T): R
  override def toString = "<function>"
}
```

3.2.10 Existential Types

Syntax:

```
Type ::= InfixType ExistentialClauses
ExistentialClauses ::= 'forSome' '{' ExistentialDcl
                      {semi ExistentialDcl} '}'
ExistentialDcl ::= 'type' TypeDcl
                  | 'val' ValDcl
```

An existential type has the form $T \text{ forSome } \{Q\}$ where Q is a sequence of type

declarations §4.3. Let $t_1[tps_1] >: L_1 <: U_1, \dots, t_n[tps_n] >: L_n <: U_n$ be the types declared in Q (any of the type parameter sections $[tps_i]$ might be missing). The scope of each type t_i includes the type T and the existential clause Q . The type variables t_i are said to be *bound* in the type $T \text{ forSome } \{Q\}$. Type variables which occur in a type T but which are not bound in T are said to be *free* in T .

A *type instance* of $T \text{ forSome } \{Q\}$ is a type σU where σ is a substitution over t_1, \dots, t_n such that, for each i , $\sigma L_i <: \sigma t_i <: \sigma U_i$. The set of values denoted by the existential type $T \text{ forSome } \{Q\}$ is the union of the set of values of all its type instances.

A *skolemization* of $T \text{ forSome } \{Q\}$ is a type instance σT , where σ is the substitution $[t'_1/t_1, \dots, t'_n/t_n]$ and each t'_i is a fresh abstract type with lower bound σL_i and upper bound σU_i .

Simplification Rules

Existential types obey the following four equivalences:

1. Multiple for-clauses in an existential type can be merged. E.g., $T \text{ forSome } \{Q\} \text{ forSome } \{Q'\}$ is equivalent to $T \text{ forSome } \{Q; Q'\}$.
2. Unused quantifications can be dropped. E.g., $T \text{ forSome } \{Q; Q'\}$ where none of the types defined in Q' are referred to by T or Q , is equivalent to $T \text{ forSome } \{Q\}$.
3. An empty quantification can be dropped. E.g., $T \text{ forSome } \{ \}$ is equivalent to T .
4. An existential type $T \text{ forSome } \{Q\}$ where Q contains a clause **type** $t[tps] >: L <: U$ is equivalent to the type $T' \text{ forSome } \{Q\}$ where T' results from T by replacing every covariant occurrence (§4.5) of t in T by U and by replacing every contravariant occurrence of t in T by L .

Existential Quantification over Values

As a syntactic convenience, the bindings clause in an existential type may also contain value declarations **val** $x: T$. An existential type $T \text{ forSome } \{Q; \text{val } x: S; Q'\}$ is treated as a shorthand for the type $T' \text{ forSome } \{Q; \text{type } t <: S \text{ with Singleton}; Q'\}$, where t is a fresh type name and T' results from T by replacing every occurrence of x . **type** with t .

Placeholder Syntax for Existential Types

Syntax:

WildcardType ::= ' _ ' TypeBounds

Scala supports a placeholder syntax for existential types. A *wildcard type* is of the form $_>: L <: U$. Both bound clauses may be omitted. If a lower bound clause $>: L$ is missing, $>: \text{scala.Nothing}$ is assumed. If an upper bound clause $<: U$ is missing, $<: \text{scala.Any}$ is assumed. A wildcard type is a shorthand for an existentially quantified type variable, where the existential quantification is implicit.

The position of the existential quantification corresponding to a wildcard type occurrence is determined as follows. Let $T\langle_>: L <: U\rangle$ be the largest possible type expression containing the wildcard type $_>: L <: U$ such that every node on the path between the root of T and the wildcard type is of one of the syntactic categories `Type`, `InfixType`, `CompoundType`, `AnnotType`, `SimpleType`, `TypeArgs`, or `Types`. Then $T\langle_>: L <: U\rangle$ is taken to be equivalent to the existential type

$$T\langle t \rangle \text{ forSome } \{ \text{type } t >: L <: U \}$$

where t is some fresh type variable.

Example 3.2.5 Assume the class definitions

```
class Ref[T]
abstract class Outer { type T } .
```

Here are some examples of existential types:

```
Ref[T] forSome { type T <: java.lang.Number }
Ref[x.T] forSome { val x: Outer }
Ref[x_type # T] forSome { type x_type <: Outer with Singleton }
```

The last two types in this list are equivalent. Alternative formulations of these types using wildcard syntax are:

```
Ref[_ <: java.lang.Number]
Ref[( _ <: Outer with Singleton) # T]
```

Example 3.2.6 Assume a covariant type

```
class List[+T]
```

The type

```
List[T] forSome { type T <: java.lang.Number }
```

is equivalent (by simplification rule 4 above) to

```
List[java.lang.Number] forSome { type T <: java.lang.Number }
```

which is in turn equivalent (by simplification rules 2 and 3 above) to `List[java.lang.Number]`.

3.2.11 Primitive Types Defined in *Predef*

The object *Predef* is imported implicitly into every Scala program. It contains type definitions which establish the primitive types mentioned above as aliases of class types. Numeric and boolean types are equated with standard Scala classes. The *String* type is equated with the *String* class of the underlying host system. In a Java environment, *Predef* contains the following bindings, among others:

```
type byte    = scala.Byte
type short   = scala.Short
type char     = scala.Char
type int      = scala.Int
type long     = scala.Long
type float    = scala.Float
type double   = scala.Double
type boolean  = scala.Boolean
type String   = java.lang.String
```

3.3 Non-Value Types

The types explained in the following do not denote sets of values, nor do they appear explicitly in programs. They are introduced in this report as the internal types of defined identifiers.

3.3.1 Method Types

A method type is denoted internally as $(Ts)U$, where (Ts) is a sequence of types (T_1, \dots, T_n) for some $n \geq 0$ and U is a (value or method) type. This type represents named methods that take arguments of types T_1, \dots, T_n and that return a result of type U .

We let method types associate to the right: $(Ts_1)(Ts_2)U$ is treated as $(Ts_1)((Ts_2)U)$.

A special case are types of methods without any parameters. They are written here $\Rightarrow T$. Parameterless methods name expressions that are re-evaluated each time the parameterless method name is referenced.

Method types do not exist as types of values. If a method name is used as a value, its type is implicitly converted to a corresponding function type (§6.25).

Example 3.3.1 The declarations

```
def a: Int
def b (x: Int): Boolean
def c (x: Int) (y: String, z: String): String
```

produce the typings

```
a: => Int
b: (Int) Boolean
c: (Int) (String, String) String
```

3.3.2 Polymorphic Method Types

A polymorphic method type is denoted internally as $[tps]T$ where $[tps]$ is a type parameter section $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]$ for some $n \geq 0$ and T is a (value or method) type. This type represents named methods that take type arguments S_1, \dots, S_n which conform (§3.2.4) to the lower bounds L_1, \dots, L_n and the upper bounds U_1, \dots, U_n and that yield results of type T .

Example 3.3.2 The declarations

```
def empty[A]: List[A]
def union[A <: Comparable[A]] (x: Set[A], xs: Set[A]): Set[A]
```

produce the typings

```
empty : [A >: Nothing <: Any] List[A]
union : [A >: Nothing <: Comparable[A]] (x: Set[A], xs: Set[A]) Set[A] .
```

3.3.3 Type Constructors

A type constructor is represented internally much like a polymorphic method type. $[\pm a_1 >: L_1 <: U_1, \dots, \pm a_n >: L_n <: U_n] T$ represents a type that is expected by a type constructor parameter (§4.4) or an abstract type constructor binding (§4.3) with the corresponding type parameter clause.

Example 3.3.3 Consider this fragment of the `Iterable[+X]` class:

```
trait Iterable[+X] {
  def flatMap[newType[+X] <: Iterable[X], S](f: T => newType[S]): newType[S]
}
```

Conceptually, the type constructor `Iterable` is a name for the anonymous type `[+X] Iterable[X]`, which may be passed to the `newType` type constructor parameter in `flatMap`.

3.4 Base Types and Member Definitions

Types of class members depend on the way the members are referenced. Central here are three notions, namely:

1. the notion of the set of base types of a type T ,
2. the notion of a type T in some class C seen from some prefix type S ,
3. the notion of the set of member bindings of some type T .

These notions are defined mutually recursively as follows.

1. The set of *base types* of a type is a set of class types, given as follows.
 - The base types of a class type C with parents T_1, \dots, T_n are C itself, as well as the base types of the compound type $T_1 \text{ with } \dots \text{ with } T_n \{R\}$.
 - The base types of an aliased type are the base types of its alias.
 - The base types of an abstract type are the base types of its upper bound.
 - The base types of a parameterized type $C[T_1, \dots, T_n]$ are the base types of type C , where every occurrence of a type parameter a_i of C has been replaced by the corresponding parameter type T_i .
 - The base types of a singleton type $p.\text{type}$ are the base types of the type of p .
 - The base types of a compound type $T_1 \text{ with } \dots \text{ with } T_n \{R\}$ are the *reduced union* of the base classes of all T_i 's. This means: Let the multi-set \mathcal{S} be the multi-set-union of the base types of all T_i 's. If \mathcal{S} contains several type instances of the same class, say $S^i \# C[T_1^i, \dots, T_n^i]$ ($i \in I$), then all those instances are replaced by one of them which conforms to all others. It is an error if no such instance exists. It follows that the reduced union, if it exists, produces a set of class types, where different types are instances of different classes.
 - The base types of a type selection $S \# T$ are determined as follows. If T is an alias or abstract type, the previous clauses apply. Otherwise, T must be a (possibly parameterized) class type, which is defined in some class B . Then the base types of $S \# T$ are the base types of T in B seen from the prefix type S .
 - The base types of an existential type $T \text{ forSome } \{Q\}$ are all types $S \text{ forSome } \{Q\}$ where S is a base type of T .

2. The notion of a type T in class C seen from some prefix type S makes sense only if the prefix type S has a type instance of class C as a base type, say $S' \# C[T_1, \dots, T_n]$. Then we define as follows.

- If $S = \epsilon.\text{type}$, then T in C seen from S is T itself.
- Otherwise, if S is an existential type $S' \text{ forSome } \{Q\}$, and T in C seen from S' is T' , then T in C seen from S is $T' \text{ forSome } \{Q\}$.
- Otherwise, if T is the i 'th type parameter of some class D , then
 - If S has a base type $D[U_1, \dots, U_n]$, for some type parameters $[U_1, \dots, U_n]$, then T in C seen from S is U_i .

- Otherwise, if C is defined in a class C' , then T in C seen from S is the same as T in C' seen from S' .
- Otherwise, if C is not defined in another class, then T in C seen from S is T itself.
- Otherwise, if T is the singleton type $D.\mathbf{this.type}$ for some class D then
 - If D is a subclass of C and S has a type instance of class D among its base types, then T in C seen from S is S .
 - Otherwise, if C is defined in a class C' , then T in C seen from S is the same as T in C' seen from S' .
 - Otherwise, if C is not defined in another class, then T in C seen from S is T itself.
- If T is some other type, then the described mapping is performed to all its type components.

If T is a possibly parameterized class type, where T 's class is defined in some other class D , and S is some prefix type, then we use “ T seen from S ” as a shorthand for “ T in D seen from S ”.

3. The *member bindings* of a type T are all bindings d such that there exists a type instance of some class C among the base types of T and there exists a definition or declaration d' in C such that d results from d' by replacing every type T' in d' by T' in C seen from T .

The *definition* of a type projection $S\#t$ is the member binding d_t of the type t in S . In that case, we also say that $S\#t$ is *defined by* d_t .

3.5 Relations between types

We define two relations between types.

<i>Type equivalence</i>	$T \equiv U$	T and U are interchangeable in all contexts.
<i>Conformance</i>	$T <: U$	Type T conforms to type U .

3.5.1 Type Equivalence

Equivalence (\equiv) between types is the smallest congruence³ such that the following holds:

- If t is defined by a type alias **type** $t = T$, then t is equivalent to T .
- If a path p has a singleton type $q.\mathbf{type}$, then $p.\mathbf{type} \equiv q.\mathbf{type}$.

³ A congruence is an equivalence relation which is closed under formation of contexts

- If O is defined by an object definition, and p is a path consisting only of package or object selectors and ending in O , then $O.\text{this.type} \equiv p.\text{type}$.
- Two compound types (§3.2.7) are equivalent if the sequences of their component are pairwise equivalent, and occur in the same order, and their refinements are equivalent. Two refinements are equivalent if they bind the same names and the modifiers, types and bounds of every declared entity are equivalent in both refinements.
- Two method types (§3.3.1) are equivalent if they have equivalent result types, both have the same number of parameters, and corresponding parameters have equivalent types. Note that the names of parameters do not matter for method type equivalence.
- Two polymorphic method types (§3.3.2) are equivalent if they have the same number of type parameters, and, after renaming one set of type parameters by another, the result types as well as lower and upper bounds of corresponding type parameters are equivalent.
- Two existential types (§3.2.10) are equivalent if they have the same number of quantifiers, and, after renaming one list of type quantifiers by another, the quantified types as well as lower and upper bounds of corresponding quantifiers are equivalent.
- Two type constructors (§3.3.3) are equivalent if they have the same number of type parameters, and, after renaming one list of type parameters by another, the result types as well as variances, lower and upper bounds of corresponding type parameters are equivalent.

3.5.2 Conformance

The conformance relation ($<:$) is the smallest transitive relation that satisfies the following conditions.

- Conformance includes equivalence. If $T \equiv U$ then $T <: U$.
- For every value type T , $\text{scala.Nothing} <: T <: \text{scala.Any}$.
- For every type constructor T (with any number of type parameters), $\text{scala.Nothing} <: T <: \text{scala.Any}$.
- For every class type T such that $T <: \text{scala.AnyRef}$ and not $T <: \text{scala.NotNull}$ one has $\text{scala.Null} <: T$.
- A type variable or abstract type t conforms to its upper bound and its lower bound conforms to t .
- A class type or parameterized type conforms to any of its base-types.
- A singleton type $p.\text{type}$ conforms to the type of the path p .
- A singleton type $p.\text{type}$ conforms to the type scala.Singleton .

- A type projection $T\#t$ conforms to $U\#t$ if T conforms to U .
- A parameterized type $T[T_1, \dots, T_n]$ conforms to $T[U_1, \dots, U_n]$ if the following three conditions hold for $i = 1, \dots, n$.
 - If the i 'th type parameter of T is declared covariant, then $T_i <: U_i$.
 - If the i 'th type parameter of T is declared contravariant, then $U_i <: T_i$.
 - If the i 'th type parameter of T is declared neither covariant nor contravariant, then $U_i \equiv T_i$.
- A compound type T_1 **with** ... **with** T_n $\{R\}$ conforms to each of its component types T_i .
- If $T <: U_i$ for $i = 1, \dots, n$ and for every binding d of a type or value x in R there exists a member binding of x in T which subsumes d , then T conforms to the compound type U_1 **with** ... **with** U_n $\{R\}$.
- The existential type T **forSome** $\{Q\}$ conforms to U if its skolemization (§3.2.10) conforms to U .
- The type T conforms to the existential type U **forSome** $\{Q\}$ if T conforms to one of the type instances (§3.2.10) of U **forSome** $\{Q\}$.
- If $T_i \equiv T'_i$ for $i = 1, \dots, n$ and U conforms to U' then the method type $(T_1, \dots, T_n)U$ conforms to $(T'_1, \dots, T'_n)U'$.
- The polymorphic type $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]T$ conforms to the polymorphic type $[a_1 >: L'_1 <: U'_1, \dots, a_n >: L'_n <: U'_n]T'$ if, assuming $L'_1 <: a_1 <: U'_1, \dots, L'_n <: a_n <: U'_n$ one has $T <: T'$ and $L_i <: L'_i$ and $U'_i <: U_i$ for $i = 1, \dots, n$.
- Type constructors T and T' follow a similar discipline. We characterize T and T' by their type parameter clauses $[a_1, \dots, a_n]$ and $[a'_1, \dots, a'_n]$, where an a_i or a'_i may include a variance annotation, a higher-order type parameter clause, and bounds. Then, T conforms to T' if any list $[t_1, \dots, t_n]$ – with declared variances, bounds and higher-order type parameter clauses – of valid type arguments for T' is also a valid list of type arguments for T and $T[t_1, \dots, t_n] <: T'[t_1, \dots, t_n]$. Note that this entails that:
 - The bounds on a_i must be weaker than the corresponding bounds declared for a'_i .
 - The variance of a_i must match the variance of a'_i , where covariance matches covariance, contravariance matches contravariance and any variance matches invariance.
 - Recursively, these restrictions apply to the corresponding higher-order type parameter clauses of a_i and a'_i .

A declaration or definition in some compound type of class type C *subsumes* another declaration of the same name in some compound type or class type C' , if one of the following holds.

- A value declaration or definition that defines a name x with type T subsumes a value or method declaration that defines x with type T' , provided $T <: T'$.
- A method declaration or definition that defines a name x with type T subsumes a method declaration that defines x with type T' , provided $T <: T'$.
- A type alias **type** $t[T_1, \dots, T_n] = T$ subsumes a type alias **type** $t[T_1, \dots, T_n] = T'$ if $T \equiv T'$.
- A type declaration **type** $t[T_1, \dots, T_n] >: L <: U$ subsumes a type declaration **type** $t[T_1, \dots, T_n] >: L' <: U'$ if $L' <: L$ and $U <: U'$.
- A type or class definition that binds a type name t subsumes an abstract type declaration **type** $t[T_1, \dots, T_n] >: L <: U$ if $L <: t <: U$.

The ($<:$) relation forms pre-order between types, i.e. it is transitive and reflexive. *least upper bounds* and *greatest lower bounds* of a set of types are understood to be relative to that order.

Note. The least upper bound or greatest lower bound of a set of types does not always exist. For instance, consider the class definitions

```
class A[+T] {}
class B extends A[B]
class C extends A[C]
```

Then the types $A[\text{Any}]$, $A[A[\text{Any}]]$, $A[A[A[\text{Any}]]]$, \dots form a descending sequence of upper bounds for B and C. The least upper bound would be the infinite limit of that sequence, which does not exist as a Scala type. Since cases like this are in general impossible to detect, a Scala compiler is free to reject a term which has a type specified as a least upper or greatest lower bound, and that bound would be more complex than some compiler-set limit⁴.

The least upper bound or greatest lower bound might also not be unique. For instance $A \text{ with } B$ and $B \text{ with } A$ are both least upper bounds of A and B. If there are several least upper bounds or greatest lower bounds, the Scala compiler is free to pick any one of them.

3.6 Type Erasure

A type is called *generic* if it contains type arguments or type variables. *Type erasure* is a mapping from (possibly generic) types to non-generic types. We write $|T|$ for the erasure of type T . The erasure mapping is defined as follows.

⁴The current Scala compiler limits the nesting level of parameterization in such bounds to be at most two deeper than the maximum nesting level of the operand types

- The erasure of an alias type is the erasure of its right-hand side.
- The erasure of an abstract type is the erasure of its upper bound.
- The erasure of the parameterized type `scala.Array[T1]` is `scala.Array[|T1|]`.
- The erasure of every other parameterized type $T[T_1, \dots, T_n]$ is $|T|$.
- The erasure of a singleton type $p.\mathbf{type}$ is the erasure of the type of p .
- The erasure of a type projection $T\#x$ is $|T|\#x$.
- The erasure of a compound type $T_1 \mathbf{with} \dots \mathbf{with} T_n \{R\}$ is $|T_1|$.
- The erasure of an existential type $T \mathbf{forSome} \{Q\}$ is $|T|$.

Chapter 4

Basic Declarations and Definitions

Syntax:

```
Dcl          ::= 'val' ValDcl
              | 'var' VarDcl
              | 'def' FunDcl
              | 'type' {nl} TypeDcl
PatVarDef    ::= 'val' PatDef
              | 'var' VarDef
Def          ::= PatVarDef
              | 'def' FunDef
              | 'type' {nl} TypeDef
              | TmplDef
```

A *declaration* introduces names and assigns them types. It can form part of a class definition (§5.1) or of a refinement in a compound type (§3.2.7).

A *definition* introduces names that denote terms or types. It can form part of an object or class definition or it can be local to a block. Both declarations and definitions produce *bindings* that associate type names with type definitions or bounds, and that associate term names with types.

The scope of a name introduced by a declaration or definition is the whole statement sequence containing the binding. However, there is a restriction on forward references in blocks: In a statement sequence $s_1 \dots s_n$ making up a block, if a simple name in s_i refers to an entity defined by s_j where $j \geq i$, then none of the definitions between and including s_i and s_j may be a value or variable definition.

4.1 Value Declarations and Definitions

Syntax:

```

Dcl      ::= 'val' ValDcl
ValDcl   ::= ids ':' Type
Def      ::= 'val' PatDef
PatDef   ::= Pattern2 {',' Pattern2} [':' Type] '=' Expr
ids      ::= id {',' id}

```

A value declaration **val** $x: T$ introduces x as a name of a value of type T .

A value definition **val** $x: T = e$ defines x as a name of the value that results from the evaluation of e . The type T may be omitted, in which case the packed type (§6.1) of expression e is assumed. If a type T is given, then e is expected to conform to it.

Evaluation of the value definition implies evaluation of its right-hand side e , unless it has the modifier **lazy**. The effect of the value definition is to bind x to the value of e converted to type T . A **lazy** value definition evaluates its right hand side e the first time the value is accessed.

Value definitions can alternatively have a pattern (§8.1) as left-hand side. If p is some pattern other than a simple name or a name followed by a colon and a type, then the value definition **val** $p = e$ is expanded as follows:

1. If the pattern p has bound variables x_1, \dots, x_n , where $n > 1$:

```

val $x = e match { case p => { $x_1, \dots, x_n$ } }
val  $x_1 = $x._1$ 
...
val  $x_n = $x._n$  .

```

Here, $$x$ is a fresh name.

2. If p has a unique bound variable x :

```

val  $x = e$  match { case p =>  $x$  }

```

3. If p has no bound variables:

```

 $e$  match { case p => () }

```

Example 4.1.1 The following are examples of value definitions

```

val pi = 3.1415
val pi: Double = 3.1415    // equivalent to first definition
val Some(x) = f()          // a pattern definition
val x :: xs = mylist       // an infix pattern definition

```

The last two definitions have the following expansions.

```

val x = f() match { case Some(x) => x }

val x$ = mylist match { case x :: xs => {x, xs} }

```

```

val x = x$._1
val xs = x$._2

```

A value declaration **val** $x_1, \dots, x_n: T$ is a shorthand for the sequence of value declarations **val** $x_1: T$; ...; **val** $x_n: T$. A value definition **val** $p_1, \dots, p_n = e$ is a shorthand for the sequence of value definitions **val** $p_1 = e$; ...; **val** $p_n = e$. A value definition **val** $p_1, \dots, p_n: T = e$ is a shorthand for the sequence of value definitions **val** $p_1: T = e$; ...; **val** $p_n: T = e$.

4.2 Variable Declarations and Definitions

Syntax:

```

Decl      ::= 'var' VarDecl
Def        ::= 'var' VarDef
VarDecl    ::= ids ':' Type
VarDef     ::= PatDef
            | ids ':' Type '=' '_'

```

A variable declaration **var** $x: T$ is equivalent to declarations of a *getter function* x and a *setter function* $x_=$, defined as follows:

```

def x: T
def x_= (y: T): Unit

```

An implementation of a class containing variable declarations may define these variables using variable definitions, or it may define setter and getter functions directly.

A variable definition **var** $x: T = e$ introduces a mutable variable with type T and initial value as given by the expression e . The type T can be omitted, in which case the type of e is assumed. If T is given, then e is expected to conform to it (§6.1).

Variable definitions can alternatively have a pattern (§8.1) as left-hand side. A variable definition **var** $p = e$ where p is a pattern other than a simple name or a name followed by a colon and a type is expanded in the same way (§4.1) as a value definition **val** $p = e$, except that the free names in p are introduced as mutable variables, not values.

A variable definition **var** $x: T = _$ can appear only as a member of a template. It introduces a mutable field with type T and a default initial value. The default value depends on the type T as follows:

0 if T is Int or one of its subrange types,
 0L if T is Long,
 0.0f if T is Float,
 0.0d if T is Double,
false if T is Boolean,
 {} if T is Unit,
null for all other types T .

When they occur as members of a template, both forms of variable definition also introduce a getter function x which returns the value currently assigned to the variable, as well as a setter function $x_=$ which changes the value currently assigned to the variable. The functions have the same signatures as for a variable declaration. The template then has these getter and setter functions as members, whereas the original variable cannot be accessed directly as a template member.

Example 4.2.1 The following example shows how *properties* can be simulated in Scala. It defines a class `TimeOfDayVar` of time values with updatable integer fields representing hours, minutes, and seconds. Its implementation contains tests that allow only legal values to be assigned to these fields. The user code, on the other hand, accesses these fields just like normal variables.

```

class TimeOfDayVar {
  private var h: Int = 0
  private var m: Int = 0
  private var s: Int = 0

  def hours          = h
  def hours_= (h: Int) = if (0 <= h && h < 24) this.h = h
                        else throw new DateError()

  def minutes        = m
  def minutes_= (m: Int) = if (0 <= m && m < 60) this.m = m
                        else throw new DateError()

  def seconds        = s
  def seconds_= (s: Int) = if (0 <= s && s < 60) this.s = s
                        else throw new DateError()
}
val d = new TimeOfDayVar
d.hours = 8; d.minutes = 30; d.seconds = 0
d.hours = 25 // throws a DateError exception

```

A variable declaration `var x_1, \dots, x_n : T` is a shorthand for the sequence of variable declarations `var x_1 : T ; ...; var x_n : T` . A variable definition `var x_1, \dots, x_n = e` is a shorthand for the sequence of variable definitions `var x_1 = e ; ...; var x_n = e` . A variable definition

var $x_1, \dots, x_n : T = e$ is a shorthand for the sequence of variable definitions
var $x_1 : T = e$; ...; **var** $x_n : T = e$.

4.3 Type Declarations and Type Aliases

Syntax:

```

Dcl      ::= 'type' {nl} TypeDcl
TypeDcl  ::= id [TypeParamClause] ['>:' Type] ['<:' Type]
Def      ::= type {nl} TypeDef
TypeDef  ::= id [TypeParamClause] '=' Type

```

A *type declaration* **type** $t[tps] >: L <: U$ declares t to be an abstract type with lower bound type L and upper bound type U . If the type parameter clause $[tps]$ is omitted, t abstracts over a first-order type, otherwise t stands for a type constructor that accepts type arguments as described by the type parameter clause.

If a type declaration appears as a member declaration of a type, implementations of the type may implement t with any type T for which $L <: T <: U$. It is a compile-time error if L does not conform to U . Either or both bounds may be omitted. If the lower bound L is absent, the bottom type `scala.Nothing` is assumed. If the upper bound U is absent, the top type `scala.Any` is assumed.

A type constructor declaration imposes additional restrictions on the concrete types for which t may stand. Besides the bounds L and U , the type parameter clause may impose higher-order bounds and variances, as governed by the conformance of type constructors (§3.5.2).

The scope of a type parameter extends over the bounds $>: L <: U$ and the type parameter clause tps itself. A higher-order type parameter clause (of an abstract type constructor tc) has the same kind of scope, restricted to the declaration of the type parameter tc .

To illustrate nested scoping, these declarations are all equivalent:
type $t[m[x] <: \text{Bound}[x], \text{Bound}[x]]$, **type** $t[m[x] <: \text{Bound}[x], \text{Bound}[y]]$
and **type** $t[m[x] <: \text{Bound}[x], \text{Bound}[_]]$, as the scope of, e.g., the type parameter of m is limited to the declaration of m . In all of them, t is an abstract type member that abstracts over two type constructors: m stands for a type constructor that takes one type parameter and that must be a subtype of *Bound*, t 's second type constructor parameter. `t[MutableList, Iterable]` is a valid use of t .

A *type alias* **type** $t = T$ defines t to be an alias name for the type T . The left hand side of a type alias may have a type parameter clause, e.g. **type** $t[tps] = T$. The scope of a type parameter extends over the right hand side T and the type parameter clause tps itself.

The scope rules for definitions (§4) and type parameters (§4.6) make it possible that

a type name appears in its own bound or in its right-hand side. However, it is a static error if a type alias refers recursively to the defined type constructor itself. That is, the type T in a type alias `type $t[tps]$ = T` may not refer directly or indirectly to the name t . It is also an error if an abstract type is directly or indirectly its own upper or lower bound.

Example 4.3.1 The following are legal type declarations and definitions:

```
type IntList = List[Integer]
type T <: Comparable[T]
type Two[A] = Tuple2[A, A]
type MyCollection[+X] <: Iterable[X]
```

The following are illegal:

```
type Abs = Comparable[Abs]           // recursive type alias

type S <: T                           // S, T are bounded by themselves.
type T <: S

type T >: Comparable[T.That]         // Cannot select from T.
                                     // T is a type, not a value
type MyCollection <: Iterable       // Type constructor members must explicitly state the
```

If a type alias `type $t[tps]$ = S` refers to a class type S , the name t can also be used as a constructor for objects of type S .

Example 4.3.2 The `Predef` object contains a definition which establishes `Pair` as an alias of the parameterized class `Tuple2`:

```
type Pair[+A, +B] = Tuple2[A, B]
```

As a consequence, for any two types S and T , the type `Pair[S , T]` is equivalent to the type `Tuple2[S , T]`. `Pair` can also be used as a constructor instead of `Tuple2`. Furthermore, because `Tuple2` is a case class (§5.3.2), `Pair2` is also an alias for the case class factory `Tuple2`, and this holds for in expressions as well as patterns. Hence, the following are all legal uses of `Pair`.

```
val x: Pair[Int, String] = new Pair(1, "abc")
val y: Pair[String, Int] = x match {
  case Pair(i, s) => Pair(z + i, i * i)
}
```

4.4 Type Parameters

Syntax:


```

TypeParamClause ::= '[' VariantTypeParam {',' VariantTypeParam} ']'
VariantTypeParam ::= ['+' | '-'] TypeParam
TypeParam        ::= id ['>:' Type] ['<:' Type] ['<%' Type]

```

Type parameters appear in type definitions, class definitions, and function definitions. In this section we consider only type parameter definitions with lower bounds $>: L$ and upper bounds $<: U$ whereas a discussion of view bounds $< \% U$ is deferred to Section 7.4.

The most general form of a first-order type parameter is $\pm t >: L <: U$. Here, L , and U are lower and upper bounds that constrain possible type arguments for the parameter. It is a compile-time error if L does not conform to U . \pm is a *variance*, i.e. an optional prefix of either $+$, or $-$.

The names of all type parameters must be pairwise different in their enclosing type parameter clause. The scope of a type parameter includes in each case the whole type parameter clause. Therefore it is possible that a type parameter appears as part of its own bounds or the bounds of other type parameters in the same clause. However, a type parameter may not be bounded directly or indirectly by itself.

A type constructor parameter adds a nested type parameter clause to the type parameter. The most general form of a type constructor parameter is $\pm t[tps] >: L <: U$.

The above scoping restrictions are generalized to the case of nested type parameter clauses, which declare higher-order type parameters. Higher-order type parameters (the type parameters of a type parameter t) are only visible in their immediately surrounding parameter clause (possibly including clauses at a deeper nesting level) and in the bounds of t . Therefore, their names must only be pairwise different from the names of other visible parameters. Since the names of higher-order type parameters are thus often irrelevant, they may be denoted with a $'_'$, which is nowhere visible.

Example 4.4.1 Here are some well-formed type parameter clauses:

```

[S, T]
[Ex <: Throwable]
[A <: Comparable[B], B <: A]
[A, B >: A, C >: A <: B]
[M[X], N[X]]
[M[_], N[_]] // equivalent to previous clause
[M[X <: Bound[X]], Bound[_]]
[M[+X] <: Iterable[X]]

```

The following type parameter clauses are illegal:

```

[A >: A] // illegal, 'A' has itself as bound
[A <: B, B <: C, C <: A] // illegal, 'A' has itself as bound

```

```
[A, B, C >: A <: B]      // illegal lower bound 'A' of 'C' does
                          // not conform to upper bound 'B'.
```

4.5 Variance Annotations

Variance annotations indicate how instances of parameterized types vary with respect to subtyping (§3.5.2). A '+' variance indicates a covariant dependency, a '-' variance indicates a contravariant dependency, and a missing variance indication indicates an invariant dependency.

A variance annotation constrains the way the annotated type variable may appear in the type or class which binds the type parameter. In a type definition **type** $T[tps] = S$, or a type declaration **type** $T[tps] >: L <: U$ type parameters labeled '+' must only appear in covariant position whereas type parameters labeled '-' must only appear in contravariant position. Analogously, for a class definition **class** $C[tps](ps)$ **extends** T $x: S \Rightarrow \dots @$, type parameters labeled '+' must only appear in covariant position in the self type S and the template T , whereas type parameters labeled '-' must only appear in contravariant position.

The variance position of a type parameter in a type or template is defined as follows. Let the opposite of covariance be contravariance, and the opposite of invariance be itself. The top-level of the type or template is always in covariant position. The variance position changes at the following constructs.

- The variance position of a method parameter is the opposite of the variance position of the enclosing parameter clause.
- The variance position of a type parameter is the opposite of the variance position of the enclosing type parameter clause.
- The variance position of the lower bound of a type declaration or type parameter is the opposite of the variance position of the type declaration or parameter.
- The right hand side S of a type alias **type** $T[tps] = S$ is always in invariant position.
- The type of a mutable variable is always in invariant position.
- The prefix S of a type selection $S\#T$ is always in invariant position.
- For a type argument T of a type $S[\dots T \dots]$: If the corresponding type parameter is invariant, then T is in invariant position. If the corresponding type parameter is contravariant, the variance position of T is the opposite of the variance position of the enclosing type $S[\dots T \dots]$.

References to the type parameters in object-private values, variables, or methods of the class are not checked for their variance position. In these members the type parameter may appear anywhere without restricting its legal variance annotations.

Example 4.5.1 The following variance annotation is legal.

```
abstract class P[+A, +B] {
  def fst: A; def snd: B
}
```

With this variance annotation, elements of type P subtype covariantly with respect to their arguments. For instance,

```
P[IOException, String] <: P[Throwable, AnyRef] .
```

If we make the elements of P mutable, the variance annotation becomes illegal.

```
abstract class Q[+A, +B](x: A, y: B) {
  var fst: A = x           // **** error: illegal variance:
  var snd: B = y           // 'A', 'B' occur in invariant position.
}
```

If the mutable variables are object-private, the class definition becomes legal again:

```
abstract class R[+A, +B](x: A, y: B) {
  private[this] var fst: A = x      // OK
  private[this] var snd: B = y      // OK
}
```

Example 4.5.2 The following variance annotation is illegal, since a appears in contravariant position in the parameter of `append`:

```
abstract class Vector[+A] {
  def append(x: Vector[A]): Vector[A]
    // **** error: illegal variance:
    // 'A' occurs in contravariant position.
}
```

The problem can be avoided by generalizing the type of `append` by means of a lower bound:

```
abstract class Vector[+A] {
  def append[B >: A](x: Vector[B]): Vector[B]
}
```

Example 4.5.3 Here is a case where a contravariant type parameter is useful.

```
abstract class OutputChannel[-A] {
  def write(x: A): Unit
}
```

With that annotation, we have that `OutputChannel[AnyRef]` conforms to `OutputChannel[String]`. That is, a channel on which one can write any object can substitute for a channel on which one can write only strings.

4.6 Function Declarations and Definitions

Syntax:

```

Dcl      ::= 'def' FunDcl
FunDcl   ::= FunSig ':' Type
Def      ::= 'def' FunDef
FunDef   ::= FunSig [':' Type] '=' Expr
FunSig   ::= id [FunTypeParamClause] ParamClauses
FunTypeParamClause ::= '[' TypeParam {',' TypeParam} ']'
ParamClauses ::= {ParamClause} [[nl] '(' 'implicit' Params ')']
ParamClause ::= [nl] '(' [Params] ')'
Params    ::= Param {',' Param}
Param     ::= {Annotation} id [':' ParamType]
ParamType ::= Type
           | '=>' Type
           | Type '*'

```

A function declaration has the form **def** *fpsig*: *T*, where *f* is the function's name, *psig* is its parameter signature and *T* is its result type. A function definition **def** *fpsig*: *T* = *e* also includes a *function body* *e*, i.e. an expression which defines the function's result. A parameter signature consists of an optional type parameter clause [*tps*], followed by zero or more value parameter clauses (*ps*₁)...(*ps*_{*n*}). Such a declaration or definition introduces a value with a (possibly polymorphic) method type whose parameter types and result type are as given.

The type of the function body is expected to conform (§6.1) to the function's declared result type, if one is given. If the function definition is not recursive, the result type may be omitted, in which case it is determined from the packed type of the function body.

A type parameter clause *tps* consists of one or more type declarations (§4.3), which introduce type parameters, possibly with bounds. The scope of a type parameter includes the whole signature, including any of the type parameter bounds as well as the function body, if it is present.

A value parameter clause *ps* consists of zero or more formal parameter bindings such as *x*: *T*, which bind value parameters and associate them with their types. The scope of a formal value parameter name *x* is the function body, if one is given. Both type parameter names and value parameter names must be pairwise distinct.

4.6.1 By-Name Parameters

Syntax:

ParamType ::= '=>' Type

The type of a value parameter may be prefixed by `=>`, e.g. `x: => T`. The type of such a parameter is then the parameterless method type `=> T`. This indicates that the corresponding argument is not evaluated at the point of function application, but instead is evaluated at each use within the function. That is, the argument is evaluated using *call-by-name*.

Example 4.6.1 The declaration

```
def whileLoop (cond: => Boolean) (stat: => Unit): Unit
```

indicates that both parameters of `whileLoop` are evaluated using call-by-name.

4.6.2 Repeated Parameters

Syntax:

ParamType ::= Type '*'

The last value parameter of a parameter section may be suffixed by `*`, e.g. `(..., x: T*)`. The type of such a *repeated* parameter inside the method is then the sequence type `scala.Seq[T]`. Methods with repeated parameters `T*` take a variable number of arguments of type `T`. That is, if a method m with type $(T_1, \dots, T_n, S^*)U$ is applied to arguments (e_1, \dots, e_k) where $k \geq n$, then m is taken in that application to have type $(T_1, \dots, T_n, S, \dots, S)U$, with $k - n$ occurrences of type `S`. The only exception to this rule is if the last argument is marked to be a *sequence argument* via a `_*` type annotation. If m above is applied to arguments $(e_1, \dots, e_n, e': _*)$, then the type of m in that application is taken to be $(T_1, \dots, T_n, \text{scala.Seq}[S])$.

Example 4.6.2 The following method definition computes the sum of a variable number of integer arguments.

```
def sum(args: Int*) = {
  var result = 0
  for (arg <- args.elements) result += arg
  result
}
```

The following applications of this method yield 0, 1, 6, in that order.

```
sum()
```

```
sum(1)
sum(1, 2, 3)
```

Furthermore, assume the definition:

```
val xs = List(1, 2, 3)
```

The following applications method `sum` is ill-formed:

```
sum(xs)          // ***** error: expected: Int, found: List[Int]
```

By contrast, the following application is well formed and yields again the result 6:

```
sum(xs: _*)
```

4.6.3 Procedures

Syntax:

```
FunDecl  ::= FunSig
FunDef   ::= FunSig [nl] '{' Block '}'
```

Special syntax exists for procedures, i.e. functions that return the `Unit` value `{}`. A procedure declaration is a function declaration where the result type is omitted. The result type is then implicitly completed to the `Unit` type. E.g., `def f(ps)` is equivalent to `def f(ps): Unit`.

A procedure definition is a function definition where the result type and the equals sign are omitted; its defining expression must be a block. E.g., `def f(ps) {stats}` is equivalent to `def f(ps): Unit = {stats}`.

Example 4.6.3 Here is a declaration and a definition of a procedure named `write`:

```
trait Writer {
  def write(str: String)
}
object Terminal extends Writer {
  def write(str: String) { System.out.println(str) }
}
```

The code above is implicitly completed to the following code:

```
trait Writer {
  def write(str: String): Unit
}
object Terminal extends Writer {
  def write(str: String): Unit = { System.out.println(str) }
}
```

4.6.4 Method Return Type Inference

A class member definition m that overrides some other function m' in a base class of C may leave out the return type, even if it is recursive. In this case, the return type R' of the overridden function m' , seen as a member of C , is taken as the return type of m for each recursive invocation of m . That way, a type R for the right-hand side of m can be determined, which is then taken as the return type of m . Note that R may be different from R' , as long as R conforms to R' .

Example 4.6.4 Assume the following definitions:

```
trait I {
  def factorial(x: Int): Int
}
class C extends I {
  def factorial(x: Int) = if (x == 0) 1 else x * factorial(x - 1)
}
```

Here, it is OK to leave out the result type of factorial in C, even though the method is recursive.

4.7 Import Clauses

Syntax:

```
Import      ::= 'import' ImportExpr {',' ImportExpr}
ImportExpr  ::= StableId '.' (id | '_' | ImportSelectors)
ImportSelectors ::= '{' {ImportSelector ','}
                (ImportSelector | '_') '}'
ImportSelector ::= id ['=>' id | '=>' '_']
```

An import clause has the form **import** $p.I$ where p is a stable identifier (§3.1) and I is an import expression. The import expression determines a set of names of members of p which are made available without qualification. The most general form of an import expression is a list of *import selectors*

$$\{ x_1 \Rightarrow y_1, \dots, x_n \Rightarrow y_n, - \} .$$

for $n \geq 0$, where the final wildcard '_' may be absent. It makes available each member $p.x_i$ under the unqualified name y_i . I.e. every import selector $x_i \Rightarrow y_i$ renames $p.x_i$ to y_i . If a final wildcard is present, all members z of p other than x_1, \dots, x_n are also made available under their own unqualified names.

Import selectors work in the same way for type and term members. For instance, an import clause **import** $p.\{x \Rightarrow y\}$ renames the term name $p.x$ to the term name

y and the type name $p.x$ to the type name y . At least one of these two names must reference a member of p .

If the target in an import selector is a wildcard, the import selector hides access to the source member. For instance, the import selector $x \Rightarrow _$ “renames” x to the wildcard symbol (which is inaccessible as a name in user programs), and thereby effectively prevents unqualified access to x . This is useful if there is a final wildcard in the same import selector list, which imports all members not mentioned in previous import selectors.

The scope of a binding introduced by an import-clause starts immediately after the import clause and extends to the end of the enclosing block, template, package clause, or compilation unit, whichever comes first.

Several shorthands exist. An import selector may be just a simple name x . In this case, x is imported without renaming, so the import selector is equivalent to $x \Rightarrow x$. Furthermore, it is possible to replace the whole import selector list by a single identifier or wildcard. The import clause **import** $p.x$ is equivalent to **import** $p.\{x\}$, i.e. it makes available without qualification the member x of p . The import clause **import** $p._$ is equivalent to **import** $p.\{_\}$, i.e. it makes available without qualification all members of p (this is analogous to **import** $p.*$ in Java).

An import clause with multiple import expressions **import** $p_1.I_1, \dots, p_n.I_n$ is interpreted as a sequence of import clauses **import** $p_1.I_1$; ...; **import** $p_n.I_n$.

Example 4.7.1 Consider the object definition:

```
object M {
  def z = 0, one = 1
  def add(x: Int, y: Int): Int = x + y
}
```

Then the block

```
{ import M.{one, z => zero, _}; add(zero, one) }
```

is equivalent to the block

```
{ M.add(M.z, M.one) } .
```


Chapter 5

Classes and Objects

Syntax:

```
TplDef ::= ['case'] 'class' ClassDef
        | ['case'] 'object' ObjectDef
        | 'trait' TraitDef
```

Classes (§5.3) and objects (§5.4) are both defined in terms of *templates*.

5.1 Templates

Syntax:

```
ClassTemplate ::= [EarlyDefs] ClassParents [TemplateBody]
TraitTemplate ::= [EarlyDefs] TraitParents [TemplateBody]
ClassParents  ::= Constr {'with' AnnotType}
TraitParents  ::= AnnotType {'with' AnnotType}
TemplateBody  ::= [nl] '{' [SelfType] TemplateStat {semi TemplateStat} '}'
SelfType      ::= id [':' Type] '=>'
                |   this ':' Type '=>'
```

A template defines the type signature, behavior and initial state of a trait or class of objects or of a single object. Templates form part of instance creation expressions, class definitions, and object definitions. A template *sc with* mt_1 **with** ... **with** mt_n {*stats*} consists of a constructor invocation *sc* which defines the template's *superclass*, trait references mt_1, \dots, mt_n ($n \geq 0$), which define the template's *traits*, and a statement sequence *stats* which contains initialization code and additional member definitions for the template.

Each trait reference mt_i must denote a trait (§5.3.3). By contrast, the superclass constructor *sc* normally refers to a class which is not a trait. It is possible to write

a list of parents that starts with a trait reference, e.g. `mt1 with ... with mtn`. In that case the list of parents is implicitly extended to include the supertype of `mt1` as first parent type. The new supertype must have at least one constructor that does not take parameters. In the following, we will always assume that this implicit extension has been performed, so that the first parent class of a template is a regular superclass constructor, not a trait reference.

The list of parents of every class is also always implicitly extended by a reference to the `scala.ScalaObject` trait as last mixin. E.g.

```
sc with mt1 with ... with mtn {stats}
```

becomes

```
mt1 with ... with mtn {stats} with ScalaObject {stats} .
```

The list of parents of a template must be well-formed. This means that the class denoted by the superclass constructor `sc` must be a subclass of the superclasses of all the traits `mt1, ..., mtn`. In other words, the non-trait classes inherited by a template form a chain in the inheritance hierarchy which starts with the template's superclass.

The *least proper supertype* of a template is the class type or compound type (§3.2.7) consisting of all its parent class types.

The statement sequence `stats` contains member definitions that define new members or overwrite members in the parent classes. If the template forms part of a class definition, the statement part `stats` may also contain declarations of abstract members. Furthermore, `stats` may contain expressions that are executed in the order they are given as part of the initialization of a template.

The sequence of template statements may be prefixed with a formal parameter definition and an arrow, e.g. `x =>`, or `x:T =>`. If a formal parameter is given, it can be used as an alias for the reference **this** throughout the body of the template. If the formal parameter comes with a type `T`, this definition affects the *self type* `S` of the underlying class or object as follows: Let `C` be the type of the class or trait or object defining the template. If a type `T` is given for the formal self parameter, `S` is the greatest lower bound of `T` and `C`. If no type `T` is given, `S` is just `C`. Inside the template, the type of **this** is assumed to be `S`.

The self type of a class or object must conform to the self types of all classes which are inherited by the template `t`.

A second form of self type annotation reads just **this**: `S =>`. It prescribes the type `S` for **this** without introducing an alias name for it.

Example 5.1.1 Consider the following class definitions:

```
class Base extends Object {}
trait Mixin extends Base {}
```

```
object O extends Mixin {}
```

In this case, the definition of `O` is expanded to:

```
object O extends Base with Mixin {}
```

Inheriting from Java Types. A template may have a Java class as its superclass and Java interfaces as its mixins.

Template Evaluation. Consider a template `sc with mt_1 with mt_n {stats}`.

If this is the template of a trait (§5.3.3) then its *mixin-evaluation* consists of an evaluation of the statement sequence *stats*.

If this is not a template of a trait, then its *evaluation* consists of the following steps.

- First, the superclass constructor *sc* is evaluated (§5.1.1).
- Then, all base classes in the template's linearization (§5.1.2) up to the template's superclass denoted by *sc* are mixin-evaluated. Mixin-evaluation happens in reverse order of occurrence in the linearization, i.e. the class immediately preceding *sc* is evaluated first.
- Finally the statement sequence *stats* is evaluated.

5.1.1 Constructor Invocations

Syntax:

```
Constr ::= AnnotType { '(' [Exprs [',']] ')' }
```

Constructor invocations define the type, members, and initial state of objects created by an instance creation expression, or of parts of an object's definition which are inherited by a class or object definition. A constructor invocation is a function application $x.c[targs](args_1) \dots (args_n)$, where *x* is a stable identifier (§3.1), *c* is a type name which either designates a class or defines an alias type for one, *targs* is a type argument list, and $args_1, \dots, args_n$ are argument lists, which match the parameters of one of the constructors of that class.

The prefix '*x.*' can be omitted. A type argument list can be given only if the class *c* takes type parameters. Even then it can be omitted, in which case a type argument list is synthesized using local type inference (§6.25.4). If no explicit arguments are given, an empty list `()` is implicitly supplied.

An evaluation of a constructor invocation $x.c[targs](args_1) \dots (args_n)$ consists of the following steps:

- First, the prefix *x* is evaluated.

- Then, the arguments $args_1, \dots, args_n$ are evaluated from left to right.
- Finally, the being constructed is initialized by evaluating the template of the class referred to by c .

5.1.2 Class Linearization

The classes reachable through transitive closure of the direct inheritance relation from a class C are called the *base classes* of C . Because of mixins, the inheritance relationship on base classes forms in general a directed acyclic graph. A linearization of this graph is defined as follows.

Definition 5.1.2 Let C be a class with template C_1 **with** ... **with** C_n { *stats* }. The *linearization* of C , $\mathcal{L}(C)$ is defined as follows:

$$\mathcal{L}(C) = C, \mathcal{L}(C_n) \dot{+} \dots \dot{+} \mathcal{L}(C_1)$$

Here $\dot{+}$ denotes concatenation where elements of the right operand replace identical elements of the left operand:

$$\begin{aligned} \{a, A\} \dot{+} B &= a, (A \dot{+} B) && \text{if } a \notin B \\ &= A \dot{+} B && \text{if } a \in B \end{aligned}$$

Example 5.1.3 Consider the following class definitions.

```
abstract class AbsIterator extends AnyRef { ... }
trait RichIterator extends AbsIterator { ... }
class StringIterator extends AbsIterator { ... }
class Iter extends StringIterator with RichIterator { ... }
```

Then the linearization of class `Iter` is

```
{ Iter, RichIterator, StringIterator, AbsIterator, ScalaObject, AnyRef, Any }
```

Trait `ScalaObject` appears in this list because it is added as last mixin to every Scala class (§5.1).

Note that the linearization of a class refines the inheritance relation: if C is a subclass of D , then C precedes D in any linearization where both C and D occur. Definition 5.1.2 also satisfies the property that a linearization of a class always contains the linearization of its direct superclass as a suffix. For instance, the linearization of `StringIterator` is

```
{ StringIterator, AbsIterator, ScalaObject, AnyRef, Any }
```

which is a suffix of the linearization of its subclass `Iter`. The same is not true for the linearization of mixins. For instance, the linearization of `RichIterator` is

{ RichIterator, AbsIterator, ScalaObject, AnyRef, Any }

which is not a suffix of the linearization of Iter.

5.1.3 Class Members

A class C defined by a template C_1 **with** ... **with** C_n { *stats* } can define members in its statement sequence *stats* and can inherit members from all parent classes. Scala adopts Java and C#'s conventions for static overloading of methods. It is thus possible that a class defines and/or inherits several methods with the same name. To decide whether a defined member of a class C overrides a member of a parent class, or whether the two co-exist as overloaded variants in C , Scala uses the following definition of *matching* on members:

Definition 5.1.4 A member definition M *matches* a member definition M' , if M and M' bind the same name, and one of following holds.

1. Neither M nor M' is a method definition.
2. M and M' define both monomorphic methods with equivalent argument types.
3. M defines a parameterless method and M' defines a method with an empty parameter list () or *vice versa*.
4. M and M' define both polymorphic methods with equal number of argument types \bar{T}, \bar{T}' and equal numbers of type parameters \bar{t}, \bar{t}' , say, and $\bar{T}' = [\bar{t}'/\bar{t}]\bar{T}$.

Member definitions fall into two categories: concrete and abstract. Members of class C are either *directly defined* (i.e. they appear in C 's statement sequence *stats*) or they are *inherited*. There are two rules that determine the set of members of a class, one for each category:

Definition 5.1.5 A *concrete member* of a class C is any concrete definition M in some class $C_i \in \mathcal{L}(C)$, except if there is a preceding class $C_j \in \mathcal{L}(C)$ where $j < i$ which directly defines a concrete member M' matching M .

An *abstract member* of a class C is any abstract definition M in some class $C_i \in \mathcal{L}(C)$, except if C contains already a concrete member M' matching M , or if there is a preceding class $C_j \in \mathcal{L}(C)$ where $j < i$ which directly defines an abstract member M' matching M .

This definition also determines the overriding relationships between matching members of a class C and its parents (§5.1.4). First, a concrete definition always overrides an abstract definition. Second, for definitions M and M' which are both concrete or both abstract, M overrides M' if M appears in a class that precedes (in the linearization of C) the class in which M' is defined.

It is an error if a template directly defines two matching members. It is also an error if a template contains two members (directly defined or inherited) with the same name and the same erased type (§3.6).

Example 5.1.6 Consider the trait definitions:

```
trait A { def f: Int = 1 ; def g: Int = 2 ; def h: Int = 3 }
trait B { def f: Int = 4 ; def g: Int }
trait C extends A with B { def h: Int }
```

Then trait C has a directly defined abstract member h. It inherits member f from trait B and member g from trait A.

5.1.4 Overriding

A member M of class C that matches (§5.1.3) a non-private member M' of a base class of C is said to *override* that member. In this case the binding of the overriding member M must subsume (§3.5.2) the binding of the overridden member M' . Furthermore, the following restrictions on modifiers apply to M and M' :

- M' must not be labeled **final**.
- M must not be **private** (§5.2).
- If M is labeled **private**[C] for some enclosing class or package C , then M' must be labeled **private**[C'] for some class or package C' where C' equals C or C' is contained in C .
- If M is labeled **protected**, then M' must also be labeled **protected**.
- If M' is not an abstract member, then M must be labeled **override**.
- If M' is incomplete (§5.2) in C then M must be labeled **abstract override**.

A special rule concerns parameterless methods. If a parameterless method defined as **def** f : $T = \dots$ or **def** $f = \dots$ overrides a method of type $()T'$ which has an empty parameter list, then f is also assumed to have an empty parameter list.

Example 5.1.7 Consider the definitions:

```
trait Root { type T <: Root }
trait A extends Root { type T <: A }
trait B extends Root { type T <: B }
trait C extends A with B
```

Then the class definition C is not well-formed because the binding of T in C is **type** T <: B, which fails to subsume the binding **type** T <: A of T in type A. The problem can be solved by adding an overriding definition of type T in class C:

```
class C extends A with B { type T <: C }
```

5.1.5 Inheritance Closure

Let C be a class type. The *inheritance closure* of C is the smallest set \mathcal{S} of types such that

- If T is in \mathcal{S} , then every type T' which forms syntactically a part of T is also in \mathcal{S} .
- If T is a class type in \mathcal{S} , then all parents (§5.1) of T are also in \mathcal{S} .

It is a static error if the inheritance closure of a class type consists of an infinite number of types. (This restriction is necessary to make subtyping decidable [KP07]).

5.1.6 Early Definitions

Syntax:

```
EarlyDefs      ::= '{' [EarlyDef {semi EarlyDef}] '}' 'with'
EarlyDef       ::= {Annotation} {Modifier} PatVarDef
```

A template may start with an *early field definition* clause, which serves to define certain field values before the supertype constructor is called. In a template

```
{ val  $p_1$ :  $T_1$  =  $e_1$ 
  ...
  val  $p_n$ :  $T_n$  =  $e_n$ 
} with  $sc$  with  $mt_1$  with  $mt_n$  {stats}
```

The initial pattern definitions of p_1, \dots, p_n are called *early definitions*. They define fields which form part of the template. Every early definition must define at least one variable.

An early definition is type-checked and evaluated in the scope which is in effect just before the template being defined, augmented by any type parameters of the enclosing class and by any early definitions preceding the one being defined. In particular, any reference to **this** in the right-hand side of an early definition refers to the identity of **this** just outside the template. Consequently, it is impossible that an early definition refers to the object being constructed by the template, or refers to one of its fields and methods, except for any other preceding early definition in the same section.

Early definitions are evaluated in the order they are being defined before the super-class constructor of the template is called.

Example 5.1.8 Early definitions are particularly useful for traits, which do not have normal constructor parameters. Example:

```
trait Greeting {
```

```

    val name: String
    val msg = "How are you, "+name
  }
  class C extends {
    val name = "Bob"
  } with Greeting {
    println(msg)
  }

```

In the code above, the field `name` is initialized before the constructor of `Greeting` is called. Therefore, field `msg` in class `Greeting` is properly initialized to "How are you, Bob".

If `name` has been initialized instead in `C`'s normal class body, it would be initialized after the constructor of `Greeting`. In that case, `msg` would be initialized to "How are you, <null>".

5.2 Modifiers

Syntax:

Modifier	::=	LocalModifier AccessModifier 'override'
LocalModifier	::=	'abstract' 'final' 'sealed' 'implicit' 'lazy'
AccessModifier	::=	('private' 'protected') [AccessQualifier]
AccessQualifier	::=	'[' (id 'this') ']

Member definitions may be preceded by modifiers which affect the accessibility and usage of the identifiers bound by them. If several modifiers are given, their order does not matter, but the same modifier may not occur repeatedly. Modifiers preceding a repeated definition apply to all constituent definitions. The rules governing the validity and meaning of a modifier are as follows.

- The **private** modifier can be used with any definition or declaration in a template. Such members can be accessed only from within the directly enclosing template and its companion module or companion class (§Example 5.4.1). They are not inherited by subclasses and they may not override definitions in parent classes.

The modifier can be *qualified* with an identifier *C* (e.g. **private**[*C*]) that must denote a class or package enclosing the definition. Members labeled with

such a modifier are accessible respectively only from code inside the package *C* or only from code inside the class *C* and its companion module (§5.4). Such members are also inherited only from templates inside *C*.

An different form of qualification is **private**[**this**]. A member *M* marked with this modifier can be accessed only from within the object in which it is defined. That is, a selection *p.M* is only legal if the prefix is **this** or *O.this*, for some class *O* enclosing the reference. In addition, the restrictions for unqualified **private** apply.

Members marked private without a qualifier are called *class-private*, whereas members labeled with **private**[**this**] are called *object-private*. A member is *private* if it is either class-private or object-private, but not if it is marked **private**[*C*] where *C* is an identifier; in the latter case the member is called *qualified private*.

Class-private or object-private members may not be deferred, and may not have **protected**, **final** or **override** modifiers.

- The **protected** modifier applies to class member definitions. Protected members of a class can be accessed from within
 - the template of the defining class,
 - all templates that have the defining class as a base class,
 - the companion module of any of those classes.

A **protected** modifier can be qualified with an package identifier *C* (e.g. **protected**[*C*]) that must denote a class or package enclosing the definition. Members labeled with such a modifier are also accessible respectively from all code inside the package *C* or from all code inside the class *C* and its companion module (§5.4).

A protected identifier *x* may be used as a member name in a selection *r.x* only if one of the following applies:

- The access is within the template defining the member, or, if a qualification *C* is given, inside the package *C*, or the class *C*, or its companion module, or
- *r* is one of the reserved words **this** and **super**, or
- *r*'s type conforms to a type-instance of the class which contains the access.

A different form of qualification is **protected**[**this**]. A member *M* marked with this modifier can be accessed only from within the object in which it is defined. That is, a selection *p.M* is only legal if the prefix is **this** or *O.this*, for some class *O* enclosing the reference. In addition, the restrictions for unqualified **protected** apply.

- The **override** modifier applies to class member definitions or declarations. It is mandatory for member definitions or declarations that override some other concrete member definition in a parent class. If an **override** modifier is given, there must be at least one overridden member definition or declaration (either concrete or abstract).
- The **override** modifier has a different significance when combined with the **abstract** modifier. That modifier combination is only allowed for value members of traits. A member labeled **abstract override** must override at least one other member and all members overridden by it must be incomplete.

We call a member M of a template *incomplete* if it is either abstract (i.e. defined by a declaration), or it is labeled **abstract** and **override** and every member overridden by M is again incomplete.

Note that the **abstract override** modifier combination does not influence the concept whether a member is concrete or abstract. A member is *abstract* if only a declaration is given for it; it is *concrete* if a full definition is given.

- The **abstract** modifier is used in class definitions. It is redundant for traits, and mandatory for all other classes which have incomplete members. Abstract classes cannot be instantiated (§6.10) with a constructor invocation unless followed by mixins and/or a refinement which override all incomplete members of the class. A case class (§5.3.2) cannot be **abstract**.

The **abstract** modifier can also be used in conjunction with **override** for class member definitions. In that case the previous discussion applies.

- The **final** modifier applies to class member definitions and to class definitions. A **final** class member definition may not be overridden in subclasses. A **final** class may not be inherited by a template. **final** is redundant for object definitions. Members of final classes or objects are implicitly also final, so the **final** modifier is redundant for them, too. **final** may not be applied to incomplete members, and it may not be combined in one modifier list with **private** or **sealed**.
- The **sealed** modifier applies to class definitions. A **sealed** class may not be directly inherited, except if the inheriting template is defined the same source file as the inherited class. However, subclasses of a sealed class can be inherited anywhere.
- The **lazy** modifier applies to value definitions. A **lazy** value is initialized the first time it is accessed (which might never happen at all). Attempting to access a lazy value during its initialization might lead to looping behavior. If an exception is thrown during initialization, the value is considered uninitialized, and a later access will retry to evaluate its right hand side.

Example 5.2.1 The following code illustrates the use of qualified private:

```

package outerpkg.innerpkg
class Outer {
  class Inner {
    private[Outer] def f()
    private[innerpkg] def g()
    private[outerpkg] def h()
  }
}

```

Here, accesses to the method `f` can appear anywhere within `OuterClass`, but not outside it. Accesses to method `g` can appear anywhere within the package `outerpkg.innerpkg`, as would be the case for package-private methods in Java. Finally, accesses to method `h` can appear anywhere within package `outerpkg`, including packages contained in it.

Example 5.2.2 A useful idiom to prevent clients of a class from constructing new instances of that class is to declare the class **abstract** and **sealed**:

```

object m {
  abstract sealed class C (x: Int) {
    def nextC = new C(x + 1) {}
  }
  val empty = new C(0) {}
}

```

For instance, in the code above clients can create instances of class `m.C` only by calling the `nextC` method of an existing `m.C` object; it is not possible for clients to create objects of class `m.C` directly. Indeed the following two lines are both in error:

```

new m.C(0)    // **** error: C is abstract, so it cannot be instantiated.
new m.C(0) {} // **** error: illegal inheritance from sealed class.

```

A similar access restriction can be achieved by marking the primary constructor **private** (see Example 5.3.2).

5.3 Class Definitions

Syntax:

```

TplDef      ::= 'class' ClassDef
ClassDef    ::= id [TypeParamClause] {Annotation}
              [AccessModifier] ClassParamClauses ClassTemplateOpt
ClassParamClauses ::= {ClassParamClause}
                  [[nl] '(' implicit ClassParams ')']
ClassParamClause ::= [nl] '(' [ClassParams] ')'

```

```

ClassParams      ::= ClassParam {',' ClassParam}
ClassParam       ::= {Annotation} [{Modifier} ('val' | 'var')]
                  id [':' ParamType]
ClassTemplateOpt ::= 'extends' ClassTemplate | [['extends'] TemplateBody]

```

The most general form of class definition is

```
class c[tps] as m(ps1)...(psn) extends t           (n ≥ 0).
```

Here,

c is the name of the class to be defined.

tps is a non-empty list of type parameters of the class being defined. The scope of a type parameter is the whole class definition including the type parameter section itself. It is illegal to define two type parameters with the same name. The type parameter section [*tps*] may be omitted. A class with a type parameter section is called *polymorphic*, otherwise it is called *monomorphic*.

as is a possibly empty sequence of annotations (§11). If any annotations are given, they apply to the primary constructor of the class.

m is an access modifier (§5.2) such as **private** or **protected**, possibly with a qualification. If such an access modifier is given it applies to the primary constructor to the class.

(*ps*₁)...(*ps*_{*n*}) are formal value parameter clauses for the *primary constructor* of the class. The scope of a formal value parameter includes the template *t*. However, a formal value parameter may not form part of the types of any of the parent classes or members of the class template *t*. It is illegal to define two formal value parameters with the same name. If no formal parameter sections are given, an empty parameter section () is assumed.

If a formal parameter declaration *x* : *T* is preceded by a **val** or **var** keyword, an accessor (getter) definition (§4.2) for this parameter is implicitly added to the class. The getter introduces a value member *x* of class *c* that is defined as an alias of the parameter. If the introducing keyword is **var**, a setter accessor *x*_ = (§4.2) is also implicitly added to the class. In invocation of that setter *x*_ = (*e*) changes the value of the parameter to the result of evaluating *e*. The formal parameter declaration may contain modifiers, which then carry over to the accessor definition(s). A formal parameter prefixed by **val** or **var** may not at the same time be a call-by-name parameter (§4.6.1).

t is a template (§5.1) of the form

```
sc with mt1 with ... with mtm { stats }           (m ≥ 0)
```

which defines the base classes, behavior and initial state of objects of the class. The extends clause **extends** *sc* **with** *mt*₁ **with** ... **with** *mt*_{*m*} can be

omitted, in which case **extends** `scala.AnyRef` is assumed. The class body `{stats}` may also be omitted, in which case the empty body `{}` is assumed.

This class definition defines a type $c[tps]$ and a constructor which when applied to parameters conforming to types ps initializes instances of type $c[tps]$ by evaluating the template t .

Example 5.3.1 The following example illustrates **val** and **var** parameters of a class C:

```
class C(x: Int, val y: String, var z: List[String])
val c = new C(1, "abc", List())
c.z = c.y :: c.z
```

Example 5.3.2 The following class can be created only from its companion module.

```
object Sensitive {
  def makeSensitive(credentials: Certificate): Sensitive =
    if (credentials == Admin) new Sensitive()
    else throw new SecurityViolationException
}
class Sensitive private () {
  ...
}
```

5.3.1 Constructor Definitions

Syntax:

```
FunDef      ::= 'this' ParamClause ParamClauses
              ('=' ConstrExpr | [nl] ConstrBlock)
ConstrExpr   ::= SelfInvocation
              | ConstrBlock
ConstrBlock  ::= '{' SelfInvocation {semi BlockStat} '}'
SelfInvocation ::= 'this' ArgumentExprs {ArgumentExprs}
```

A class may have additional constructors besides the primary constructor. These are defined by constructor definitions of the form **def this**(ps_1)...(ps_n) = e . Such a definition introduces an additional constructor for the enclosing class, with parameters as given in the formal parameter lists ps_1, \dots, ps_n , and whose evaluation is defined by the constructor expression e . The scope of each formal parameter is the constructor expression e . A constructor expression is either a self constructor invocation **this**($args_1$)...($args_n$) or a block which begins with a self constructor invocation. The self constructor invocation must construct a generic instance of the class. I.e. if the class in question has name C and type parameters $[tps]$, then a self

constructor invocation must generate an instance of $C[tps]$; it is not permitted to instantiate formal type parameters.

The signature and the self constructor invocation of a constructor definition are type-checked and evaluated in the scope which is in effect at the point of the enclosing class definition, augmented by any type parameters of the enclosing class and by any early definitions (§5.1.6) of the enclosing template. The rest of the constructor expression is type-checked and evaluated as a function body in the current class.

If there are auxiliary constructors of a class C , they form together with C 's primary constructor (§5.3) an overloaded constructor definition. The usual rules for overloading resolution (§6.25.3) apply for constructor invocations of C , including for the self constructor invocations in the constructor expressions themselves. However, unlike other methods, constructors are never inherited. To prevent infinite cycles of constructor invocations, there is the restriction that every self constructor invocation must refer to a constructor definition which precedes it (i.e. it must refer to either a preceding auxiliary constructor or the primary constructor of the class).

Example 5.3.3 Consider the class definition

```
class LinkedList[A]() {
  var head = _
  var tail = null
  def isEmpty = tail != null
  def this(head: A) = { this(); this.head = head }
  def this(head: A, tail: List[A]) = { this(head); this.tail = tail }
}
```

This defines a class `LinkedList` with three constructors. The second constructor constructs an singleton list, while the third one constructs a list with a given head and tail.

5.3.2 Case Classes

Syntax:

```
TmpDef ::= 'case' 'class' ClassDef
```

If a class definition is prefixed with **case**, the class is said to be a *case class*.

The formal parameters in the first parameter section of a case class are called *elements*; they are treated specially. First, the value of such a parameter can be extracted as a field of a constructor pattern. Second, a **val** prefix is implicitly added to such a parameter, unless the parameter carries already a **val** or **var** modifier. Hence, an accessor definition for the parameter is generated (§5.3).

A case class definition of $c[tps](ps_1) \dots (ps_n)$ with type parameters tps and value

parameters ps implicitly generates a function definition for a *case class factory* together with the class definition itself:

```
def c[tps](ps1)...(psn): s = new c[tps](xs1)...(xsn)
```

(Here, s is the self type of class c and each xs_i denotes the parameters of ps_i . If a type parameter section is missing in the class, it is also missing in the factory definition).

Every case class implicitly overrides some method definitions of class `scala.AnyRef` (§12.1) unless a definition of the same method is already given in the case class itself or a concrete definition of the same method is given in some base class of the case class different from `AnyRef`. In particular:

Method `equals`: `(Any)Boolean` is structural equality, where two instances are equal if they both belong to the case class in question and they have equal (with respect to `equals`) constructor arguments.

Method `hashCode`: `Int` computes a hash-code. If the `hashCode` methods of the data structure members map equal (with respect to `equals`) values to equal hash-codes, then the case class `hashCode` method does too.

Method `toString`: `String` returns a string representation which contains the name of the class and its elements.

Example 5.3.4 Here is the definition of abstract syntax for lambda calculus:

```
class Expr
case class Var (x: String) extends Expr
case class Apply (f: Expr, e: Expr) extends Expr
case class Lambda(x: String, e: Expr) extends Expr
```

This defines a class `Expr` with case classes `Var`, `Apply` and `Lambda`. A call-by-value evaluator for lambda expressions could then be written as follows.

```
type Env = String => Value
case class Value(e: Expr, env: Env)

def eval(e: Expr, env: Env): Value = e match {
  case Var (x) =>
    env(x)
  case Apply(f, g) =>
    val Value(Lambda (x, e1), env1) = eval(f, env)
    val v = eval(g, env)
    eval (e1, (y => if (y == x) v else env1(y)))
  case Lambda(_, _) =>
    Value(e, env)
}
```

It is possible to define further case classes that extend type `Expr` in other parts of the program, for instance

```
case class Number(x: Int) extends Expr
```

This form of extensibility can be excluded by declaring the base class `Expr` **sealed**; in this case, all classes that directly extend `Expr` must be in the same source file as `Expr`.

5.3.3 Traits

Syntax:

```
TplDef      ::= 'trait' TraitDef
TraitDef     ::= id [TypeParamClause] TraitTemplateOpt
TraitTemplateOpt ::= 'extends' TraitTemplate | [['extends'] TemplateBody]
```

A trait is a class that is meant to be added to some other class as a mixin. Unlike normal classes, traits cannot have constructor parameters. Furthermore, no constructor arguments are passed to its superclass. This is not necessary as traits are initialized after the superclass is initialized.

Assume a trait D defines some aspect of an instance x of type C (i.e. D is a base class of C). Then the *actual supertype* of D in x is the compound type consisting of all the base classes in $\mathcal{L}(C)$ that succeed D . The actual supertype gives the context for resolving a **super** reference in a trait (§6.5). Note that the actual supertype depends on the type to which the trait is added in a mixin composition; it is not statically known at the time the trait is defined.

If D is not a trait, then its actual supertype is simply its least proper supertype (which is statically known).

Example 5.3.5 The following trait defines the property of being comparable to objects of some type. It contains an abstract method `<` and default implementations of the other comparison operators `<=`, `>`, and `>=`.

```
trait Comparable[T <: Comparable[T]] { self: T =>
  def < (that: T): Boolean
  def <=(that: T): Boolean = this < that || this == that
  def > (that: T): Boolean = that < this
  def >=(that: T): Boolean = that <= this
}
```

Example 5.3.6 Consider an abstract class `Table` that implements maps from a type of keys A to a type of values B . The class has a method `set` to enter a new key / value pair into the table, and a method `get` that returns an optional value matching a given key. Finally, there is a method `apply` which is like `get`, except that it returns

a given default value if the table is undefined for the given key. This class is implemented as follows.

```
abstract class Table[A, B](defaultValue: B) {  
  def get(key: A): Option[B]  
  def set(key: A, value: B)  
  def apply(key: A) = get(key) match {  
    case Some(value) => value  
    case None => defaultValue  
  }  
}
```

Here is a concrete implementation of the Table class.

```
class ListTable[A, B](defaultValue: B) extends Table[A, B](defaultValue) {  
  private var elems: List[(A, B)]  
  def get(key: A) = elems.find(_._1==(key)).map(_._2)  
  def set(key: A, value: B) = { elems = (key, value) :: elems }  
}
```

Here is a trait that prevents concurrent access to the get and set operations of its parent class:

```
trait SynchronizedTable[A, B] extends Table[A, B] {  
  abstract override def get(key: A): B =  
    synchronized { super.get(key) }  
  abstract override def set((key: A, value: B) =  
    synchronized { super.set(key, value) }  
}
```

Note that SynchronizedTable does not pass an argument to its superclass, Table, even though Table is defined with a formal parameter. Note also that the **super** calls in SynchronizedTable's get and set methods statically refer to abstract methods in class Table. This is legal, as long as the calling method is labeled **abstract override** (§5.2).

Finally, the following mixin composition creates a synchronized list table with strings as keys and integers as values and with a default value 0:

```
object MyTable extends ListTable[String, Int](0) with SynchronizedTable
```

The object MyTable inherits its get and set method from SynchronizedTable. The **super** calls in these methods are re-bound to refer to the corresponding implementations in ListTable, which is the actual supertype of SynchronizedTable in MyTable.

5.4 Object Definitions

Syntax:

```
ObjectDef ::= id ClassTemplate
```

An object definition defines a single object of a new class. Its most general form is **object** *m* **extends** *t*. Here, *m* is the name of the object to be defined, and *t* is a template (§5.1) of the form

```
sc with mt1 with ... with mtn { stats }
```

which defines the base classes, behavior and initial state of *m*. The **extends** clause **extends** *sc with mt₁ with ... with mt_n* can be omitted, in which case **extends** `scala.AnyRef` is assumed. The class body `{stats}` may also be omitted, in which case the empty body `{}` is assumed.

The object definition defines a single object (or: *module*) conforming to the template *t*. It is roughly equivalent to the following three definitions, which together define a class and create a single object of that class on demand:

```
final class m$cls extends t
private var m$instance = null
final def m = {
  if (m$instance == null) m$instance = new m$cls
  m$instance
}
```

Here, the **final** modifiers are omitted if the definition occurs as part of a block. The names *m\$cls* and *m\$instance* are inaccessible for user programs.

Note that the value defined by an object definition is instantiated lazily. The **new** *m\$cls* constructor is evaluated not at the point of the object definition, but is instead evaluated the first time *m* is dereferenced during execution of the program (which might be never at all). An attempt to dereference *m* again in the course of evaluation of the constructor leads to a infinite loop or run-time error.

However, the expansion given above is not accurate for top-level objects. It cannot be because variable and method definition cannot appear on the top-level. Instead, top-level objects are translated to static fields.

Example 5.4.1 Classes in Scala do not have static members; however, an equivalent effect can be achieved by an accompanying object definition E.g.

```
abstract class Point {
  val x: Double
  val y: Double
  def isOrigin = (x == 0.0 && y == 0.0)
```

```
}  
object Point {  
  val origin = new Point() { val x = 0.0; val y = 0.0 }  
}
```

This defines a class `Point` and an object `Point` which contains `origin` as a member. Note that the double use of the name `Point` is legal, since the class definition defines the name `Point` in the type name space, whereas the object definition defines a name in the term namespace.

This technique is applied by the Scala compiler when interpreting a Java class with static members. Such a class *C* is conceptually seen as a pair of a Scala class that contains all instance members of *C* and a Scala object that contains all static members of *C*.

Generally, a *companion module* of a class is an object which has the same name as the class and is defined in the same scope and compilation unit. Conversely, the class is called the *companion class* of the module.

Chapter 6

Expressions

Syntax:

```
Expr      ::= (Bindings | id) '=>' Expr
           | Expr1
Expr1     ::= 'if' '(' Expr ')' {nl} Expr [[semi] else Expr]
           | 'while' '(' Expr ')' {nl} Expr
           | 'try' '{' Block '}' [catch '{' CaseClauses '}']
           | 'finally' Expr
           | 'do' Expr [semi] 'while' '(' Expr ')'
           | 'for' '(' Enumerators ')' | '{' Enumerators '}'
           {nl} [yield] Expr
           | 'throw' Expr
           | 'return' [Expr]
           | [SimpleExpr '.'] id '=' Expr
           | SimpleExpr1 ArgumentExprs '=' Expr
           | PostfixExpr
           | PostfixExpr Ascription
           | PostfixExpr 'match' '{' CaseClauses '}'
PostfixExpr ::= InfixExpr [id [nl]]
InfixExpr  ::= PrefixExpr
           | InfixExpr id [nl] InfixExpr
PrefixExpr ::= ['- ' | '+ ' | '~ ' | '!'] SimpleExpr
SimpleExpr ::= 'new' (ClassTemplate | TemplateBody)
           | BlockExpr
           | SimpleExpr1 ['_']
SimpleExpr1 ::= Literal
           | Path
           | '_'
           | '(' [Exprs [',']] ')'
           | SimpleExpr '.' id
           | SimpleExpr TypeArgs
```

```

| SimpleExpr1 ArgumentExprs
| XmlExpr
Exprs      ::= Expr {',' Expr}
BlockExpr  ::= '{' CaseClauses '}'
           | '{' Block '}'
Block      ::= {BlockStat semi} [ResultExpr]
ResultExpr ::= Expr1
           | (Bindings | id ':' CompoundType) '=>' Block
Ascription ::= ':' CompoundType
           | ':' Annotation {Annotation}
           | ':' '_' '*'

```

Expressions are composed of operators and operands. Expression forms are discussed subsequently in decreasing order of precedence.

6.1 Expression Typing

The typing of expressions is often relative to some *expected type* (which might be undefined). When we write “expression e is expected to conform to type T ”, we mean: (1) the expected type of e is T , and (2) the type of expression e must conform to T .

The following skolemization rule is applied universally for every expression: If the type of an expression would be an existential type T , then the type of the expression is assumed instead to be a skolemization (§3.2.10) of T .

Skolemization is reversed by type packing. Assume an expression e of type T and let $t_1[tps_1] >: L_1 <: U_1, \dots, t_n[tps_n] >: L_n <: U_n$ be all the type variables created by skolemization of some part of e which are free in T . The *packed type* of e is

$$T \text{ forSome } \{ \text{type } t_1[tps_1] >: L_1 <: U_1; \dots; \text{type } t_n[tps_n] >: L_n <: U_n \}.$$

6.2 Literals

Syntax:

```
SimpleExpr ::= Literal
```

Typing of literals is as described in (§1.3); their evaluation is immediate.

A different form of literals designate classes. These are written

```
classOf[C]
```

Here, `classOf` is a method defined in `scala.Predef` (§12.5) and C is a class type.

The value of such a class literal is the run-time representation of the class type C .

6.3 The *Null* Value

The **null** value is of type `scala.Null`, and is thus compatible with every reference type. It denotes a reference value which refers to a special “**null**” object. This object implements methods in class `scala.AnyRef` as follows:

- `eq(x)`, `==(x)`, `equals(x)` return **true** iff their argument x is also the “null” object.
- `asInstanceOf[T]` always returns **false**.
- `asInstanceOf[T]` returns the “null” object itself if T conforms to `scala.AnyRef`, and throws a `NullPointerException` otherwise.

A reference to any other member of the “null” object causes a `NullPointerException` to be thrown.

6.4 Designators

Syntax:

```
SimpleExpr ::= Path
            | SimpleExpr '.' id
```

A designator refers to a named term. It can be a *simple name* or a *selection*.

A simple name x refers to a value as specified in §2. If x is bound by a definition or declaration in an enclosing class or object C , it is taken to be equivalent to the selection $C.this.x$ where C is taken to refer to the class containing x even if the type name C is shadowed (§2) at the occurrence of x .

If r is a stable identifier (§3.1) of type T , the selection $r.x$ refers statically to a term member m of r that is identified in T by the name x .

For other expressions e , $e.x$ is typed as if it was `{ val y = e ; $y.x$ }`, for some fresh name y . The typing rules for blocks implies that in that case x ’s type may not refer to any abstract type member of e .

The expected type of a designator’s prefix is always undefined. The type of a designator is the type T of the entity it refers to, with the following exception: The type of a path (§3.1) p which occurs in a context where a stable type (§3.2.1) is required is the singleton type $p.type$.

The contexts where a stable type is required are those that satisfy one of the following conditions:

1. The path p occurs as the prefix of a selection and it does not designate a constant, or
2. The expected type pt is a stable type, or
3. The expected type pt is an abstract type with a stable type as lower bound, and the type T of the entity referred to by p does not conform to pt , or
4. The path p designates a module.

The selection $e.x$ is evaluated by first evaluating the qualifier expression e , which yields an object r , say. The selection's result is then the member of r that is either defined by m or defined by a definition overriding m . If that member has a type which conforms to `scala.NotNull@`, the member's value must be initialized to a value different from `null@`, otherwise a `scala.UninitializedError@` is thrown.

6.5 This and Super

Syntax:

```
SimpleExpr ::= [id '.'] 'this'
             | [id '.'] 'super' [ClassQualifier] '.' id
```

The expression **this** can appear in the statement part of a template or compound type. It stands for the object being defined by the innermost template or compound type enclosing the reference. If this is a compound type, the type of **this** is that compound type. If it is a template of an instance creation expression, the type of **this** is the type of that template. If it is a template of a class or object definition with simple name C , the type of this is the same as the type of $C.\mathbf{this}$.

The expression $C.\mathbf{this}$ is legal in the statement part of an enclosing class or object definition with simple name C . It stands for the object being defined by the innermost such definition. If the expression's expected type is a stable type, or $C.\mathbf{this}$ occurs as the prefix of a selection, its type is $C.\mathbf{this.type}$, otherwise it is the self type of class C .

A reference **super**. m refers statically to a member m in the least proper supertype of the innermost template containing the reference. It evaluates to the member m' in the actual supertype of that template which is equal to m or which overrides m . The statically referenced member m must be concrete, or the template containing the reference must have a member m' which overrides m and which is labeled **abstract override**.

A reference $C.\mathbf{super}.m$ refers statically to a member m in the least proper supertype of the innermost enclosing class or object definition named C which encloses the reference. It evaluates to the member m' in the actual supertype of that class or object which is equal to m or which overrides m . The statically referenced

member m must be concrete, or the innermost enclosing class or object definition named C must have a member m' which overrides m and which is labeled **abstract override**.

The **super** prefix may be followed by a class qualifier $[C]$, as in $C.\text{super}[C].x$. This is called a *static super reference*. In this case, the reference is to the member of x in the parent class of C whose simple name is M . That member must be uniquely defined and concrete.

Example 6.5.1 Consider the following class definitions

```
class Root { val x = "Root" }
class A extends Root { override val x = "A" ; val superA = super.x }
trait B extends Root { override val x = "B" ; val superB = super.x }
class C extends Root with B {
  override val x = "C" ; val superC = super.x }
}
class D extends A with B {
  override val x = "D" ; val superD = super.x }
}
```

The linearization of class C is $\{C, B, \text{Root}\}$ and the linearization of class D is $\{D, B, A, \text{Root}\}$. Then we have:

```
(new A).superA == "Root",
(new C).superA == "Root", (new C).superB = "Root", (new C).superC = "B",
(new D).superA == "Root", (new D).superB = "A",    (new D).superD = "B",
```

Note that the `superB` function returns different results depending on whether B is mixed in with class `Root` or `A`.

6.6 Function Applications

Syntax:

```
SimpleExpr    ::= SimpleExpr1 ArgumentExprs
ArgumentExprs ::= '(' [Exprs [',']] ')'
               | '(' [Exprs [',']] PostfixExpr ':' '_' '*' ')'
               | [nl] BlockExpr
Exprs         ::= Expr {',' Expr}
```

An application $f(e_1, \dots, e_n)$ applies the function f to the argument expressions e_1, \dots, e_n . If f has a method type $(T_1, \dots, T_n)U$, the type of each argument expression e_i must conform to the corresponding parameter type T_i . If f has some value type, the application is taken to be equivalent to $f.\text{apply}(e_1, \dots, e_n)$, i.e. the application of an `apply` method defined by f .

Evaluation of $f(e_1, \dots, e_n)$ usually entails evaluation of f and e_1, \dots, e_n in that order. Each argument expression is converted to the type of its corresponding formal parameter. After that, the application is rewritten to the function's right hand side, with actual arguments substituted for formal parameters. The result of evaluating the rewritten right-hand side is finally converted to the function's declared result type, if one is given.

A function application usually allocates a new frame on the program's run-time stack. However, if a local function or a final method calls itself as its last action, the call is executed using the stack-frame of the caller.

The case of a formal parameter with a parameterless method type $\Rightarrow T$ is treated specially. In this case, the corresponding actual argument expression e is not evaluated before the application. Instead, every use of the formal parameter on the right-hand side of the rewrite rule entails a re-evaluation of e . In other words, the evaluation order for \Rightarrow -parameters is *call-by-name* whereas the evaluation order for normal parameters is *call-by-value*. Furthermore, it is required that e 's packed type (§6.1) conforms to the parameter type T .

The last argument in an application may be marked as a sequence argument, e.g. $e: _*$. Such an argument must correspond to a repeated parameter (§4.6.2) of type S^* and it must be the only argument matching this parameter (i.e. the number of formal parameters and actual arguments must be the same). Furthermore, the type of e must conform to `scala.Seq[T]`, for some type T which conforms to S . In this case, the argument list is transformed by replacing the sequence e with its elements.

Example 6.6.1 Assume the following function which computes the sum of a variable number of arguments:

```
def sum(xs: Int*) = (0 /: xs) ((x, y) => x + y)
```

Then

```
sum(1, 2, 3, 4)
sum(List(1, 2, 3, 4): _*)
```

both yield 10 as result. On the other hand,

```
sum(List(1, 2, 3, 4))
```

would not typecheck.

6.7 Method Values

Syntax:

```
SimpleExpr ::= SimpleExpr1 '_'
```

The expression `e _` is well-formed if `e` is of method type or if `e` is a call-by-name parameter. If `e` is a method with parameters, `e _` represents `e` converted to a function type by eta expansion (§6.25.5). If `e` is a parameterless method or call-by-name parameter of type $\Rightarrow T$, `e _` represents the function of type $() \Rightarrow T$, which evaluates `e` when it is applied to the empty parameterlist `()`.

Example 6.7.1 The method values in the left column are each equivalent to the anonymous functions (§6.23) on their right.

<code>Math.sin _</code>	<code>x => Math.sin(x)</code>
<code>Array.range _</code>	<code>(x1, x2) => Array.range(x1, x2)</code>
<code>List.map2 _</code>	<code>(x1, x2) => (x3) => List.map2(x1, x2)(x3)</code>
<code>List.map2(xs, ys)_</code>	<code>x => List.map2(xs, ys)(x)</code>

Note that a space is necessary between a method name and the trailing underscore because otherwise the underscore would be considered part of the name.

6.8 Type Applications

Syntax:

`SimpleExpr ::= SimpleExpr TypeArgs`

A type application `e[T1, ..., Tn]` instantiates a polymorphic value `e` of type $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]S$ with argument types T_1, \dots, T_n . Every argument type T_i must obey the corresponding bounds L_i and U_i . That is, for each $i = 1, \dots, n$, we must have $\sigma L_i <: T_i <: \sigma U_i$, where σ is the substitution $[a_1 := T_1, \dots, a_n := T_n]$. The type of the application is σS .

If the function part `e` is of some value type, the type application is taken to be equivalent to `e.apply[T1, ..., Tn]`, i.e. the application of an `apply` method defined by `e`.

Type applications can be omitted if local type inference (§6.25.4) can infer best type parameters for a polymorphic functions from the types of the actual function arguments and the expected result type.

6.9 Tuples

Syntax:

`SimpleExpr ::= '(' [Exprs [' , ']] ')'`

A tuple expression `(e1, ..., en)` is an alias for the class instance creation `scala.Tuplen(e1, ..., en)`, where $n \geq 2$. The expression may also be written with

a trailing comma, i.e. $(e_1, \dots, e_n,)$. Unary tuples can be expressed in this syntax only by using a trailing comma, i.e. $(e,)$. Finally, the empty tuple $()$ is the unique value of type `scala.Unit`.

6.10 Instance Creation Expressions

Syntax:

`SimpleExpr ::= 'new' (ClassTemplate | TemplateBody)`

A simple instance creation expression is of the form **new** c where c is a constructor invocation (§5.1.1). Let T be the type of c . Then T must denote a (a type instance of) a non-abstract subclass of `scala.AnyRef` which conforms to its self type (§5.1). The expression is evaluated by creating a fresh object of type T which is initialized by evaluating c . The type of the expression is T .

A general instance creation expression is of the form **new** t for some class template t (§5.1). Such an expression is equivalent to the block

```
{ class a extends t; new a }
```

where a is a fresh name of an *anonymous class*.

There is also a shorthand form for creating values of structural types: If $\{D\}$ is a class body, then **new** $\{D\}$ is equivalent to the general instance creation expression **new** `AnyRef{D}`.

Example 6.10.1 Consider the following structural instance creation expression:

```
new { def getName() = "aaron" }
```

This is a shorthand for the general instance creation expression

```
new AnyRef{ def getName() = "aaron" }
```

The latter is in turn a shorthand for the block

```
{ class anon$X extends AnyRef{ def getName() = "aaron" }; new anon$X }
```

where `anon$X` is some freshly created name.

6.11 Blocks

Syntax:

`BlockExpr ::= '{' Block '}'`

Block ::= [{BlockStat semi} ResultExpr]

A block expression $\{s_1; \dots; s_n; e\}$ is constructed from a sequence of block statements s_1, \dots, s_n and a final expression e . The statement sequence may not contain two definitions or declarations that bind the same name in the same namespace. The final expression can be omitted, in which case the unit value $()$ is assumed.

The expected type of the final expression e is the expected type of the block. The expected type of all preceding statements is undefined.

The type of a block $s_1; \dots; s_n; e$ is $T \text{ forSome } \{Q\}$, where T is the type of e and Q contains existential clauses (§3.2.10) for every value or type name which is free in T and which is defined locally in one of the statements s_1, \dots, s_n . We say the existential clause *binds* the occurrence of the value or type name. Specifically,

- A locally defined type definition **type** $t[tps] = T$ is bound by the existential clause **type** $t[tps] >: T <: T$.
- A locally defined value definition **val** $x : T = e$ is bound by the existential clause **val** $x : T$.
- A locally defined class definition **class** $c[tps]$ **extends** t is bound by the existential clause **type** $c[tps] <: T$ where T is the least class type or refinement type which is a proper supertype of the type $c[tps]$.
- A locally defined object definition **object** x **extends** t is bound by the existential clause **val** $x : T$ where T is the least class type or refinement type which is a proper supertype of the type $x.\text{type}$.

Evaluation of the block entails evaluation of its statement sequence, followed by an evaluation of the final expression e , which defines the result of the block.

Example 6.11.1 Assuming a class `Ref[T](x: T)`, the block

```
{ class C extends B {...} ; new Ref(new C) }
```

has the type `Ref[_1] forSome { type _1 <: B }`. The block

```
{ class C extends B {...} ; new C }
```

simply has type `B`, because with the rules in (§3.2.10 the existentially quantified type `_1 forSome { type _1 <: B }` can be simplified to `B`.

6.12 Prefix, Infix, and Postfix Operations

Syntax:

```

PostfixExpr ::= InfixExpr [id [nl]]
InfixExpr  ::= PrefixExpr
              | InfixExpr id [nl] InfixExpr
PrefixExpr ::= ['- ' | '+ ' | '! ' | '~'] SimpleExpr

```

Expressions can be constructed from operands and operators.

6.12.1 Prefix Operations

A prefix operation *op e* consists of a prefix operator *op*, which must be one of the identifiers '+', '-', '!' or '~'. The expression *op e* is equivalent to the postfix method application *e.unary_op*.

Prefix operators are different from normal function applications in that their operand expression need not be atomic. For instance, the input sequence *-sin(x)* is read as *-(sin(x))*, whereas the function application *negate sin(x)* would be parsed as the application of the infix operator *sin* to the operands *negate* and *(x)*.

6.12.2 Postfix Operations

An postfix operator can be an arbitrary identifier. The postfix operation *e op* is interpreted as *e.op*.

6.12.3 Infix Operations

An infix operator can be an arbitrary identifier. Infix operators have precedence and associativity defined as follows:

The *precedence* of an infix operator is determined by the operator's first character. Characters are listed below in increasing order of precedence, with characters on the same line having the same precedence.

```

(all letters)
|
^
&
< >
= !
:
+ -
* / %
(all other special characters)

```

That is, operators starting with a letter have lowest precedence, followed by operators starting with '|', etc.

The *associativity* of an operator is determined by the operator's last character. Operators ending in a colon ':' are right-associative. All other operators are left-

associative.

Precedence and associativity of operators determine the grouping of parts of an expression as follows.

- If there are several infix operations in an expression, then operators with higher precedence bind more closely than operators with lower precedence.
- If there are consecutive infix operations $e_0 \text{ op}_1 e_1 \text{ op}_2 \dots \text{op}_n e_n$ with operators $\text{op}_1, \dots, \text{op}_n$ of the same precedence, then all these operators must have the same associativity. If all operators are left-associative, the sequence is interpreted as $(\dots (e_0 \text{ op}_1 e_1) \text{ op}_2 \dots) \text{op}_n e_n$. Otherwise, if all operators are right-associative, the sequence is interpreted as $e_0 \text{ op}_1 (e_1 \text{ op}_2 (\dots \text{op}_n e_n) \dots)$.
- Postfix operators always have lower precedence than infix operators. E.g. $e_1 \text{ op}_1 e_2 \text{ op}_2$ is always equivalent to $(e_1 \text{ op}_1 e_2) \text{ op}_2$.

The right-hand operand of a left-associative operator may consist of several arguments enclosed in parentheses, e.g. $e \text{ op } (e_1, \dots, e_n)$. This expression is then interpreted as $e.\text{op}(e_1, \dots, e_n)$.

A left-associative binary operation $e_1 \text{ op } e_2$ is interpreted as $e_1.\text{op}(e_2)$. If op is right-associative, the same operation is interpreted as $\{ \text{val } x=e_1; e_2.\text{op}(x) \}$, where x is a fresh name.

6.12.4 Assignment Operators

An assignment operator is an operator symbol (syntax category `op` in (§1.1)) that ends in an equals sign “`=`”. Assignment operators are treated specially in that they can be expanded to assignments if no other interpretation is valid.

Let’s consider an assignment operator such as `+=` in an infix operation $l \text{ += } r$, where l, r are expressions. This operation can be re-interpreted as an operation which corresponds to the assignment

$$l = l + r$$

except that the operation’s left-hand-side l is evaluated only once.

The re-interpretation occurs if the following two conditions are fulfilled.

1. The left-hand-side l does not have a member named `+=`, and also cannot be converted by an implicit conversion (§6.25) to a value with a member named `+=`.
2. The assignment $l = l + r$ is type-correct. In particular this implies that l refers to a variable or object that can be assigned to, and that is convertible to a value with a member named `+`.

6.13 Typed Expressions

Syntax:

Expr1 ::= PostfixExpr ':' CompoundType

The typed expression $e : T$ has type T . The type of expression e is expected to conform to T . The result of the expression is the value of e converted to type T .

Example 6.13.1 Here are examples of well-typed and illegally typed expressions.

```
1: Int           // legal, of type Int
1: Long          // legal, of type Long
// 1: string     // ***** illegal
```

6.14 Annotated Expressions

Syntax:

Expr1 ::= PostfixExpr ':' Annotation {Annotation}

An annotated expression $e : @a_1 \dots @a_n$ attaches annotations a_1, \dots, a_n to the expression e (§11).

6.15 Assignments

Syntax:

Expr1 ::= [SimpleExpr '.'] id '=' Expr
| SimpleExpr1 ArgumentExprs '=' Expr

The interpretation of an assignment to a simple variable $x = e$ depends on the definition of x . If x denotes a mutable variable, then the assignment changes the current value of x to be the result of evaluating the expression e . The type of e is expected to conform to the type of x . If x is a parameterless function defined in some template, and the same template contains a setter function $x_=(e)$ as member, then the assignment $x = e$ is interpreted as the invocation $x_=(e)$ of that setter function. Analogously, an assignment $f.x = e$ to a parameterless function x is interpreted as the invocation $f.x_=(e)$.

An assignment $f(args) = e$ with a function application to the left of the “=” operator is interpreted as $f.update(args, e)$, i.e. the invocation of an update function defined by f .

Example 6.15.1 Here is the usual imperative code for matrix multiplication.

```
def matmul(xss: Array[Array[Double]], yss: Array[Array[Double]]) = {
  val zss: Array[Array[Double]] = new Array(xss.length, yss.length)
  var i = 0
  while (i < xss.length) {
    var j = 0
    while (j < yss(0).length) {
      var acc = 0.0
      var k = 0
      while (k < yss.length) {
        acc = acc + xss(i)(k) * yss(k)(j)
        k += 1
      }
      zss(i)(j) = acc
      j += 1
    }
    i += 1
  }
  zss
}
```

Desugaring the array accesses and assignments yields the following expanded version:

```
def matmul(xss: Array[Array[Double]], yss: Array[Array[Double]]) = {
  val zss: Array[Array[Double]] = new Array(xss.length, yss.length)
  var i = 0
  while (i < xss.length) {
    var j = 0
    while (j < yss(0).length) {
      var acc = 0.0
      var k = 0
      while (k < yss.length) {
        acc = acc + xss.apply(i).apply(k) * yss.apply(k).apply(j)
        k += 1
      }
      zss.apply(i).update(j, acc)
      j += 1
    }
    i += 1
  }
  zss
}
```

6.16 Conditional Expressions

Syntax:

`Expr1 ::= 'if' '(' Expr ')' {nl} Expr [[semi] 'else' Expr]`

The conditional expression `if (e1) e2 else e3` chooses one of the values of `e2` and `e3`, depending on the value of `e1`. The condition `e1` is expected to conform to type `Boolean`. The then-part `e2` and the else-part `e3` are both expected to conform to the expected type of the conditional expression. The type of the conditional expression is the least upper bound of the types of `e1` and `e2`. A semicolon preceding the `else` symbol of a conditional expression is ignored.

The conditional expression is evaluated by evaluating first `e1`. If this evaluates to `true`, the result of evaluating `e2` is returned, otherwise the result of evaluating `e3` is returned.

A short form of the conditional expression eliminates the else-part. The conditional expression `if (e1) e2` is evaluated as if it was `if (e1) e2 else ()`. The type of this expression is `Unit` and the then-part `e2` is also expected to conform to type `Unit`.

6.17 While Loop Expressions

Syntax:

`Expr1 ::= 'while' '(' Expr ')' {nl} Expr`

The while loop expression `while (e1) e2` is typed and evaluated as if it was an application of `whileLoop (e1) (e2)` where the hypothetical function `whileLoop` is defined as follows.

```
def whileLoop(cond: => Boolean)(body: => Unit): Unit =
  if (cond) { body ; whileLoop(cond)(body) } else {}
```

6.18 Do Loop Expressions

Syntax:

`Expr1 ::= 'do' Expr [semi] 'while' '(' Expr ')'`

The do loop expression `do e1 while (e2)` is typed and evaluated as if it was the expression `(e1 ; while (e2) e1)`. A semicolon preceding the `while` symbol of a do loop expression is ignored.

6.19 For-Comprehensions

Syntax:

```

Expr1      ::= 'for' ((' Enumerators ') | '{' Enumerators '}')
              {nl} ['yield'] Expr
Enumerators ::= Generator {semi Enumerator}
Enumerator  ::= Generator
              | Guard
              | 'val' Pattern1 '=' Expr
Generator   ::= Pattern1 '<-' Expr [Guard]
Guard       ::= 'if' PostfixExpr

```

A comprehension **for** (*enums*) **yield** *e* evaluates expression *e* for each binding generated by the enumerators *enums*. An enumerator sequence always starts with a generator; this can be followed by further generators, value definitions, or guards. A *generator* *p* <- *e* produces bindings from an expression *e* which is matched in some way against pattern *p*. A *value definition* **val** *p* = *e* binds the value name *p* (or several names in a pattern *p*) to the result of evaluating the expression *e*. A *guard* **if** *e* contains a boolean expression which restricts enumerated bindings. The precise meaning of generators and guards is defined by translation to invocations of four methods: `map`, `filter`, `flatMap`, and `foreach`. These methods can be implemented in different ways for different carrier types.

The translation scheme is as follows. In a first step, every generator *p* <- *e*, where *p* is not irrefutable (§8.1) for the type of *e* is replaced by

```
p <- e.filter { case p => true; case _ => false }
```

Then, the following rules are applied repeatedly until all comprehensions have been eliminated.

- A for-comprehension **for** (*p* <- *e*) **yield** *e'* is translated to *e*.map { **case** *p* => *e'* }.
- A for-comprehension **for** (*p* <- *e*) *e'* is translated to *e*.foreach { **case** *p* => *e'* }.
- A for-comprehension

```
for (p <- e; p' <- e' ...) yield e'' ,
```

where ... is a (possibly empty) sequence of generators or guards, is translated to

```
e.flatMap { case p => for (p' <- e' ...) yield e'' } .
```

- A for-comprehension

for ($p \leftarrow e; p' \leftarrow e' \dots$) e'' .

where \dots is a (possibly empty) sequence of generators or guards, is translated to

$e.\text{foreach } \{ \text{case } p \Rightarrow \text{for } (p' \leftarrow e' \dots) e'' \} .$

- A generator $p \leftarrow e$ followed by a guard **if** g is translated to a single generator $p \leftarrow e.\text{filter}((x_1, \dots, x_n) \Rightarrow g)$ where x_1, \dots, x_n are the free variables of p .
- A generator $p \leftarrow e$ followed by a value definition **val** $p' = e'$ is translated to the following generator of pairs of values, where x and x' are fresh names:

val (p, p') \leftarrow
for ($x@p \leftarrow e$) **yield** { **val** $x'@p' = e'$; (x, x') }

Example 6.19.1 The following code produces all pairs of numbers between 1 and $n - 1$ whose sums are prime.

```
for { i <- 1 until n
      j <- 1 until i
      if isPrime(i+j)
    } yield (i, j)
```

The for-comprehension is translated to:

```
(1 until n)
  .flatMap {
    case i => (1 until i)
      .filter { j => isPrime(i+j) }
      .map { case j => (i, j) } }
```

Example 6.19.2 For comprehensions can be used to express vector and matrix algorithms concisely. For instance, here is a function to compute the transpose of a given matrix:

```
def transpose[A](xss: Array[Array[A]]) {
  for (i <- Array.range(0, xss(0).length)) yield
    Array(for (xs <- xss) yield xs(i))
}
```

Here is a function to compute the scalar product of two vectors:

```
def scalprod(xs: Array[Double], ys: Array[Double]) {
  var acc = 0.0
  for ((x, y) <- xs zip ys) acc = acc + x * y
  acc
}
```

Finally, here is a function to compute the product of two matrices. Compare with the imperative version of Example 6.15.1.

```
def matmul(xss: Array[Array[Double]], yss: Array[Array[Double]]) = {  
  val ysst = transpose(yss)  
  for (xs <- xss) yield  
    for (yst <- ysst) yield  
      scalprod(xs, yst)  
}
```

The code above makes use of the fact that `map`, `flatMap`, `filter`, and `foreach` are defined for members of class `scala.Array`.

6.20 Return Expressions

Syntax:

```
Expr1 ::= 'return' [Expr]
```

A return expression **return** *e* must occur inside the body of some enclosing named method or function. The innermost enclosing named method or function, *f*, must have an explicitly declared result type, and the type of *e* must conform to it. The return expression evaluates the expression *e* and returns its value as the result of *f*. The evaluation of any statements or expressions following the return expression is omitted. The type of a return expression is `scala.Nothing`.

If the return expression is itself part of a closure, it is possible that the enclosing instance of *f* has already returned before the return expression is executed. In that case, a `scala.runtime.NonLocalReturnException` is thrown.

6.21 Throw Expressions

Syntax:

```
Expr1 ::= 'throw' Expr
```

A throw expression **throw** *e* evaluates the expression *e*. The type of this expression must conform to `Throwable`. If *e* evaluates to an exception reference, evaluation is aborted with the thrown exception. If *e* evaluates to **null**, evaluation is instead aborted with a `NullPointerException`. If there is an active **try** expression (§6.22) which handles the thrown exception, evaluation resumes with the handler; otherwise the thread executing the **throw** is aborted. The type of a throw expression is `scala.Nothing`.

6.22 Try Expressions

Syntax:

```
Expr1 ::= 'try' '{' Block '}' ['catch' '{' CaseClauses '}']
        ['finally' Expr]
```

A try expression is of the form **try** { *b* } **catch** *h* where the handler *h* is a pattern matching anonymous function (§8.5)

```
{ case p1 => b1 ... case pn => bn } .
```

This expression is evaluated by evaluating the block *b*. If evaluation of *b* does not cause an exception to be thrown, the result of *b* is returned. Otherwise the handler *h* is applied to the thrown exception. If the handler contains a case matching the thrown exception, the first such case is invoked. If the handler contains no case matching the thrown exception, the exception is re-thrown.

Let *pt* be the expected type of the try expression. The block *b* is expected to conform to *pt*. The handler *h* is expected conform to type `scala.PartialFunction[scala.Throwable, pt]`. The type of the try expression is the least upper bound of the type of *b* and the result type of *h*.

A try expression **try** { *b* } **finally** *e* evaluates the block *b*. If evaluation of *b* does not cause an exception to be thrown, the expression *e* is evaluated. If an exception is thrown during evaluation of *e*, the evaluation of the try expression is aborted with the thrown exception. If no exception is thrown during evaluation of *e*, the result of *b* is returned as the result of the try expression.

If an exception is thrown during evaluation of *b*, the finally block *e* is also evaluated. If another exception *e* is thrown during evaluation of *e*, evaluation of the try expression is aborted with the thrown exception. If no exception is thrown during evaluation of *e*, the original exception thrown in *b* is re-thrown once evaluation of *e* has completed. The block *b* is expected to conform to the expected type of the try expression. The finally expression *e* is expected to conform to type `Unit`.

A try expression **try** { *b* } **catch** *e*₁ **finally** *e*₂ is a shorthand for **try** { **try** { *b* } **catch** *e*₁ } **finally** *e*₂.

6.23 Anonymous Functions

Syntax:

```
Expr1      ::= (Bindings | Id) '=>' Expr
ResultExpr ::= (Bindings | Id [':' CompoundType]) '=>' Block
Bindings   ::= '(' Binding {',' Binding} ')'
Binding    ::= id [':' Type]
```

The anonymous function $(x_1: T_1, \dots, x_n: T_n) \Rightarrow e$ maps parameters x_i of types T_i to a result given by expression e . The scope of each formal parameter x_i is e . Formal parameters must have pairwise distinct names.

If the expected type of the anonymous function is of the form `scala.Functionn[S_1, \dots, S_n, R]`, the expected type of e is R and the type T_i of any of the parameters x_i can be omitted, in which case $T_i = S_i$ is assumed. If the expected type of the anonymous function is some other type, all formal parameter types must be explicitly given, and the expected type of e is undefined. The type of the anonymous function is `scala.Functionn[S_1, \dots, S_n, T]`, where T is the packed type (§6.1) of e . T must be equivalent to a type which does not refer to any of the formal parameters x_i .

The anonymous function is evaluated as the instance creation expression

```
new scala.Functionn[ $T_1, \dots, T_n, T$ ] {
  def apply( $x_1: T_1, \dots, x_n: T_n$ ):  $T = e$ 
}
```

In the case of a single untyped formal parameter, $(x) \Rightarrow e$ can be abbreviated to $x \Rightarrow e$. If an anonymous function $(x: T) \Rightarrow e$ with a single typed parameter appears as the result expression of a block, it can be abbreviated to $x: T \Rightarrow e$.

Example 6.23.1 Examples of anonymous functions:

```
x => x                                // The identity function

f => g => x => f(g(x))                  // Curried function composition

(x: Int, y: Int) => x + y              // A summation function

() => { count += 1; count }            // The function which takes an
// empty parameter list (),
// increments a non-local variable
// 'count' and returns the new value.
```

Placeholder Syntax for Anonymous Functions

Syntax:

```
SimpleExpr1 ::= '_'
```

An expression (of syntactic category Expr) may contain embedded underscore symbols `_` at places where identifiers are legal. Such an expression represents an anonymous function where subsequent occurrences of underscores denote successive parameters.

Define an *underscore section* to be an expression of the form `_: T` where T is a type,

or else of the form `_`, provided the underscore does not appear as the expression part of a type ascription `_: T`.

An expression e of syntactic category `Expr` *binds* an underscore section u , if the following two conditions hold: (1) e properly contains u , and (2) there is no other expression of syntactic category `Expr` which is properly contained in e and which itself properly contains u .

If an expression e binds underscore sections u_1, \dots, u_n , in this order, it is equivalent to the anonymous function $(u'_1, \dots, u'_n) \Rightarrow e'$ where each u'_i results from u_i by replacing the underscore with a fresh identifier and e' results from e by replacing each underscore section u_i by u'_i .

Example 6.23.2 The anonymous functions in the left column use placeholder syntax. Each of these is equivalent to the anonymous function on its right.

<code>_ + 1</code>	<code>x => x + 1</code>
<code>_ * _</code>	<code>(x1, x2) => x1 * x2</code>
<code>(_: Int) * 2</code>	<code>(x: Int) => (x: Int) * 2</code>
<code>if (_) x else y</code>	<code>z => if (z) x else y</code>
<code>_.map(f)</code>	<code>x => x.map(f)</code>
<code>_.map(_ + 1)</code>	<code>x => x.map(y => y + 1)</code>

6.24 Statements

Syntax:

```

BlockStat ::= Import
           | ['implicit'] Def
           | {LocalModifier} TmplDef
           | Expr1
           |
TemplateStat ::= Import
              | {Annotation} {Modifier} Def
              | {Annotation} {Modifier} Dcl
              | Expr
              |

```

Statements occur as parts of blocks and templates. A statement can be an import, a definition or an expression, or it can be empty. Statements used in the template of a class definition can also be declarations. An expression that is used as a statement can have an arbitrary value type. An expression statement e is evaluated by evaluating e and discarding the result of the evaluation.

Block statements may be definitions which bind local names in the block. The only modifiers allowed in block-local definitions are modifiers **abstract**, **final**, or

sealed preceding a class or object definition.

Evaluation of a statement sequence entails evaluation of the statements in the order they are written.

6.25 Implicit Conversions

Implicit conversions can be applied to expressions whose type does not match their expected type, as well as to unapplied methods. The available implicit conversions are given in the next two sub-sections.

We say, a type T is *compatible* to a type U if T conforms to U after applying eta-expansion (§6.25.5) and view applications (§7.3).

6.25.1 Value Conversions

The following five implicit conversions can be applied to an expression e which has some value type T and which is type-checked with some expected type pt .

Overloading Resolution. If an expression denotes several possible members of a class, overloading resolution (§6.25.3) is applied to pick a unique member.

Type Instantiation. An expression e of polymorphic type

$$[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]T$$

which does not appear as the function part of a type application is converted to a type instance of T by determining with local type inference (§6.25.4) instance types T_1, \dots, T_n for the type variables a_1, \dots, a_n and implicitly embedding e in the type application $e[T_1, \dots, T_n]$ (§6.8).

Numeric Literal Narrowing. If the expected type is `Byte`, `Short` or `Char`, and the expression e is an integer literal fitting in the range of that type, it is converted to the same literal in that type.

Value Discarding. If e has some value type and the expected type is `Unit`, e is converted to the expected type by embedding it in the term $\{ e; () \}$.

View Application. If none of the previous conversions applies, and the e 's type does not conform to the expected type pt , it is attempted to convert e to the expected type with a view (§7.3).

6.25.2 Method Conversions

The following four implicit conversions can be applied to methods which are not applied to some argument list.

Evaluation. A parameterless method m of type $\Rightarrow T$ is always converted to type T by evaluating the expression to which m is bound.

Implicit Application. If the method takes only implicit parameters, implicit arguments are passed following the rules of §7.2.

Eta Expansion. Otherwise, if the method is not a constructor, and the expected type pt is a function type $(Ts') \Rightarrow T'$ eta-expansion (§6.25.5) is performed on the expression e .

Empty Application. Otherwise, if e has method type $()T$, it is implicitly applied to the empty argument list, yielding $e()$.

6.25.3 Overloading Resolution

If an identifier or selection e references several members of a class, the context of the reference is used to identify a unique member. The way this is done depends on whether or not e is used as a function. Let \mathcal{A} be the set of members referenced by e .

Assume first that e appears as a function in an application, as in $e(args)$. If there is precisely one alternative in \mathcal{A} which is a (possibly polymorphic) method type whose arity matches the number of arguments given, that alternative is chosen.

Otherwise, let Ts be the vector of types obtained by typing each argument with an undefined expected type. One determines first the set of applicable alternatives. A method type alternative is *applicable* if each type in Ts is compatible with the corresponding formal parameter type in the alternative, and, if the expected type is defined, the method's result type is compatible to it. A polymorphic method type is applicable if local type inference can determine type arguments so that the instantiated method type is applicable.

Let \mathcal{B} be the set of applicable alternatives. It is an error if \mathcal{B} is empty. Otherwise, one chooses the *most specific* alternative among the alternatives in \mathcal{B} , according to the following definition of being “more specific”.

- A method type $(Ts)U$ is more specific than some other type S if S is applicable to arguments (ps) of types Ts .
- A polymorphic method type $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]T$ is more specific than some other type S if T is more specific than S under the

assumption that for $i = 1, \dots, n$ each a_i is an abstract type name bounded from below by L_i and from above by U_i .

- Any other type is always more specific than a parameterized method type or a polymorphic type.

It is an error if there is no unique alternative in \mathcal{B} which is more specific than all other alternatives in \mathcal{B} .

Assume next that e appears as a function in a type application, as in $e[\text{targs}]$. Then we choose all alternatives in \mathcal{A} which take the same number of type parameters as there are type arguments in targs . It is an error if no such alternative exists. If there are several such alternatives overloading resolution is applied again to the whole expression $e[\text{targs}]$.

Assume finally that e does not appear as a function in either an application or a type application. If an expected type is given, let \mathcal{B} be the set of those alternatives in \mathcal{A} which are compatible (§6.25) to it. Otherwise, let \mathcal{B} be the same as \mathcal{A} . We choose in this case the most specific alternative among all alternatives in \mathcal{B} . It is an error if there is no unique alternative in \mathcal{B} which is more specific than all other alternatives in \mathcal{B} .

In both cases, it is an error if the most specific alternative is defined in a class C , and there is another applicable alternative which is defined in a true subclass of C .

Example 6.25.1 Consider the following definitions:

```
class A extends B {}
def f(x: B, y: B) = ...
def f(x: A, y: B) = ...
val a: A
val b: B
```

Then the application $f(b, b)$ refers to the first definition of f whereas the application $f(a, a)$ refers to the second. Assume now we add a third overloaded definition

```
def f(x: B, y: A) = ...
```

Then the application $f(a, a)$ is rejected for being ambiguous, since no most specific applicable signature exists.

6.25.4 Local Type Inference

Local type inference infers type arguments to be passed to expressions of polymorphic type. Say e is of type $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]T$ and no explicit type parameters are given.

Local type inference converts this expression to a type application $e[T_1, \dots, T_n]$. The choice of the type arguments T_1, \dots, T_n depends on the context in which the

expression appears and on the expected type pt . There are three cases.

Case 1: Selections. If the expression appears as the prefix of a selection with a name x , then type inference is *deferred* to the whole expression $e.x$. That is, if $e.x$ has type S , it is now treated as having type $[a_1 >: L_1 <: U_1, \dots, a_n >: L_n <: U_n]S$, and local type inference is applied in turn to infer type arguments for a_1, \dots, a_n , using the context in which $e.x$ appears.

Case 2: Values. If the expression e appears as a value without being applied to value arguments, the type arguments are inferred by solving a constraint system which relates the expression's type T with the expected type pt . Without loss of generality we can assume that T is a value type; if it is a method type we apply eta-expansion (§6.25.5) to convert it to a function type. Solving means finding a substitution σ of types T_i for the type parameters a_i such that

- All type parameter bounds are respected, i.e. $\sigma L_i <: \sigma a_i$ and $\sigma a_i <: \sigma U_i$ for $i = 1, \dots, n$.
- The expression's type conforms to the expected type, i.e. $\sigma T <: \sigma pt$.

It is a compile time error if no such substitution exists. If several substitutions exist, local-type inference will choose for each type variable a_i a minimal or maximal type T_i of the solution space. A *maximal* type T_i will be chosen if the type parameter a_i appears contravariantly (§4.5) in the type T of the expression. A *minimal* type T_i will be chosen in all other situations, i.e. if the variable appears covariantly, non-variantly or not at all in the type T . We call such a substitution an *optimal solution* of the given constraint system for the type T .

Case 3: Methods. The last case applies if the expression e appears in an application $e(d_1, \dots, d_m)$. In that case T is a method type $(R_1, \dots, R_m)T'$. Without loss of generality we can assume that the result type T' is a value type; if it is a method type we apply eta-expansion (§6.25.5) to convert it to a function type. One computes first the types S_j of the argument expressions d_j , using two alternative schemes. Each argument expression d_j is typed first with the expected type R_j , in which the type parameters a_1, \dots, a_n are taken as type constants. If this fails, the argument d_j is typed instead with an expected type R'_j which results from R_j by replacing every type parameter in a_1, \dots, a_n with *undefined*.

In a second step, type arguments are inferred by solving a constraint system which relates the method's type with the expected type pt and the argument types S_1, \dots, S_m . Solving the constraint system means finding a substitution σ of types T_i for the type parameters a_i such that

- All type parameter bounds are respected, i.e. $\sigma L_i <: \sigma a_i$ and $\sigma a_i <: \sigma U_i$ for $i = 1, \dots, n$.

- The method's result type T' conforms to the expected type, i.e. $\sigma T' <: \sigma pt$.
- Each argument type conforms to the corresponding formal parameter type, i.e. $\sigma S_j <: \sigma R_j$ for $j = 1, \dots, m$.

It is a compile time error if no such substitution exists. If several solutions exist, an optimal one for the type T' is chosen.

All or parts of an expected type pt may be undefined. The rules for conformance (§3.5.2) are extended to this case by adding the rule that for any type T the following two statements are always true:

$$undefined <: T \quad \text{and} \quad T <: undefined.$$

It is possible that no minimal or maximal solution for a type variable exists, in which case a compile-time error results. Because $<:$ is a pre-order, it is also possible that a solution set has several optimal solutions for a type. In that case, a Scala compiler is free to pick any one of them.

Example 6.25.2 Consider the two methods:

```
def cons[A](x: A, xs: List[A]): List[A] = x :: xs
def nil[B]: List[B] = Nil
```

and the definition

```
val xs = cons(1, nil) .
```

The application of `cons` is typed with an undefined expected type. This application is completed by local type inference to `cons[Int](1, nil)`. Here, one uses the following reasoning to infer the type argument `Int` for the type parameter `a`:

First, the argument expressions are typed. The first argument `1` has type `Int` whereas the second argument `nil` is itself polymorphic. One tries to type-check `nil` with an expected type `List[a]`. This leads to the constraint system

```
List[b?] <: List[a]
```

where we have labeled `b?` with a question mark to indicate that it is a variable in the constraint system. Because class `List` is covariant, the optimal solution of this constraint is

```
b = scala.Nothing .
```

In a second step, one solves the following constraint system for the type parameter `a` of `cons`:

```
Int <: a?
List[scala.Nothing] <: List[a?]
List[a?] <: undefined
```

The optimal solution of this constraint system is

```
a = Int ,
```

so `Int` is the type inferred for `a`.

Example 6.25.3 Consider now the definition

```
val ys = cons("abc", xs)
```

where `xs` is defined of type `List[Int]` as before. In this case local type inference proceeds as follows.

First, the argument expressions are typed. The first argument `"abc"` has type `String`. The second argument `xs` is first tried to be typed with expected type `List[a]`. This fails, as `List[Int]` is not a subtype of `List[a]`. Therefore, the second strategy is tried; `xs` is now typed with expected type `List[undefined]`. This succeeds and yields the argument type `List[Int]`.

In a second step, one solves the following constraint system for the type parameter `a` of `cons`:

```
String <: a?
List[Int] <: List[a?]
List[a?] <: undefined
```

The optimal solution of this constraint system is

```
a = scala.Any ,
```

so `scala.Any` is the type inferred for `a`.

6.25.5 Eta Expansion

Eta-expansion converts an expression of method type to an equivalent expression of function type. It proceeds in two steps.

First, one identifies the maximal sub-expressions of e ; let's say these are e_1, \dots, e_m . For each of these, one creates a fresh name x_i . Let e' be the expression resulting from replacing every maximal subexpression e_i in e by the corresponding fresh name x_i . Second, one creates a fresh name y_i for every argument type T_i of the method ($i = 1, \dots, n$). The result of eta-conversion is then:

```
{ val x1 = e1;
  ...
  val xm = em;
  (y1 : T1, ..., yn : Tn) => e'(y1, ..., yn)
}
```

If the expression e has a single call-by-name parameter (i.e. it is of type $(\Rightarrow T)U$, for some types T and U), eta-expansion of e yields a value of type `ByNameFunction`. The latter is defined as follows.

```
trait ByNameFunction[-A, +B] extends AnyRef {  
  def apply(x:  $\Rightarrow$  A): B  
  override def toString = "<function>"  
}
```

Eta expansion is not applicable to methods where a call-by-name parameter appears together with other parameters in one parameter section. Neither is it applicable to methods with repeated parameters $x: T^*$ (§4.6.2).

Chapter 7

Implicit Parameters and Views

7.1 The Implicit Modifier

Syntax:

```
LocalModifier ::= 'implicit'
ParamClauses  ::= {ParamClause} [nl] '(' 'implicit' Params ')'
```

Template members and parameters labeled with an **implicit** modifier can be passed to implicit parameters (§7.2) and can be used as implicit conversions called views (§7.3). The **implicit** modifier is illegal for all type members, as well as for top-level (§9.2) objects.

Example 7.1.1 The following code defines an abstract class of monoids and two concrete implementations, `StringMonoid` and `IntMonoid`. The two implementations are marked implicit.

```
abstract class Monoid[A] extends SemiGroup[A] {
  def unit: A
}
object Monoids {
  implicit object stringMonoid extends Monoid[String] {
    def add(x: String, y: String): String = x.concat(y)
    def unit: String = ""
  }
  implicit object intMonoid extends Monoid[Int] {
    def add(x: Int, y: Int): Int = x + y
    def unit: Int = 0
  }
}
```

7.2 Implicit Parameters

An implicit parameter list (**implicit** p_1, \dots, p_n) marks the parameters p_1, \dots, p_n as implicit. A method or constructor can have only one implicit parameter list, and it must be the last parameter list given.

A method with implicit parameters can be applied to arguments just like a normal method. In this case the **implicit** label has no effect. However, if such a method misses arguments for its implicit parameters, such arguments will be automatically provided.

The actual arguments that are eligible to be passed to an implicit parameter of type T fall into two categories. First, eligible are all identifiers x that can be accessed at the point of the method call without a prefix and that denote an implicit definition (§7.1) or an implicit parameter. An eligible identifier may thus be a local name, or a member of an enclosing template, or it may have been made accessible without a prefix through an import clause (§4.7). Second, eligible are also all **implicit** members of some object that belongs to the implicit scope of the implicit parameter's type, T .

The *implicit scope* of a type T consists of all companion modules (§5.4) of classes that are associated with the implicit parameter's type. Here, we say a class C is *associated* with a type T , if it is a base class (§5.1.2) of some part of T . The *parts* of a type T are:

- if T is a compound type T_1 **with** ... **with** T_n , the union of the parts of T_1, \dots, T_n , as well as T itself,
- if T is a parameterized type $S[T_1, \dots, T_n]$, the union of the parts of S and T_1, \dots, T_n ,
- if T is a singleton type p .**type**, the parts of the type of p ,
- if T is a type projection $S\#U$, the parts of S as well as T itself,
- in all other cases, just T itself.

If there are several eligible arguments which match the implicit parameter's type, a most specific one will be chosen using the rules of static overloading resolution (§6.25.3).

Example 7.2.1 Assuming the classes from Example 7.1.1, here is a method which computes the sum of a list of elements using the monoid's `add` and `unit` operations.

```
def sum[A](xs: List)(implicit m: Monoid[A]): A =
  if (xs.isEmpty) m.unit
  else m.add(xs.head, sum(xs.tail))
```

The monoid in question is marked as an implicit parameter, and can therefore be inferred based on the type of the list. Consider for instance the call

```
sum(List(1, 2, 3))
```

in a context where `stringMonoid` and `intMonoid` are visible. We know that the formal type parameter `a` of `sum` needs to be instantiated to `Int`. The only eligible object which matches the implicit formal parameter type `Monoid[Int]` is `intMonoid` so this object will be passed as implicit parameter.

This discussion also shows that implicit parameters are inferred after any type arguments are inferred (§6.25.4).

Implicit methods can themselves have implicit parameters. An example is the following method from module `scala.List`, which injects lists into the `scala.Ordered` class, provided the element type of the list is also convertible to this type.

```
implicit def list2ordered[A](x: List[A])
  (implicit elem2ordered: A => Ordered[A]): Ordered[List[A]] =
  ...
```

Assume in addition a method

```
implicit def int2ordered(x: Int): Ordered[Int]
```

that injects integers into the `Ordered` class. We can now define a `sort` method over ordered lists:

```
sort(xs: List[A])(implicit a2ordered: A => Ordered[A]) = ...
```

We can apply `sort` to a list of lists of integers `yss: List[List[Int]]` as follows:

```
sort(yss)
```

The call above will be completed by passing two nested implicit arguments:

```
sort(yss)(xs: List[Int] => list2ordered[Int](xs)(int2ordered)) .
```

The possibility of passing implicit arguments to implicit arguments raises the possibility of an infinite recursion. For instance, one might try to define the following method, which injects *every* type into the `Ordered` class:

```
def magic[A](x: A)(implicit a2ordered: A => Ordered[A]): Ordered[A] =
  a2ordered(x)
```

Now, if one tried to apply `sort` to an argument `arg` of a type that did not have another injection into the `Ordered` class, one would obtain an infinite expansion:

```
sort(arg)(x => magic(x)(x => magic(x)(x => ... )))
```

To prevent such infinite expansions, we require that every implicit method defini-

tion is contractive.

A method definition is *contractive* if the type of every implicit parameter type is properly contained in the type that is obtained by removing all implicit parameters from the method type and converting the rest to a function type.

A type T is *contained* in a type U if one of the following holds:

- T is the same as some part of U ,
- U is a function type and T is not.
- U and T are both function types, and the arity of U is greater than the arity of T .
- U and T both parameterized types (including function types) with the same type constructor, and each type argument of T is contained in the corresponding type argument of U .

A type T is *properly contained* in a type U if T is contained in U and different from U .

Example 7.2.2 The type of `list2ordered` is

```
(List[A])(implicit A => Ordered[A]): Ordered[List[A]] .
```

This type is contractive, because the type of the implicit parameter, $A \Rightarrow \text{Ordered}[A]$, is properly contained in the function type of the method without implicit parameters, $\text{List}[A] \Rightarrow \text{Ordered}[\text{List}[A]]$.

The type of `magic` is

```
(A)(implicit A => Ordered[A]): Ordered[A] .
```

This type is not contractive, because the type of the implicit parameter, $A \Rightarrow \text{Ordered}[A]$, is the same as the function type of the method without implicit parameters.

7.3 Views

Implicit parameters and methods can also define implicit conversions called views. A *view* from type S to type T is defined by an implicit value which has function type $S \Rightarrow T$ or $(\Rightarrow S) \Rightarrow T$ or by a method convertible to a value of that type.

Views are applied in two situations.

1. If an expression e is of type T , and T does not conform to the expression's expected type pt . In this case an implicit v is searched which is applicable to e and whose result type conforms to pt . The search proceeds as in the case of

implicit parameters, where the implicit scope is the one of $T \Rightarrow pt$. If such a view is found, the expression e is converted to $v(e)$.

2. In a selection $e.m$ with e of type T , if the selector m does not denote a member of T . In this case, a view v is searched which is applicable to e and whose result contains a member named m . The search proceeds as in the case of implicit parameters, where the implicit scope is the one of T . If such a view is found, the selection $e.m$ is converted to $v(e).m$.

As for implicit parameters, overloading resolution is applied if there are several possible candidates.

Example 7.3.1 Class `scala.Ordered[A]` contains a method

```
def <= [B >: A](that: B)(implicit b2ordered: B => Ordered[B]): Boolean .
```

Assume two lists `xs` and `ys` of type `List[Int]` and assume that the `list2ordered` and `int2ordered` methods defined in §7.2 are in scope. Then the operation

```
xs <= ys
```

is legal, and is expanded to:

```
list2ordered(xs)(int2ordered).<=
  (ys)
  (xs => list2ordered(xs)(int2ordered))
```

The first application of `list2ordered` converts the list `xs` to an instance of class `Ordered`, whereas the second occurrence is part of an implicit parameter passed to the `<=` method.

7.4 View Bounds

Syntax:

```
TypeParam      ::= id ['>:' Type] ['<:' Type] ['<%' Type]
```

A type parameter A of a method or non-trait class may have a view bound $A <\% T$. In this case the type parameter may be instantiated to any type S which is convertible by application of a view to the bound T .

A method or class containing such a type parameter is treated as being equivalent to a method with a view parameter. E.g.

```
def f[A <% T](ps): R = ...
```

is expanded to

```
def  $f[A](ps)(\text{implicit } v: A \Rightarrow T): R = \dots$ 
```

where v is a fresh name for the implicit parameter. Since traits do not take constructor parameters, this translation does not work for them. Consequently, type-parameters in traits may not be view-bounded.

Example 7.4.1 The `<=` method mentioned in Example 7.3.1 can be declared more concisely as follows:

```
def <= [B >: A <% Ordered[B]](that: B): Boolean
```

Chapter 8

Pattern Matching

8.1 Patterns

Syntax:

```
Pattern      ::= Pattern1 { '|' Pattern1 }
Pattern1     ::= varid ':' TypePat
               | '_' ':' TypePat
               | Pattern2
Pattern2     ::= varid ['@' Pattern3]
               | Pattern3
Pattern3     ::= SimplePattern
               | SimplePattern {id [nl] SimplePattern}
SimplePattern ::= '_'
               | varid
               | Literal
               | StableId
               | StableId '(' [Patterns [',']] ')'
               | StableId '(' [Patterns ']' '_' '*' '(')
               | '(' [Patterns [',']] ')'
               | XmlPattern
Patterns     ::= Pattern {',' Patterns}
```

A pattern is built from constants, constructors, variables and type tests. Pattern matching tests whether a given value (or sequence of values) has the shape defined by a pattern, and, if it does, binds the variables in the pattern to the corresponding components of the value (or sequence of values). The same variable name may not be bound more than once in a pattern.

Example 8.1.1 Some examples of patterns are:

1. The pattern `ex: IOException` matches all instances of class `IOException`,

binding variable ex to the instance.

2. The pattern $\text{Some}(x)$ matches values of the form $\text{Some}(v)$, binding x to the argument value v of the Some constructor.
3. The pattern $(x, _)$ matches pairs of values, binding x to the first component of the pair. The second component is matched with a wildcard pattern.
4. The pattern $x :: y :: xs$ matches lists of length ≥ 2 , binding x to the list's first element, y to the list's second element, and xs to the remainder.
5. The pattern $1 \mid 2 \mid 3$ matches the integers between 1 and 3.

Pattern matching is always done in a context which supplies an expected type of the pattern. We distinguish the following kinds of patterns.

8.1.1 Variable Patterns

Syntax:

```
SimplePattern ::= '_'
               | varid
```

A variable pattern x is a simple identifier which starts with a lower case letter. It matches any value, and binds the variable name to that value. The type of x is the expected type of the pattern as given from outside. A special case is the wild-card pattern $_$ which is treated as if it was a fresh variable on each occurrence.

8.1.2 Typed Patterns

Syntax:

```
Pattern1 ::= varid ':' TypePat
           | '_' ':' TypePat
```

A typed pattern $x : T$ consists of a pattern variable x and a type pattern T . This pattern matches any value matched by the type pattern T (§8.2); it binds the variable name to that value.

8.1.3 Literal Patterns

Syntax:

```
SimplePattern ::= Literal
```

A literal pattern L matches any value that is equal (in terms of $==$) to the literal L . The type of L type must conform to the expected type of the pattern.

8.1.4 Stable Identifier Patterns

Syntax:

`SimplePattern ::= StableId`

A stable identifier pattern is a stable identifier r (§3.1). The type of r must conform to the expected type of the pattern. The pattern matches any value v such that $r == v$ (§12.1).

To resolve the syntactic overlap with a variable pattern, a stable identifier pattern may not be a simple name starting with a lower-case letter. However, it is possible to enclose a such a variable name in backquotes; then it is treated as a stable identifier pattern.

Example 8.1.2 Consider the following function definition:

```
def f(x: Int, y: Int) = x match {
  case y => ...
}
```

Here, y is a variable pattern, which matches any value. If we wanted to turn the pattern into a stable identifier pattern, this can be achieved as follows:

```
def f(x: Int, y: Int) = x match {
  case 'y' => ...
}
```

Now, the pattern matches the y parameter of the enclosing function f . That is, the match succeeds only if the x argument and the y argument of f are equal.

8.1.5 Constructor Patterns

Syntax:

`SimplePattern ::= StableId '(' [Patterns [',']] '('`

A constructor pattern is of the form $c(p_1, \dots, p_n)$ where $n \geq 0$. It consists of a stable identifier c , followed by element patterns p_1, \dots, p_n . The constructor c is a simple or qualified name which denotes a case class (§5.3.2). If the case class is monomorphic, then it must conform to the expected type of the pattern, and the formal parameter types of c 's primary constructor (§5.3) are taken as the expected types of the element patterns p_1, \dots, p_n . If the case class is polymorphic, then its type parameters are instantiated so that the instantiation of c conforms to the expected type of the pattern. The instantiated formal parameter types of c 's primary constructor are then taken as the expected types of the component patterns p_1, \dots, p_n . The pattern matches all objects created from constructor invocations $c(v_1, \dots, v_n)$ where each element pattern p_i matches the corresponding value v_i .

A special case arises when c 's formal parameter types end in a repeated parameter. This is further discussed in (§8.1.8).

8.1.6 Tuple Patterns

Syntax:

```
SimplePattern ::= '(' [Patterns [' ','']] ')'
```

A tuple pattern (p_1, \dots, p_n) is an alias for the constructor pattern `scala.Tuplen(p_1, \dots, p_n)`, where $n \geq 2$. The pattern may also be written with a trailing comma, i.e. $(p_1, \dots, p_n,)$. Unary tuple patterns can be expressed in this syntax only by using a trailing comma, i.e. $(p,)$. Finally, the empty tuple $()$ is the unique value of type `scala.Unit`.

8.1.7 Extractor Patterns

Syntax:

```
SimplePattern ::= StableId '(' [Patterns [' ','']] ')'
```

An extractor pattern $x(p_1, \dots, p_n)$ where $n \geq 0$ is of the same syntactic form as a constructor pattern. However, instead of a case class, the stable identifier x denotes an object which has a member method named `unapply` or `unapplySeq` that matches the pattern.

An `unapply` method in an object x *matches* the pattern $x(p_1, \dots, p_n)$ if it takes exactly one argument and one of the following applies:

$n = 0$ and `unapply`'s result type is `Boolean`. In this case the extractor pattern matches all values v for which `x.unapply(v)` yields **true**.

$n = 1$ and `unapply`'s result type is `Option[T]`, for some type T . In this case, the (only) argument pattern p_1 is typed in turn with expected type T . The extractor pattern matches then all values v for which `x.unapply(v)` yields a value of form `Some(v_1)`, and p_1 matches v_1 .

$n > 1$ and `unapply`'s result type is `Option[(T_1, \dots, T_n)]`, for some types T_1, \dots, T_n . In this case, the argument patterns p_1, \dots, p_n are typed in turn with expected types T_1, \dots, T_n . The extractor pattern matches then all values v for which `x.unapply(v)` yields a value of form `Some((v_1, \dots, v_n))`, and each pattern p_i matches the corresponding value v_i .

An `unapplySeq` method in an object x matches the pattern $x(p_1, \dots, p_n)$ if it takes exactly one argument and its result type is of the form `Option[S]`, where S is a subtype of `Seq[T]` for some element type T . This case is further discussed in (§8.1.8).

8.1.8 Pattern Sequences

Syntax:

`SimplePattern ::= StableId '(' [Patterns ','] '_' '*' '(')'`

A pattern sequence p_1, \dots, p_n appears in two contexts. First, in a constructor pattern $c(q_1, \dots, q_m, p_1, \dots, p_n)$, where c is a case class which has $m + 1$ primary constructor parameters, ending in a repeated parameter (§4.6.2) of type S^* . Second, in an extractor pattern $x(p_1, \dots, p_n)$ if the extractor object x has an `unapplySeq` method with a result type conforming to `Seq[S]`, but does not have an `unapply` method that matches p_1, \dots, p_n . The expected type for the pattern sequence is in each case the type S .

The last pattern in a pattern sequence may be a *sequence wildcard* `_*`. Each element pattern p_i is type-checked with S as expected type, unless it is a sequence wildcard. If a final sequence wildcard is present, the pattern matches all values v that are sequences which start with elements matching patterns p_1, \dots, p_{n-1} . If no final sequence wildcard is given, the pattern matches all values v that are sequences of length n which consist of elements matching patterns p_1, \dots, p_n .

8.1.9 Infix Operation Patterns

Syntax:

`Pattern3 ::= SimplePattern {id [nl] SimplePattern}`

An infix operation pattern $p \text{ op } q$ is a shorthand for the constructor or extractor pattern $\text{op}(p, q)$. The precedence and associativity of operators in patterns is the same as in expressions (§6.12).

An infix operation pattern $p \text{ op } (q_1, \dots, q_n)$ is a shorthand for the constructor or extractor pattern $\text{op}(p, q_1, \dots, q_n)$.

8.1.10 Pattern Alternatives

Syntax:

`Pattern ::= Pattern1 { '|' Pattern1 }`

A pattern alternative $p_1 \mid \dots \mid p_n$ consists of a number of alternative patterns p_i . All alternative patterns are type checked with the expected type of the pattern. They may not bind variables other than wildcards. The alternative pattern matches a value v if at least one its alternatives matches v .

8.1.11 XML Patterns

XML patterns are treated in §10.2.

8.1.12 Regular Expression Patterns

Regular expression patterns have been discontinued in Scala from version 2.0.

Later version of Scala provide a much simplified version of regular expression patterns that cover most scenarios of non-text sequence processing. A *sequence pattern* is a pattern that stands in a position where either (1) a pattern of a type T which is conforming to $\text{Seq}[A]$ for some A is expected, or (2) a case class constructor that has an iterated formal parameter A^* . A wildcard star pattern $_*$ in the rightmost position stands for arbitrary long sequences. It can be bound to variables, as usual, in which case the variable will have the type $\text{Seq}[A]$.

8.1.13 Irrefutable Patterns

A pattern p is *irrefutable* for a type T , if one of the following applies:

1. p is a variable pattern,
2. p is a typed pattern $x : T'$, and $T <: T'$,
3. p is a constructor pattern $c(p_1, \dots, p_n)$, the type T is an instance of class c , the primary constructor (§5.3) of type T has argument types T_1, \dots, T_n , and each p_i is irrefutable for T_i .

8.2 Type Patterns

Syntax:

TypePat ::= Type

Type patterns consist of types, type variables, and wildcards. A type pattern T is of one of the following forms:

- A reference to a class C , $p.C$, or $T\#C$. This type pattern matches any non-null instance of the given class. Note that the prefix of the class, if it is given, is relevant for determining class instances. For instance, the pattern $p.C$ matches only instances of classes C which were created with the path p as prefix.

The bottom types `scala.Nothing` and `scala.Null` cannot be used as type patterns, because they would match nothing in any case.

- A singleton type $p.type$. This type pattern matches only the value denoted by the path p (that is, a pattern match involved a comparison of the matched value with p using method `eq` in class `AnyRef`).
- A compound type pattern T_1 **with** ... **with** T_n where each T_i is a type pattern. This type pattern matches all values that are matched by each of the type patterns T_i .

- A parameterized type pattern $T[a_1, \dots, a_n]$, where the a_i are type variable patterns or wildcards $_$. This type pattern matches all values which match T for some arbitrary instantiation of the type variables and wildcards. The bounds or alias type of these type variable are determined as described in (§8.3).
- A parameterized type pattern `scala.Array[T_1]`, where T_1 is a type pattern. This type pattern matches any non-null instance of type `scala.Array[U_1]`, where U_1 is a type matched by T_1 .

Types which are not of one of the forms described above are also accepted as type patterns. However, such type patterns will be translated to their erasure (§3.6). The Scala compiler will issue an “unchecked” warning for these patterns to flag the possible loss of type-safety.

A *type variable pattern* is a simple identifier which starts with a lower case letter. However, the predefined primitive type aliases `Unit`, `Boolean`, `Byte`, `Short`, `Char`, `Int`, `Long`, `Float`, and `Double` are not classified as type variable patterns.

8.3 Type Parameter Inference in Patterns

Type parameter inference is the process of finding bounds for the bound type variables in a typed pattern or constructor pattern. Inference takes into account the expected type of the pattern.

Type parameter inference for typed patterns.. Assume a typed pattern $p : T'$. Let T result from T' where all wildcards in T' are renamed to fresh variable names. Let a_1, \dots, a_n be the type variables in T . These type variables are considered bound in the pattern. Let the expected type of the pattern be pt .

Type parameter inference constructs first a set of subtype constraints over the type variables a_i . The initial constraints set \mathcal{C}_0 reflects just the bounds of these type variables. That is, assuming T has bound type variables a_1, \dots, a_n which correspond to class type parameters a'_1, \dots, a'_n with lower bounds L_1, \dots, L_n and upper bounds U_1, \dots, U_n , \mathcal{C}_0 contains the constraints

$$\begin{aligned} a_i &<: \sigma U_i & (i = 1, \dots, n) \\ \sigma L_i &<: a_i & (i = 1, \dots, n) \end{aligned}$$

where σ is the substitution $[a'_1 := a_1, \dots, a'_n := a_n]$.

The set \mathcal{C}_0 is then augmented by further subtype constraints. There are two cases.

Case 1:. If there exists a substitution σ over the type variables a_i, \dots, a_n such that σT conforms to pt , one determines the weakest subtype constraints \mathcal{C}_1 over the type variables a_1, \dots, a_n such that $\mathcal{C}_0 \wedge \mathcal{C}_1$ implies that T conforms to pt .

Case 2:. Otherwise, if T can not be made to conform to pt by instantiating its type variables, one determines all type variables in pt which are defined as type parameters of a method enclosing the pattern. Let the set of such type parameters be b_1, \dots, b_m . Let \mathcal{C}'_0 be the subtype constraints reflecting the bounds of the type variables b_i . If T denotes an instance type of a final class, let \mathcal{C}_2 be the weakest set of subtype constraints over the type variables a_1, \dots, a_n and b_1, \dots, b_m such that $\mathcal{C}_0 \wedge \mathcal{C}'_0 \wedge \mathcal{C}_2$ implies that T conforms to pt . If T does not denote an instance type of a final class, let \mathcal{C}_2 be the weakest set of subtype constraints over the type variables a_1, \dots, a_n and b_1, \dots, b_m such that $\mathcal{C}_0 \wedge \mathcal{C}'_0 \wedge \mathcal{C}_2$ implies that it is possible to construct a type T' which conforms to both T and pt . It is a static error if there is no satisfiable set of constraints \mathcal{C}_2 with this property.

The final step consists in choosing type bounds for the type variables which imply the established constraint system. The process is different for the two cases above.

Case 1:. We take $a_i >: L_i <: U_i$ where each L_i is minimal and each U_i is maximal wrt $<:$ such that $a_i >: L_i <: U_i$ for $i = 1, \dots, n$ implies $\mathcal{C}_0 \wedge \mathcal{C}_1$.

Case 2:. We take $a_i >: L_i <: U_i$ and $b_j >: L'_j <: U'_j$ where each L_i and L'_j is minimal and each U_i and U'_j is maximal such that $a_i >: L_i <: U_i$ for $i = 1, \dots, n$ and $b_j >: L'_j <: U'_j$ for $j = 1, \dots, m$ implies $\mathcal{C}_0 \wedge \mathcal{C}'_0 \wedge \mathcal{C}_2$.

In both cases, local type inference is permitted to limit the complexity of inferred bounds. Minimality and maximality of types have to be understood relative to the set of types of acceptable complexity.

Type parameter inference for constructor patterns.. Assume a constructor pattern $C(p_1, \dots, p_n)$ where class C has type type parameters a_1, \dots, a_n . These type parameters are inferred in the same way as for the typed pattern $(_ : C[a_1, \dots, a_n])$.

Example 8.3.1 Consider the program fragment:

```
val x: Any
x match {
  case y: List[a] => ...
}
```

Here, the type pattern $List[a]$ is matched against the expected type Any . The pattern binds the type variable a . Since $List[a]$ conforms to Any for every type argument, there are no constraints on a . Hence, a is introduced as an abstract type with no bounds. The scope of a is right-hand side of its case clause.

On the other hand, if x is declared as

```
val x: List[List[String]],
```

this generates the constraint `List[a] <: List[List[String]]`, which simplifies to `a <: List[String]`, because `List` is covariant. Hence, `a` is introduced with upper bound `List[String]`.

Example 8.3.2 Consider the program fragment:

```
val x: Any
x match {
  case y: List[String] => ...
}
```

Scala does not maintain information about type arguments at run-time, so there is no way to check that `x` is a list of strings. Instead, the Scala compiler will erase (§3.6) the pattern to `List[_]`; that is, it will only test whether the top-level runtime-class of the value `x` conforms to `List`, and the pattern match will succeed if it does. This might lead to a class cast exception later on, in the case where the list `x` contains elements other than strings. The Scala compiler will flag this potential loss of type-safety with an “unchecked” warning message.

Example 8.3.3 Consider the program fragment

```
class Term[A]
class Number(val n: Int) extends Term[Int]
def f[B](t: Term[B]): B = t match {
  case y: Number => y.n
}
```

The expected type of the pattern `y: Number` is `Term[B]`. The type `Number` does not conform to `Term[B]`; hence Case 2 of the rules above applies. This means that `b` is treated as another type variable for which subtype constraints are inferred. In our case the applicable constraint is `Number <: Term[B]`, which entails `B = Int`. Hence, `B` is treated in the case clause as an abstract type with lower and upper bound `Int`. Therefore, the right hand side of the case clause, `y.n`, of type `Int`, is found to conform to the function’s declared result type, `Number`.

8.4 Pattern Matching Expressions

Syntax:

```
Expr          ::= PostfixExpr 'match' '{' CaseClauses '}'
CaseClauses   ::= CaseClause {CaseClause}
CaseClause    ::= 'case' Pattern [Guard] '=>' Block
```

A pattern matching expression

e match { **case** $p_1 \Rightarrow b_1$... **case** $p_n \Rightarrow b_n$ }

consists of a selector expression e and a number $n > 0$ of cases. Each case consists of a (possibly guarded) pattern p_i and a block b_i . Each p_i might be complemented by a guard **if** e where e is a boolean expression. The scope of the pattern variables in p_i comprises the pattern's guard and the corresponding block b_i .

Let T be the type of the selector expression e and let a_1, \dots, a_m be the type parameters of all methods enclosing the pattern matching expression. For every a_i , let L_i be its lower bound and U_i be its higher bound. Every pattern $p \in \{p_1, \dots, p_n\}$ can be typed in two ways. First, it is attempted to type p with T as its expected type. If this fails, p is instead typed with a modified expected type T' which results from T by replacing every occurrence of a type parameter a_i by *undefined*. If this second step fails also, a compile-time error results. If the second step succeeds, let T_p be the type of pattern p seen as an expression. One then determines minimal bounds L'_1, \dots, L'_m and maximal bounds U'_1, \dots, U'_m such that for all i , $L_i <: L'_i$ and $U'_i <: U_i$ and the following constraint system is satisfied:

$$L_1 <: a_1 <: U_1 \wedge \dots \wedge L_m <: a_m <: U_m \Rightarrow T_p <: T$$

If no such bounds can be found, a compile time error results. If such bounds are found, the pattern matching clause starting with p is then typed under the assumption that each a_i has lower bound L'_i instead of L_i and has upper bound U'_i instead of U_i .

The expected type of every block b_i is the expected type of the whole pattern matching expression. The type of the pattern matching expression is then the least upper bound of the types of all blocks b_i .

When applying a pattern matching expression to a selector value, patterns are tried in sequence until one is found which matches the selector value (§8.1). Say this case is **case** $p_i \Rightarrow b_i$. The result of the whole expression is then the result of evaluating b_i , where all pattern variables of p_i are bound to the corresponding parts of the selector value. If no matching pattern is found, a `scala.MatchError` exception is thrown.

The pattern in a case may also be followed by a guard suffix **if** e with a boolean expression e . The guard expression is evaluated if the preceding pattern in the case matches. If the guard expression evaluates to **true**, the pattern match succeeds as normal. If the guard expression evaluates to **false**, the pattern in the case is considered not to match and the search for a matching pattern continues.

In the interest of efficiency the evaluation of a pattern matching expression may try patterns in some other order than textual sequence. This might affect evaluation through side effects in guards. However, it is guaranteed that a guard expression is evaluated only if the pattern it guards matches.

If the selector of a pattern match is an instance of a **sealed** class (§5.2), the compilation of pattern matching can emit warnings which diagnose that a given set of

patterns is not exhaustive, i.e. that there is a possibility of a `MatchError` being raised at run-time.

Example 8.4.1 Consider the following definitions of arithmetic terms:

```
abstract class Term[T]
case class Lit(x: Int) extends Term[Int]
case class Succ(t: Term[Int]) extends Term[Int]
case class IsZero(t: Term[Int]) extends Term[Boolean]
case class If[T](c: Term[Boolean],
                 t1: Term[T],
                 t2: Term[T]) extends Term[T]
```

There are terms to represent numeric literals, incrementation, a zero test, and a conditional. Every term carries as a type parameter the type of the expression it represents (either `Int` or `Boolean`).

A type-safe evaluator for such terms can be written as follows.

```
def eval[T](t: Term[T]): T = t match {
  case Lit(n)          => n
  case Succ(u)          => eval(u) + 1
  case IsZero(u)        => eval(u) == 0
  case If(c, u1, u2)    => eval(if (eval(c)) u1 else u2)
}
```

Note that the evaluator makes crucial use of the fact that type parameters of enclosing methods can acquire new bounds through pattern matching.

For instance, the type of the pattern in the second case, `Succ(u)`, is `Int`. It conforms to the selector type `T` only if we assume an upper and lower bound of `Int` for `T`. Under the assumption `Int <: T <: Int` we can also verify that the type right hand side of the second case, `Int` conforms to its expected type, `T`.

8.5 Pattern Matching Anonymous Functions

Syntax:

```
BlockExpr ::= '{' CaseClauses '}'
```

An anonymous function can be defined by a sequence of cases

```
{ case  $p_1$  =>  $b_1$  ... case  $p_n$  =>  $b_n$  }
```

which appear as an expression without a prior `match`. The expected type of such an expression must in part be defined. It must be either `scala.Function k [S_1, \dots, S_k, R]` for some $k > 0$, or

`scala.PartialFunction[S1, R]`, where the argument type(s) S_1, \dots, S_k must be fully determined, but the result type R may be undetermined.

If the expected type is `scala.Functionk[S1, ..., Sk, R]`, the expression is taken to be equivalent to the anonymous function:

```
(x1:S1, ..., xk:Sk) => (x1, ..., xk) match {
  case p1 => b1 ... case pn => bn
}
```

Here, each x_i is a fresh name. As was shown in (§6.23), this anonymous function is in turn equivalent to the following instance creation expression, where T is the least upper bound of the types of all b_i .

```
new scala.Functionk[S1, ..., Sk, T] {
  def apply(x1:S1, ..., xk:Sk): T = (x1, ..., xk) match {
    case p1 => b1 ... case pn => bn
  }
}
```

If the expected type is `scala.PartialFunction[S, R]`, the expression is taken to be equivalent to the following instance creation expression:

```
new scala.PartialFunction[S, T] {
  def apply(x: S): T = x match {
    case p1 => b1 ... case pn => bn
  }
  def isDefinedAt(x: S): Boolean = {
    case p1 => true ... case pn => true
    case _ => false
  }
}
```

Here, x is a fresh name and T is the least upper bound of the types of all b_i . The final default case in the `isDefinedAt` method is omitted if one of the patterns p_1, \dots, p_n is already a variable or wildcard pattern.

Example 8.5.1 Here is a method which uses a fold-left operation `/:` to compute the scalar product of two vectors:

```
def scalarProduct(xs: Array[Double], ys: Array[Double]) =
  (0.0 /: (xs zip ys)) {
    case (a, (b, c)) => a + b * c
  }
```

The case clauses in this code are equivalent to the following anonymous function:

```
(x, y) => (x, y) match {
```

```
    case (a, (b, c)) => a + b * c  
  }
```


Chapter 9

Top-Level Definitions

9.1 Compilation Units

Syntax:

```
CompilationUnit ::= ['package' QualId semi] TopStatSeq
TopStatSeq     ::= TopStat {semi TopStat}
TopStat        ::= {Annotation} {Modifier} TmplDef
                | Import
                | Packaging
                |
QualId          ::= id {'.' id}
```

A compilation unit consists of a sequence of packagings, import clauses, and class and object definitions, which may be preceded by a package clause.

A compilation unit **package** *p*; *stats* starting with a package clause is equivalent to a compilation unit consisting of a single packaging **package** *p* { *stats* }.

Implicitly imported into every compilation unit are, in that order : the package `java.lang`, the package `scala`, and the object `scala.Predef` (§12.5). Members of a later import in that order hide members of an earlier import.

9.2 Packagings

Syntax:

```
Packaging      ::= package QualId [nl] '{' TopStatSeq '}'
```

A package is a special object which defines a set of member classes, objects and packages. Unlike other objects, packages are not introduced by a definition. In-

stead, the set of members of a package is determined by packagings.

A packaging **package** $p \{ ds \}$ injects all definitions in ds as members into the package whose qualified name is p . Members of a package are called *top-level* definitions. If a definition in ds is labeled **private**, it is visible only for other members in the package.

Selections $p.m$ from p as well as imports from p work as for objects. However, unlike other objects, packages may not be used as values. It is illegal to have a package with the same fully qualified name as a module or a class.

Top-level definitions outside a packaging are assumed to be injected into a special empty package. That package cannot be named and therefore cannot be imported. However, members of the empty package are visible to each other without qualification.

9.3 Package References

Syntax:

QualId ::= id { '.' id }

A reference to a package takes the form of a qualified identifier. Like all other references, package references are relative. That is, a package reference starting in a name p will be looked up in the closest enclosing scope that defines a member named p .

The special predefined name `_root_` refers to the outermost root package which contains all top-level packages.

Example 9.3.1 Consider the following program:

```
package b {  
  class B  
}  
  
package a.b {  
  class A {  
    val x = new _root_.B  
  }  
}
```

Here, the reference `_root_.B` refers to class B in the toplevel package b. If the `_root_` prefix had been omitted, the name b would instead resolve to the package a.b, and, provided that package does not also contain a class B, a compiler-time error would result.

9.4 Programs

A *program* is a top-level object that has a member method `main` of type `(Array[String])Unit`. Programs can be executed from a command shell. The program's command arguments are passed to the `main` method as a parameter of type `Array[String]`.

The `main` method of a program can be directly defined in the object, or it can be inherited. The `scala` library defines a class `scala.Application` that defines an empty inherited `main` method. An object *m* inheriting from this class is thus a program, which executes the initialization code of the object *m*.

Example 9.4.1 The following example will create a hello world program by defining a method `main` in module `test.HelloWorld`.

```
package test
object HelloWorld {
  def main(args: Array[String]) { println("hello world") }
}
```

This program can be started by the command

```
scala test.HelloWorld
```

In a Java environment, the command

```
java test.HelloWorld
```

would work as well.

`HelloWorld` can also be defined without a `main` method by inheriting from `Application` instead:

```
package test
object HelloWorld extends Application {
  println("hello world")
}
```


Chapter 10

XML expressions and patterns

By Burak Emir

This chapter describes the syntactic structure of XML expressions and patterns. It follows as close as possible the XML 1.0 specification [W3C], changes being mandated by the possibility of embedding Scala code fragments.

10.1 XML expressions

XML expressions are expressions generated by the following production, where the opening bracket ‘<’ of the first element must be in a position to start the lexical XML mode (§1.5).

Syntax:

```
XmlExpr ::= XmlContent {Element}
```

Well-formedness constraints of the XML specification apply, which means for instance that start tags and end tags must match, and attributes may only be defined once, with the exception of constraints related to entity resolution.

The following productions describe Scala’s extensible markup language, designed as close as possible to the W3C extensible markup language standard. Only the productions for attribute values and character data are changed. Scala does not support neither declarations, CDATA sections nor processing instructions. Entity references are not resolved at runtime.

Syntax:

```
Element      ::=      EmptyElemTag  
                |      STag Content ETag
```

```

EmptyElemTag ::= '<' Name {S Attribute} [S] '>'

STag          ::= '<' Name {S Attribute} [S] '>'
ETag          ::= '</' Name [S] '>'
Content       ::= [CharData] {Content1 [CharData]}
Content1      ::= XmlContent
                | Reference
                | ScalaExpr
XmlContent    ::= Element
                | CDsect
                | PI
                | Comment

```

If an XML expression is a single element, its value is a runtime representation of an XML node (an instance of a subclass of `scala.xml.Node`). If the XML expression consists of more than one element, then its value is a runtime representation of a sequence of XML nodes (an instance of a subclass of `scala.Seq[scala.xml.Node]`).

If an XML expression is an entity reference, CDATA section, processing instructions or a comments, it is represented by an instance of the corresponding Scala runtime class.

By default, beginning and trailing whitespace in element content is removed, and consecutive occurrences of whitespace are replaced by a single space character `\u0020`. This behavior can be changed to preserve all whitespace with a compiler option. **Syntax:**

```

Attribute ::= Name Eq AttValue

AttValue  ::=  '"' {CharQ | CharRef} '"'
              |  "'" {CharA | CharRef} "'"
              |  ScalaExp

ScalaExpr ::= '{' expr '}'

CharData  ::= { CharNoRef } without {CharNoRef}{'CharB {CharNoRef}
                                     and without {CharNoRef}']>'{CharNoRef}

```

XML expressions may contain Scala expressions as attribute values or within nodes. In the latter case, these are embedded using a single opening brace `{` and ended by a closing brace `}`. To express a single opening braces within XML text as generated by `CharData`, it must be doubled. Thus, `{{` represents the XML text `"` and does not introduce an embedded Scala expression.

Syntax:

BaseChar, Char, Comment, CombiningChar, Ideographic, NameChar, S, Reference

```

::= "as in W3C XML"

Char1      ::= Char without '<' | '&'
CharQ      ::= Char1 without '"'
CharA      ::= Char1 without "'"
CharB      ::= Char1 without '{'

Name        ::= XNameStart {NameChar}

XNameStart  ::= '_' | BaseChar | Ideographic
               (as in W3C XML, but without ':')

```

10.2 XML patterns

XML patterns are patterns generated by the following production, where the opening bracket '`<`' of the element patterns must be in a position to start the lexical XML mode (§1.5).

Syntax:

```
XmlPattern ::= ElementPattern
```

Well-formedness constraints of the XML specification apply.

An XML pattern has to be a single element pattern. It matches exactly those runtime representations of an XML tree that have the same structure as described by the pattern. XML patterns may contain Scala patterns (§8.4).

Whitespace is treated the same way as in XML expressions. Patterns that are entity references, CDATA sections, processing instructions and comments match runtime representations which are the the same.

By default, beginning and trailing whitespace in element content is removed, and consecutive occurrences of whitespace are replaced by a single space character `\u0020`. This behavior can be changed to preserve all whitespace with a compiler option.

Syntax:

```

ElemPattern  ::=      EmptyElemTagP
                   |      STagP ContentP ETagP

EmptyElemTagP ::=      '<' Name [S] '>'
STagP         ::=      '<' Name [S] '>'
ETagP         ::=      '</' Name [S] '>'
ContentP      ::=      [CharData] {(ElemPattern|ScalaPatterns) [CharData]}
ContentP1     ::=      ElemPattern

```

```
          | Reference
          | CDsect
          | PI
          | Comment
          | ScalaPatterns
ScalaPatterns ::= '{' patterns '}'
```

Chapter 11

User-Defined Annotations

Syntax:

```
Annotation      ::= '@' AnnotationExpr [nl]
AnnotationExpr  ::= Constr ['{' {NameValuePair} '}']
NameValuePair    ::= val id '=' PrefixExpr
```

User-defined annotations associate meta-information with definitions. A simple annotation has the form `@c` or `@c(a1, ..., an)`. Here, *c* is a constructor of a class *C*, which must conform to the class `scala.Annotation`. The constructor may be optionally followed by a list of name/value pairs in braces, e.g. `{n1 = c1, ..., nk = ck}`. All values *c*_{*i*} in that list must be constant expressions, as defined below.

Annotations may apply to definitions or declarations, types, or expressions. An annotation of a definition or declaration appears in front of that definition. An annotation of a type appears after that type. An annotation of an expression *e* appears after the expression *e*, separated by a colon. More than one annotation clause may apply to an entity. The order in which these annotations are given does not matter.

Examples:

```
@serializable class C { ... }           // A class annotation.
@transient @volatile var m: Int         // A variable annotation
String @local                            // A type annotation
(e: @unchecked) match { ... }           // An expression annotation
```

The meaning of annotation clauses is implementation-dependent. On the Java platform, the following annotations have a standard meaning.

@transient

Marks a field to be non-persistent; this is equivalent to the `transient` modifier in Java.

@volatile

Marks a field which can change its value outside the control of the program; this is equivalent to the `volatile` modifier in Java.

@serializable

Marks a class to be serializable; this is equivalent to inheriting from the `java.io.Serializable` interface in Java.

@SerialVersionUID(<longlit>)

Attaches a serial version identifier (a long constant) to a class. This is equivalent to a the following field definition in Java:

```
private final static SerialVersionUID = <longlit>
```

@throws(<classlit>)

A Java compiler checks that a program contains handlers for checked exceptions by analyzing which checked exceptions can result from execution of a method or constructor. For each checked exception which is a possible result, the throws clause for the method or constructor must mention the class of that exception or one of the superclasses of the class of that exception. Since Scala has no checked exceptions, Scala methods must be annotated with one or more throws annotations such that Java code can catch exceptions thrown by a Scala method.

@deprecated

Marks a definition as deprecated. Accesses to the defined entity will then cause a deprecated warnig to be issued from the compiler. Deprecated warnings are suppressed in code that belongs itself to a definition that is labeled deprecated.

@scala.reflect.BeanProperty

When prefixed to a definition of some variable `X`, this annotation causes getter and setter methods `getX`, `setX` in the Java bean style to be added in the class containing the variable. The first letter of the variable appears capitalized after the `get` or `set`. When the annotation is added to the definition of an immutable value definition `X`, only a getter is generated. The construction of these methods is part of code-generation; therefore, these methods become visible only once a classfile for the containing class is generated.

@unchecked

When applied to the selector of a **match** expression, this attribute suppresses any warnings about non-exhaustive pattern matches which would otherwise be emitted. For instance, no warnings would be produced for the method definition below.

```
def f(x: Option[Int]) = (x: @unchecked) match {  
  case Some(y) => y  
}
```

Without the @unchecked annotation, a Scala compiler could infer that the pattern match is non-exhaustive, and could produce a warning because `Option` is a **sealed** class.

Other annotations may be interpreted by platform- or application-dependent tools. Class `scala.Annotation` has two sub-traits which are used to indicate how these annotations are retained. Instances of an annotation class inheriting from trait `scala.ClassfileAnnotation` will be stored in the generated class files. Instances of an annotation class inheriting from trait `scala.StaticAnnotation` will be visible to the Scala type-checker in every compilation unit where the annotated symbol is accessed. An annotation class can inherit from both `scala.ClassfileAnnotation` and `scala.StaticAnnotation`. If an annotation class inherits from neither `scala.ClassfileAnnotation` nor `scala.StaticAnnotation`, its instances are visible only locally during the compilation run that analyzes them.

Classes inheriting from `scala.ClassfileAnnotation` may be subject to further restrictions in order to assure that they can be mapped to the host environment. In particular, on both the Java and the .NET platforms, such classes must be toplevel; i.e. they may not be contained in another class or object. Additionally, on both Java and .NET, all constructor arguments must be constant expressions.

The definition of “constant expressions” depends on the platform, but must include at least the expressions of the following forms:

- A literal of a value class, such as an integer
- A string literal
- A class constructed with `classOf`
- An element of an enumeration from the underlying platform
- A literal array, of the form `@Array(c_1, \dots, c_n)`, where all of the c_i ’s are themselves constant expressions

Chapter 12

The Scala Standard Library

The Scala standard library consists of the package `scala` with a number of classes and modules. Some of these classes are described in the following.

12.1 Root Classes

Figure 12 illustrates Scala's class hierarchy. The root of this hierarchy is formed by class `Any`. Every class in a Scala execution environment inherits directly or indirectly from this class. Class `Any` has two direct subclasses: `AnyRef` and `AnyVal`.

The subclass `AnyRef` represents all values which are represented as objects in the underlying host system. Every user-defined Scala class inherits directly or indirectly from this class. Furthermore, every user-defined Scala class also inherits the trait `scala.ScalaObject`. Classes written in other languages still inherit from `scala.AnyRef`, but not from `scala.ScalaObject`.

The class `AnyVal` has a fixed number subclasses, which describe values which are not implemented as objects in the underlying host system.

Classes `AnyRef` and `AnyVal` are required to provide only the members declared in class `Any`, but implementations may add host-specific methods to these classes (for instance, an implementation may identify class `AnyRef` with its own root class for objects).

The signatures of these root classes are described by the following definitions.

```
package scala
/** The universal root class */
abstract class Any {

    /** Defined equality; abstract here */
    def equals(that: Any): Boolean
```



```

}

/** The root class of all value types */
final class AnyVal extends Any

/** The root class of all reference types */
class AnyRef extends Any {
  def equals(that: Any): Boolean = this eq that
  final def eq(that: AnyRef): Boolean = ... // reference equality

  def hashCode: Int = ... // hashCode computed from allocation address
  def toString: String = ... // toString computed from hashCode and class name

  /** A mixin class for every user-defined Scala class */
  trait ScalaObject extends AnyRef

```

The test `x.asInstanceOf[T]` is treated specially if `T` is a numeric value type (§12.2). In this case the cast will be translated to an application of a conversion method `x.toT` (§12.2.1). For non-numeric values `x` the operation will raise a `ClassCastException`.

12.2 Value Classes

Value classes are classes whose instances are not represented as objects by the underlying host system. All value classes inherit from class `AnyVal`. Scala implementations need to provide the value classes `Unit`, `Boolean`, `Double`, `Float`, `Long`, `Int`, `Char`, `Short`, and `Byte` (but are free to provide others as well). The signatures of these classes are defined in the following.

12.2.1 Numeric Value Types

Classes `Double`, `Float`, `Long`, `Int`, `Char`, `Short`, and `Byte` are together called *numeric value types*. Classes `Byte`, `Short`, or `Char` are called *subrange types*. Subrange types, as well as `Int` and `Long` are called *integer types*, whereas `Float` and `Double` are called *floating point types*.

Numeric value types are ranked in the following partial order:

```

Byte - Short
      \
      Int - Long - Float - Double
      /
Char

```

`Byte` and `Short` are the lowest-ranked types in this order, whereas `Double` is the

highest-ranked. Ranking does *not* imply a conformance (§3.5.2) relationship; for instance `Int` is not a subtype of `Long`. However, object `Predef` (§12.5) defines views (§7.3) from every numeric value type to all higher-ranked numeric value types. Therefore, lower-ranked types are implicitly converted to higher-ranked types when required by the context (§6.25).

Given two numeric value types S and T , the *operation type* of S and T is defined as follows: If both S and T are subrange types then the operation type of S and T is `Int`. Otherwise the operation type of S and T is the larger of the two types wrt ranking. Given two numeric values v and w the operation type of v and w is the operation type of their run-time types.

Any numeric value type T supports the following methods.

- Comparison methods for equals (`==`), not-equals (`!=`), less-than (`<`), greater-than (`>`), less-than-or-equals (`<=`), greater-than-or-equals (`>=`), which each exist in 7 overloaded alternatives. Each alternative takes a parameter of some numeric value type. Its result type is type `Boolean`. The operation is evaluated by converting the receiver and its argument to their operation type and performing the given comparison operation of that type.
- Arithmetic methods addition (`+`), subtraction (`-`), multiplication (`*`), division (`/`), and remainder (`%`), which each exist in 7 overloaded alternatives. Each alternative takes a parameter of some numeric value type U . Its result type is the operation type of T and U . The operation is evaluated by converting the receiver and its argument to their operation type and performing the given arithmetic operation of that type.
- Parameterless arithmetic methods identity (`+`) and negation (`-`), with result type T . The first of these returns the receiver unchanged, whereas the second returns its negation.
- Conversion methods `toByte`, `toShort`, `toChar`, `toInt`, `toLong`, `toFloat`, `toDouble` which convert the receiver object to the target type, using the rules of Java's numeric type cast operation. The conversion might truncate the numeric value (as when going from `Long` to `Int` or from `Int` to `Byte`) or it might lose precision (as when going from `Double` to `Float` or when converting between `Long` and `Float`).

Integer numeric value types support in addition the following operations:

- Bit manipulation methods bitwise-and (`&`), bitwise-or (`|`), and bitwise-exclusive-or (`^`), which each exist in 5 overloaded alternatives. Each alternative takes a parameter of some integer numeric value type. Its result type is the operation type of T and U . The operation is evaluated by converting the receiver and its argument to their operation type and performing the given bitwise operation of that type.

- A parameterless bit-negation method (`~`). Its result type is the receiver type *T* or `Int`, whichever is larger. The operation is evaluated by converting the receiver to the result type and negating every bit in its value.
- Bit-shift methods left-shift (`<<`), arithmetic right-shift (`>>`), and unsigned right-shift (`>>>`). Each of these methods has two overloaded alternatives, which take a parameter *n* of type `Int`, respectively `Long`. The result type of the operation is the receiver type *T*, or `Int`, whichever is larger. The operation is evaluated by converting the receiver to the result type and performing the specified shift by *n* bits.

Numeric value types also implement operations `equals`, `hashCode`, and `toString` from class `Any`.

The `equals` method tests whether the argument is a numeric value type. If this is true, it will perform the `==` operation which is appropriate for that type. That is, the `equals` method of a numeric value type can be thought of being defined as follows:

```
def equals(other: Any): Boolean = other match {
  case that: Byte    => this == that
  case that: Short   => this == that
  case that: Char     => this == that
  case that: Int      => this == that
  case that: Long     => this == that
  case that: Float    => this == that
  case that: Double   => this == that
  case _ => false
}
```

The `hashCode` method returns an integer hashCode that maps equal numeric values to equal results. It is guaranteed to be the identity for type `Int` and for all subrange types.

The `toString` method displays its receiver as an integer or floating point number.

Example 12.2.1 As an example, here is the signature of the numeric value type `Int`:

```
package scala
abstract sealed class Int extends AnyVal {
  def == (that: Double): Boolean // double equality
  def == (that: Float): Boolean  // float equality
  def == (that: Long): Boolean   // long equality
  def == (that: Int): Boolean    // int equality
  def == (that: Short): Boolean  // int equality
  def == (that: Byte): Boolean   // int equality
  def == (that: Char): Boolean   // int equality
  /* analogous for !=, <, >, <=, >= */
}
```

```

def + (that: Double): Double    // double addition
def + (that: Float): Double    // float addition
def + (that: Long): Long       // long addition
def + (that: Int): Int         // int addition
def + (that: Short): Int       // int addition
def + (that: Byte): Int        // int addition
def + (that: Char): Int        // int addition
/* analogous for -, *, /, % */

def & (that: Long): Long       // long bitwise and
def & (that: Int): Int         // int bitwise and
def & (that: Short): Int       // int bitwise and
def & (that: Byte): Int        // int bitwise and
def & (that: Char): Int        // int bitwise and
/* analogous for |, ^ */

def << (cnt: Int): Int         // int left shift
def << (cnt: Long): Int        // long left shift
/* analogous for >>, >>> */

def unary_+ : Int             // int identity
def unary_- : Int             // int negation
def unary_~ : Int             // int bitwise negation

def toByte: Byte              // convert to Byte
def toShort: Short            // convert to Short
def toChar: Char              // convert to Char
def toInt: Int                // convert to Int
def toLong: Long              // convert to Long
def toFloat: Float            // convert to Float
def toDouble: Double          // convert to Double
}

```

12.2.2 Class Boolean

Class `Boolean` has only two values: **true** and **false**. It implements operations as given in the following class definition.

```

package scala
abstract sealed class Boolean extends AnyVal {
  def && (p: => Boolean): Boolean = // boolean and
    if (this) p else false
  def || (p: => Boolean): Boolean = // boolean or
    if (this) true else p
  def & (x: Boolean): Boolean =    // boolean strict and
    if (this) x else false

```

```

def | (x: Boolean): Boolean =      // boolean strict or
  if (this) true else x
def == (x: Boolean): Boolean =    // boolean equality
  if (this) x else x.unary_!
def != (x: Boolean): Boolean      // boolean inequality
  if (this) x.unary_! else x
def unary_!: Boolean             // boolean negation
  if (this) false else true
}

```

The class also implements operations `equals`, `hashCode`, and `toString` from class `Any`.

The `equals` method returns **true** if the argument is the same boolean value as the receiver, **false** otherwise. The `hashCode` method returns 1 when invoked on **true**, and 0 when invoked on **false**. The `toString` method returns the receiver converted to a string, i.e. either **"true"** or **"false"**.

12.2.3 Class Unit

Class `Unit` has only one value: `()`. It implements only the three methods `equals`, `hashCode`, and `toString` from class `Any`.

The `equals` method returns **true** if the argument is the unit value `()`, **false** otherwise. The `hashCode` method returns a fixed, implementation-specific hash-code. The `toString` method returns **"()"**.

12.3 Standard Reference Classes

This section presents some standard Scala reference classes which are treated in a special way in Scala compiler – either Scala provides syntactic sugar for them, or the Scala compiler generates special code for their operations. Other classes in the standard Scala library are documented in the Scala library documentation by HTML pages.

12.3.1 Class String

Scala's `String` class is usually derived from the standard `String` class of the underlying host system (and may be identified with it). For Scala clients the class is taken to support in each case a method

```
def + (that: Any): String
```

which concatenates its left operand with the textual representation of its right operand.

12.3.2 The Tuple classes

Scala defines tuple classes `Tuple n` for $n = 2, \dots, 9$. These are defined as follows.

```
package scala
case class Tuple $n$ [+a1, ..., +a $n$ ](_1: a1, ..., _ $n$ : a $n$ ) {
  def toString = "(" ++ _1 ++ "," ++ ... ++ "," ++ _ $n$  ++ ")"
}
```

The implicitly imported `Predef` object (§12.5) defines the names `Pair` as an alias of `Tuple2` and `Triple` as an alias for `Tuple3`.

12.3.3 The Function Classes

Scala defines function classes `Function n` for $n = 1, \dots, 9$. These are defined as follows.

```
package scala
trait Function $n$ [-a1, ..., -a $n$ , +b] {
  def apply(x1: a1, ..., x $n$ : a $n$ ): b
  def toString = "<function>"
}
```

A subclass of `Function1` represents partial functions, which are undefined on some points in their domain. In addition to the `apply` method of functions, partial functions also have a `isDefinedAt` method, which tells whether the function is defined at the given argument:

```
class PartialFunction[-A, +B] extends Function1[A, B] {
  def isDefinedAt(x: A): Boolean
}
```

The implicitly imported `Predef` object (§12.5) defines the name `Function` as an alias of `Function1`.

12.3.4 Class Array

The class of generic arrays is given as follows.

```
final class Array[A](len: Int) extends Seq[A] {
  def length: Int = len
  def apply(i: Int): A = ...
  def update(i: Int, x: A): Unit = ...
  def elements: Iterator[A] = ...
  def subArray(from: Int, end: Int): Array[A] = ...
  def filter(p: A => Boolean): Array[A] = ...
  def map[B](f: A => B): Array[B] = ...
  def flatMap[B](f: A => Array[B]): Array[B] = ...
}
```



```
}
```

If T is not a type parameter or abstract type, the type `Array[T]` is represented as the native array type `[]T` in the underlying host system. In that case `length` returns the length of the array, `apply` means subscripting, and `update` means element update. Because of the syntactic sugar for `apply` and `update` operations (§6.25, we have the following correspondences between Scala and Java/C# code for operations on an array `xs`:

<i>Scala</i>	<i>Java/C#</i>
<code>xs.length</code>	<code>xs.length</code>
<code>xs(i)</code>	<code>xs[i]</code>
<code>xs(i) = e</code>	<code>xs[i] = e</code>

Arrays also implement the sequence trait `scala.Seq` by defining an `elements` method which returns all elements of the array in an `Iterator`.

Because of the tension between parametrized types in Scala and the ad-hoc implementation of arrays in the host-languages, some subtle points need to be taken into account when dealing with arrays. These are explained in the following.

First, unlike arrays in Java or C#, arrays in Scala are *not* co-variant; That is, $S <: T$ does not imply `Array[S] <: Array[T]` in Scala. However, it is possible to cast an array of S to an array of T if such a cast is permitted in the host environment.

For instance `Array[String]` does not conform to `Array[Object]`, even though `String` conforms to `Object`. However, it is possible to cast an expression of type `Array[String]` to `Array[Object]`, and this cast will succeed without raising a `ClassCastException`. Example:

```
val xs = new Array[String](2)
// val ys: Array[Object] = xs    // **** error: incompatible types
val ys: Array[Object] = xs.asInstanceOf[Array[Object]] // OK
```

Second, for *polymorphic arrays*, that have a type parameter or abstract type T as their element type, a representation different from `[]T` might be used. However, it is guaranteed that `asInstanceOf` and `asInstanceOf` still work as if the array used the standard representation of monomorphic arrays:

```
val ss = new Array[String](2)

def f[T](xs: Array[T]): Array[String] =
  if (xs.asInstanceOf[Array[String]]) xs.asInstanceOf[Array[String]]
  else throw new Error("not an instance")

f(ss)                                // returns ss
```

The representation chosen for polymorphic arrays also guarantees that polymorphic array creations work as expected. An example is the following implementation of method `mkArray`, which creates an array of an arbitrary type T , given a sequence of T 's which defines its elements.

```
def mkArray[T](elems: Seq[T]): Array[T] = {
  val result = new Array[T](elems.length)
  var i = 0
  for (elem <- elems) {
    result(i) = elem
    i += 1
  }
}
```

Note that under Java's erasure model of arrays the method above would not work as expected – in fact it would always return an array of `Object`.

Third, in a Java environment there is a method `System.arraycopy` which takes two objects as parameters together with start indices and a length argument, and copies elements from one object to the other, provided the objects are arrays of compatible element types. `System.arraycopy` will not work for Scala's polymorphic arrays because of their different representation. One should instead use method `Array.copy` which is defined in the companion object of class `Array`. This companion object also defines various constructor methods for arrays, as well as the extractor method `unapplySeq` (§8.1.7) which enables pattern matching over arrays.

```
package scala
object Array {
  /** copies array elements from 'src' to 'dest'. */
  def copy(src: AnyRef, srcPos: Int,
           dest: AnyRef, destPos: Int, length: Int): Unit = ...

  /** Concatenate all argument arrays into a single array. */
  def concat[T](xs: Array[T]*): Array[T] = ...

  /** Create a an array of successive integers. */
  def range(start: Int, end: Int): Array[Int] = ...

  /** Create an array with given elements. */
  def apply[A <: AnyRef](xs: A*): Array[A] = ...

  /** Analogous to above. */
  def apply(xs: Boolean*): Array[Boolean] = ...
  def apply(xs: Byte*)   : Array[Byte]    = ...
  def apply(xs: Short*)  : Array[Short]   = ...
  def apply(xs: Char*)   : Array[Char]    = ...
  def apply(xs: Int*)    : Array[Int]     = ...
}
```

```

def apply(xs: Long*) : Array[long] = ...
def apply(xs: Float*) : Array[float] = ...
def apply(xs: Double*) : Array[double] = ...
def apply(xs: Unit*) : Array[unit] = ...

/** Create an array containing several copies of an element. */
def make[A](n: Int, elem: A): Array[A] = {

  /** Enables pattern matching over arrays */
  def unapplySeq[A](x: Array[A]): Option[Seq[A]] = Some(x)
}

```

Example 12.3.1 The following method duplicates a given argument array and returns a pair consisting of the original and the duplicate:

```

def duplicate[T](xs: Array[T]) = {
  val ys = new Array[T](xs.length)
  Array.copy(xs, 0, ys, 0, xs.length)
  (xs, ys)
}

```

12.4 Class Node

```

package scala.xml

trait Node {

  /** the label of this node */
  def label: String

  /** attribute axis */
  def attribute: Map[String, String]

  /** child axis (all children of this node) */
  def child: Seq[Node]

  /** descendant axis (all descendants of this node) */
  def descendant: Seq[Node] = child.toList.flatMap {
    x => x::x.descendant.asInstanceOf[List[Node]]
  }

  /** descendant axis (all descendants of this node) */
  def descendant_or_self: Seq[Node] = this::child.toList.flatMap {
    x => x::x.descendant.asInstanceOf[List[Node]]
  }
}

```

```

}

override def equals(x: Any): Boolean = x match {
  case that:Node =>
    that.label == this.label &&
    that.attribute.sameElements(this.attribute) &&
    that.child.sameElements(this.child)
  case _ => false
}

/** XPath style projection function. Returns all children of this node
 *  that are labeled with 'that'. The document order is preserved.
 */
def \ (that: Symbol): NodeSeq = {
  new NodeSeq({
    that.name match {
      case "_" => child.toList
      case _ =>
        var res:List[Node] = Nil
        for (x <- child.elements if x.label == that.name) {
          res = x::res
        }
        res.reverse
    }
  })
}

/** XPath style projection function. Returns all nodes labeled with the
 *  name 'that' from the 'descendant_or_self' axis. Document order is preserved.
 */
def \\\ (that: Symbol): NodeSeq = {
  new NodeSeq(
    that.name match {
      case "_" => this.descendant_or_self
      case _ => this.descendant_or_self.asInstanceOf[List[Node]].
        filter(x => x.label == that.name)
    }
  )
}

/** hashCode for this XML node */
override def hashCode =
  Utility.hashCode(label, attribute.toList.hashCode, child)

/** string representation of this node */
override def toString = Utility.toXML(this)

```

```
}
```

12.5 The Predef Object

The Predef object defines standard functions and type aliases for Scala programs. It is always implicitly imported, so that all its defined members are available without qualification. Its definition for the JVM environment conforms to the following signature:

```
package scala
object Predef {

  // classOf -----

  /** Return the runtime representation of a class type. */
  def classOf[T]: Class = null // this is a dummy, classOf is handled by compiler.

  // Standard type aliases -----

  type byte    = scala.Byte
  type short   = scala.Short
  type char     = scala.Char
  type int      = scala.Int
  type long     = scala.Long
  type float    = scala.Float
  type double   = scala.Double
  type boolean  = scala.Boolean
  type unit     = scala.Unit

  type String = java.lang.String
  type NullPointerException = java.lang.NullPointerException
  type Throwable = java.lang.Throwable
  type Function[-a,+b] = Function1[a,b]

  // Aliases and extractors for tuples -----

  type Pair[+A, +B] = Tuple2[A, B]
  object Pair {
    def apply[A, B](x: A, y: B) = Tuple2(x, y)
    def unapply[A, B](x: Tuple2[A, B]): Option[Tuple2[A, B]] = Some(x)
  }

  type Triple[+A, +B, +C] = Tuple3[A, B, C]
  object Triple {
    def apply[A, B, C](x: A, y: B, z: C) = Tuple3(x, y, z)
    def unapply[A, B, C](x: Tuple3[A, B, C]): Option[Tuple3[A, B, C]] = Some(x)
  }
}
```

```

// The ‘‘catch-all’’ view -----

implicit def identity[A](x: A): A = x

// Views into class Ordered

implicit def int2ordered(x: Int): Ordered[Int] = new Ordered[Int] with Proxy {
  def self: Any = x
  def compare[B >: Int <% Ordered[B]](y: B): Int = y match {
    case y1: Int =>
      if (x < y1) -1
      else if (x > y1) 1
      else 0
    case _ => -(y compare x)
  }
}

// The implementations of following methods are analogous to the last one:

implicit def char2ordered(x: Char): Ordered[Char] = ...
implicit def long2ordered(x: Long): Ordered[Long] = ...
implicit def float2ordered(x: Float): Ordered[Float] = ...
implicit def double2ordered(x: Double): Ordered[Double] = ...
implicit def boolean2ordered(x: Boolean): Ordered[Boolean] = ...

implicit def seq2ordered[A <% Ordered[A]](xs: Array[A]): Ordered[Seq[A]] =
  new Ordered[Seq[A]] with Proxy {
    def compare[B >: Seq[A] <% Ordered[B]](that: B): Int = that match {
      case that: Seq[A] =>
        var res = 0
        val these = this.elements
        val those = that.elements
        while (res == 0 && these.hasNext)
          res = if (!those.hasNext) 1 else these.next compare those.next
        case _ => -(that compare xs)
    }
  }

implicit def string2ordered(x: String): Ordered[String] =
  new Ordered[String] with Proxy {
    def self: Any = x
    def compare [b >: String <% Ordered[b]](y: b): Int = y match {
      case y1: String => x compare y1
      case _ => -(y compare x)
    }
  }
}

```

```

implicit def tuple2ordered[a1 <% Ordered[a1], a2 <% Ordered[a2]]
    (x: Tuple2[a1, a2]): Ordered[Tuple2[a1, a2]] =
  new Ordered[Tuple2[a1, a2]] with Proxy {
    def self: Any = x
    def compare[T >: Tuple2[a1, a2] <% Ordered[T]](y: T): Int = y match {
      case y: Tuple2[a1, a2] =>
        val res = x._1 compare y._1
        if (res == 0) x._2 compare y._2
        else res
      case _ => -(y compare x)
    }
  }

```

// Analogous for Tuple3 to Tuple9

// Views into class Seq

```

implicit def string2seq(str: String): Seq[Char] = new Seq[Char] {
  def length = str.length()
  def elements = Iterator.fromString(str)
  def apply(n: Int) = str.charAt(n)
  override def hashCode: Int = str.hashCode
  override def equals(y: Any): Boolean = (str == y)
  override protected def stringPrefix: String = "String"
}

```

// Views from primitive types to Java's boxed types

```

implicit def byte2Byte(x: Byte) = new java.lang.Byte(x)
implicit def short2Short(x: Short) = new java.lang.Short(x)
implicit def char2Character(x: Char) = new java.lang.Character(x)
implicit def int2Integer(x: Int) = new java.lang.Integer(x)
implicit def long2Long(x: Long) = new java.lang.Long(x)
implicit def float2Float(x: Float) = new java.lang.Float(x)
implicit def double2Double(x: Double) = new java.lang.Double(x)
implicit def boolean2Boolean(x: Boolean) = new java.lang.Boolean(x)

```

// Numeric conversion views

```

implicit def byte2short(x: Byte): Short = x.toShort
implicit def byte2int(x: Byte): Int = x.toInt
implicit def byte2long(x: Byte): Long = x.toLong
implicit def byte2float(x: Byte): Float = x.toFloat
implicit def byte2double(x: Byte): Double = x.toDouble

```



```
implicit def short2int(x: Short): Int = x.toInt
implicit def short2long(x: Short): Long = x.toLong
implicit def short2float(x: Short): Float = x.toFloat
implicit def short2double(x: Short): Double = x.toDouble

implicit def char2int(x: Char): Int = x.toInt
implicit def char2long(x: Char): Long = x.toLong
implicit def char2float(x: Char): Float = x.toFloat
implicit def char2double(x: Char): Double = x.toDouble

implicit def int2long(x: Int): Long = x.toLong
implicit def int2float(x: Int): Float = x.toFloat
implicit def int2double(x: Int): Double = x.toDouble

implicit def long2float(x: Long): Float = x.toFloat
implicit def long2double(x: Long): Double = x.toDouble

implicit def float2double(x: Float): Double = x.toDouble

// Errors and asserts -----

def error(message: String): Nothing = throw new Error(message)

def exit(): Nothing = exit(0)
def exit(status: Int): Nothing = {
  java.lang.System.exit(status)
  throw new Throwable()
}

def assert(assertion: Boolean): Unit =
  if (!assertion)
    throw new Error("assertion failed")

def assert(assertion: Boolean, message: Any): Unit =
  if (!assertion)
    throw new Error("assertion failed: " + message)

def assume(assumption: Boolean): Unit =
  if (!assumption)
    throw new Error("assumption failed")

def assume(assumption: Boolean, message: Any): Unit =
  if (!assumption)
    throw new Error("assumption failed: " + message)
}
```


Bibliography

- [KP07] Andrew J. Kennedy and Benjamin C. Pierce. On Decidability of Nominal Subtyping with Variance, January 2007. FOOL-WOOD '07.
- [Oa04] Martin Odersky and al. An Overview of the Scala Programming Language. Technical Report IC/2004/64, EPFL Lausanne, Switzerland, 2004.
- [OCRZ03] Martin Odersky, Vincent Cremet, Christine Röckl, and Matthias Zenger. A Nominal Theory of Objects with Dependent Types. In *Proc. ECOOP'03*, Springer LNCS, July 2003.
- [Ode06] Martin Odersky. The Scala Experiment – Can We Provide Better Language Support for Component Systems? In *Proc. ACM Symposium on Principles of Programming Languages*, 2006.
- [OZ05a] Martin Odersky and Matthias Zenger. Independently Extensible Solutions to the Expression Problem. In *Proc. FOOL 12*, January 2005. <http://homepages.inf.ed.ac.uk/wadler/fool>.
- [OZ05b] Martin Odersky and Matthias Zenger. Scalable Component Abstractions. In *Proc. OOPSLA*, 2005.
- [W3C] W3C. Extensible Markup Language (XML). <http://www.w3.org/TR/REC-xml>.

Chapter A

Scala Syntax Summary

The lexical syntax of Scala is given by the following grammar in EBNF form.

```
upper      ::= 'A' | ... | 'Z' | '$' | '_' and Unicode category Lu
lower      ::= 'a' | ... | 'z' and Unicode category Ll
letter     ::= upper | lower and Unicode categories Lo, Lt, Nl
digit      ::= '0' | ... | '9'
opchar     ::= "all other characters in \u0020-007F and Unicode
               categories Sm, So except parentheses ([]) and periods"

op         ::= opchar {opchar}
varid      ::= lower idrest
plainid    ::= upper idrest
            | varid
            | op
id         ::= plainid
            | '\'' stringLit '\''
idrest     ::= {letter | digit} ['_' op]

integerLiteral ::= (decimalNumeral | hexNumeral | octalNumeral) ['L' | 'l']
decimalNumeral ::= '0' | nonZeroDigit {digit}
hexNumeral     ::= '0' 'x' hexDigit {hexDigit}
octalNumeral   ::= '0' octalDigit {octalDigit}
digit          ::= '0' | nonZeroDigit
nonZeroDigit   ::= '1' | ... | '9'
octalDigit     ::= '0' | ... | '7'

floatingPointLiteral
    ::= digit {digit} '.' {digit} [exponentPart] [floatType]
    | '.' digit {digit} [exponentPart] [floatType]
    | digit {digit} exponentPart [floatType]
    | digit {digit} [exponentPart] floatType
exponentPart  ::= ('E' | 'e') ['+' | '-'] digit {digit}
floatType     ::= 'F' | 'f' | 'D' | 'd'
```

```

booleanLiteral ::= 'true' | 'false'

characterLiteral ::= '\\' printableChar '\\'
                  | '\\' charEscapeSeq '\\'

stringLiteral ::= '"' {stringElement} '"'
               | '"""' multiLineChars '"""'
stringElement ::= printableCharNoDoubleQuote
               | charEscapeSeq
multiLineChars ::= {['"'] ['"'] charNoDoubleQuote}

symbolLiteral  ::= ''' plainid

comment        ::= '/*' "any sequence of characters" '*/'
               | '// ' "any sequence of characters up to end of line"

nl             ::= "new line character"
semi          ::= ';' | nl {nl}

```

The context-free syntax of Scala is given by the following EBNF grammar.

```

Literal        ::= integerLiteral
                  | floatingPointLiteral
                  | booleanLiteral
                  | characterLiteral
                  | stringLiteral
                  | symbolLiteral
                  | 'null'

QualId         ::= id {'.' id}
ids            ::= id {',' id}

Path           ::= StableId
                  | [id '.' ] 'this'

StableId       ::= id
                  | Path '.' id
                  | [id '.' ] 'super' [ClassQualifier] '.' id

ClassQualifier ::= '[' id '['

Type           ::= InfixType '=>' Type
                  | '(' ['=>' Type] ')' '=>' Type
                  | InfixType [ExistentialClause]

ExistentialClause ::= 'forSome' '{' ExistentialDcl {semi ExistentialDcl} '}'
ExistentialDcl   ::= 'type' TypeDcl
                  | 'val' ValDcl

InfixType       ::= CompoundType {id [nl] CompoundType}
CompoundType    ::= AnnotType {'with' AnnotType} [Refinement]
                  | Refinement

```

```

AnnotType      ::= {Annotation} SimpleType
SimpleType     ::= SimpleType TypeArgs
                | SimpleType '#' id
                | StableId
                | Path '.' 'type'
                | '(' Types [' ',' ')]
TypeArgs       ::= '[' Types ']'
Types          ::= Type {' ',' Type}
Refinement     ::= [nl] '{' RefineStat {semi RefineStat} '}'
RefineStat     ::= Decl
                | 'type' TypeDef
                |
TypePat        ::= Type

Ascription     ::= ':' CompoundType
                | ':' Annotation {Annotation}
                | ':' '_' '*'

Expr           ::= (Bindings | id) '=>' Expr
                | Expr1
Expr1          ::= 'if' '(' Expr ')' {nl} Expr [[semi] else Expr]
                | while '(' Expr ')' {nl} Expr
                | try '{' Block '}' [catch '{' CaseClauses '}]
                | finally Expr
                | do Expr [semi] while '(' Expr ')'
                | for '(' Enumerators ')' | '{' Enumerators '}'
                | {nl} [yield] Expr
                | throw Expr
                | return [Expr]
                | [SimpleExpr '.'] id '=' Expr
                | SimpleExpr1 ArgumentExprs '=' Expr
                | PostfixExpr
                | PostfixExpr Ascription
                | PostfixExpr match '{' CaseClauses '}'

PostfixExpr    ::= InfixExpr [id [nl]]
InfixExpr      ::= PrefixExpr
                | InfixExpr id [nl] InfixExpr
PrefixExpr     ::= ['- ' | '+ ' | '~ ' | '!'] SimpleExpr
SimpleExpr     ::= new (ClassTemplate | TemplateBody)
                | BlockExpr
                | SimpleExpr1 ['_']

SimpleExpr1    ::= Literal
                | Path
                | '_'
                | '(' [Exprs [' ',' ')]
                | SimpleExpr '.' id
                | SimpleExpr TypeArgs
                | SimpleExpr1 ArgumentExprs
                | XmlExpr

```

Exprs	::= Expr {',' Expr}
ArgumentExprs	::= '(' [Exprs [',']] ')' [nl] BlockExpr
BlockExpr	::= '{' CaseClauses '}' '{' Block '}'
Block	::= {BlockStat semi} [ResultExpr]
BlockStat	::= Import ['implicit'] Def {LocalModifier} TmplDef Expr1
ResultExpr	::= Expr1 (Bindings id ':' CompoundType) '=>' Block
Enumerators	::= Generator {semi Enumerator}
Enumerator	::= Generator Guard 'val' Pattern1 '=' Expr
Generator	::= Pattern1 '<-' Expr [Guard]
CaseClauses	::= CaseClause { CaseClause }
CaseClause	::= 'case' Pattern [Guard] '=>' Block
Guard	::= 'if' PostfixExpr
Pattern	::= Pattern1 { ' ' Pattern1 }
Pattern1	::= varid ':' TypePat '_' ':' TypePat Pattern2
Pattern2	::= varid ['@' Pattern3] Pattern3
Pattern3	::= SimplePattern SimplePattern { id [nl] SimplePattern }
SimplePattern	::= '_' varid Literal StableId StableId '(' [Patterns [',']] ')' StableId '(' [Patterns ',',] '_' '*' ')' '(' [Patterns [',']] ')' XmlPattern
Patterns	::= Pattern [','] Patterns '_' *
TypeParamClause	::= '[' VariantTypeParam {',' VariantTypeParam} ']'
FunTypeParamClause	::= '[' TypeParam {',' TypeParam} ']'
VariantTypeParam	::= ['+' '-'] TypeParam
TypeParam	::= id ['>:' Type] ['<:' Type] ['<%' Type]
ParamClauses	::= {ParamClause} [[nl] '(' 'implicit' Params ')']
ParamClause	::= [nl] '(' [Params] ')'

```

Params          ::= Param {',' Param}
Param           ::= {Annotation} id [':' ParamType]
ParamType       ::= Type
                  | '=>' Type
                  | Type '*'
ClassParamClauses ::= {ClassParamClause}
                  [[nl] '(' implicit ClassParams ')']
ClassParamClause ::= [nl] '(' [ClassParams] ')'
ClassParams      ::= ClassParam {'' ClassParam}
ClassParam       ::= {Annotation} [{Modifier} ('val' | 'var')]
                  id [':' ParamType]
Bindings         ::= '(' Binding {',' Binding ')'
Binding          ::= id [':' Type]

Modifier         ::= LocalModifier
                  | AccessModifier
                  | override
LocalModifier    ::= abstract
                  | final
                  | sealed
                  | implicit
                  | lazy
AccessModifier   ::= ('private' | 'protected') [AccessQualifier]
AccessQualifier  ::= '[' (id | this) '['

Annotation       ::= '@' AnnotationExpr [nl]
AnnotationExpr   ::= Constr [[nl] '{' {NameValuePair} '}']
NameValuePair    ::= val id '=' PrefixExpr

TemplateBody     ::= [nl] '{' [SelfType] TemplateStat {semi TemplateStat} '}'
TemplateStat     ::= Import
                  | {Annotation} {Modifier} Def
                  | {Annotation} {Modifier} Dcl
                  | Expr
                  |
SelfType         ::= id [':' Type] '=>'
                  | this ':' Type '=>'

Import           ::= import ImportExpr {',' ImportExpr}
ImportExpr       ::= StableId '.' (id | '_' | ImportSelectors)
ImportSelectors  ::= '{' {ImportSelector ','} (ImportSelector | '_') '}'
ImportSelector   ::= id ['=>' id | '=>' '_']

Dcl              ::= val ValDcl
                  | var VarDcl
                  | def FunDcl
                  | type {nl} TypeDcl

ValDcl           ::= ids ':' Type

```

VarDcl	::=	ids ':' Type
FunDcl	::=	FunSig [':' Type]
FunSig	::=	id [FunTypeParamClause] ParamClauses
TypeDcl	::=	id [TypeParamClause] ['>:' Type] ['<:' Type]
PatVarDef	::=	'val' PatDef 'var' VarDef
Def	::=	PatVarDef 'def' FunDef 'type' {nl} TypeDef TmplDef
PatDef	::=	Pattern2 {' ,' Pattern2} [':' Type] '=' Expr
VarDef	::=	PatDef ids ':' Type '=' '_'
FunDef	::=	FunSig [':' Type] '=' Expr FunSig [nl] '{' Block '}' 'this' ParamClause ParamClauses ('=' ConstrExpr [nl] ConstrBlock)
TypeDef	::=	id [TypeParamClause] '=' Type
TmplDef	::=	['case'] 'class' ClassDef ['case'] 'object' ObjectDef 'trait' TraitDef
ClassDef	::=	id [TypeParamClause] {Annotation} [AccessModifier] ClassParamClauses ClassTemplateOpt
TraitDef	::=	id [TypeParamClause] TraitTemplateOpt
ObjectDef	::=	id ClassTemplateOpt
ClassTemplateOpt	::=	'extends' ClassTemplate [['extends'] TemplateBody]
TraitTemplateOpt	::=	'extends' TraitTemplate [['extends'] TemplateBody]
ClassTemplate	::=	[EarlyDefs] ClassParents [TemplateBody]
TraitTemplate	::=	[EarlyDefs] TraitParents [TemplateBody]
ClassParents	::=	Constr {'with' AnnotType}
TraitParents	::=	AnnotType {'with' AnnotType}
Constr	::=	AnnotType {ArgumentExprs}
EarlyDefs	::=	'{' [EarlyDef {semi EarlyDef}] '}' 'with'
EarlyDef	::=	{Annotation} {Modifier} PatVarDef
ConstrExpr	::=	SelfInvocation ConstrBlock
ConstrBlock	::=	'{' SelfInvocation {semi BlockStat} '}'
SelfInvocation	::=	'this' ArgumentExprs {ArgumentExprs}
TopStatSeq	::=	TopStat {semi TopStat}
TopStat	::=	{Annotation} {Modifier} TmplDef Import Packaging
Packaging	::=	'package' QualId [nl] '{' TopStatSeq '}'

CompilationUnit ::= [**package** QualId semi] TopStatSeq

Chapter B

Change Log

Changes in Version 2.6 (27-July-2007)

Existential types

It is now possible to define existential types (§3.2.10). An existential type has the form `T forSome {Q}` where `Q` is a sequence of value and/or type declarations. Given the class definitions

```
class Ref[T]
abstract class Outer { type T }
```

one may for example write the following existential types

```
Ref[T] forSome { type T <: java.lang.Number }
Ref[x.T] forSome { val x: Outer }
```

Lazy values

It is now possible to define lazy value declarations using the new modifier **lazy** (§4.1). A **lazy** value definition evaluates its right hand side *e* the first time the value is accessed. Example:

```
import compat.Platform._
val t0 = currentTime
lazy val t1 = currentTime
val t2 = currentTime

println("t0 <= t2: " + (t0 <= t2)) //true
println("t1 <= t2: " + (t1 <= t2)) //false (lazy evaluation of t1)
```

Structural types

It is now possible to declare structural types using type refinements (§3.2.7). For example:

```
class File(name: String) {
  def getName(): String = name
  def open() { /*..*/ }
  def close() { println("close file") }
}
def test(f: { def getName(): String }) { println(f.getName) }

test(new File("test.txt"))
test(new java.io.File("test.txt"))
```

There's also a shorthand form for creating values of structural types. For instance,

```
new { def getName() = "aaron" }
```

is a shorthand for

```
new AnyRef{ def getName() = "aaron" }
```

Changes in Version 2.5 (02-May-2007)

Type constructor polymorphism¹

Type parameters (§4.4) and abstract type members (§4.3) can now also abstract over type constructors (§3.3.3).

This allows a more precise *Iterable* interface:

```
trait Iterable[+T] {
  type MyType[+T] <: Iterable[T] // MyType is a type constructor

  def filter(p: T => Boolean): MyType[T] = ...
  def map[S](f: T => S): MyType[S] = ...
}

abstract class List[+T] extends Iterable[T] {
  type MyType[+T] = List[T]
}
```

This definition of *Iterable* makes explicit that mapping a function over a certain structure (e.g., a *List*) will yield the same structure (containing different elements).

¹Implemented by Adriaan Moors

Early object initialization

It is now possible to initialize some fields of an object before any parent constructors are called (§5.1.6). This is particularly useful for traits, which do not have normal constructor parameters. Example:

```
trait Greeting {
  val name: String
  val msg = "How are you, "+name
}
class C extends {
  val name = "Bob"
} with Greeting {
  println(msg)
}
```

In the code above, the field `name` is initialized before the constructor of `Greeting` is called. Therefore, field `msg` in class `Greeting` is properly initialized to `"How are you, Bob"`.

For-comprehensions, revised

The syntax of for-comprehensions has changed (§6.19). In the new syntax, generators do not start with a `val` anymore, but filters start with an `if` (and are called guards). A semicolon in front of a guard is optional. For example:

```
for (val x <- List(1, 2, 3); x % 2 == 0) println(x)
```

is now written

```
for (x <- List(1, 2, 3) if x % 2 == 0) println(x)
```

The old syntax is still available but will be deprecated in the future.

Implicit anonymous functions

It is now possible to define anonymous functions using underscores in parameter position (§Example 6.23.1). For instance, the expressions in the left column are each function values which expand to the anonymous functions on their right.

<code>_ + 1</code>	<code>x => x + 1</code>
<code>_ * _</code>	<code>(x1, x2) => x1 * x2</code>
<code>(_: int) * 2</code>	<code>(x: int) => (x: int) * 2</code>
<code>if (_) x else y</code>	<code>z => if (z) x else y</code>
<code>_.map(f)</code>	<code>x => x.map(f)</code>
<code>_.map(_ + 1)</code>	<code>x => x.map(y => y + 1)</code>

As a special case (§6.7), a partially unapplied method is now designated `m _` instead of the previous notation `&m`.

The new notation will displace the special syntax forms `.m()` for abstracting over method receivers and `&m` for treating an unapplied method as a function value. For the time being, the old syntax forms are still available, but they will be deprecated in the future.

Pattern matching anonymous functions, refined

It is now possible to use case clauses to define a function value directly for functions of arities greater than one (§8.5). Previously, only unary functions could be defined that way. Example:

```
def scalarProduct(xs: Array[Double], ys: Array[Double]) =
  (0.0 /: (xs zip ys)) {
    case (a, (b, c)) => a + b * c
  }
```

Changes in Version 2.4 (09-Mar-2007)

Object-local private and protected

The **private** and **protected** modifiers now accept a `[this]` qualifier (§5.2). A definition `M` which is labelled **private**`[this]` is private, and in addition can be accessed only from within the current object. That is, the only legal prefixes for `M` are **this** or `C.this`. Analogously, a definition `M` which is labelled **protected**`[this]` is protected, and in addition can be accessed only from within the current object.

Tuples, revised

The syntax for tuples has been changed from `{...}` to `(...)` (§6.9). For any sequence of types T_1, \dots, T_n ,

(T_1, \dots, T_n) is a shorthand for `Tuplen[T_1, \dots, T_n]`.

Analogously, for any sequence of expressions or patterns x_1, \dots, x_n ,

(x_1, \dots, x_n) is a shorthand for `Tuplen(x_1, \dots, x_n)`.

Access modifiers for primary constructors

The primary constructor of a class can now be marked **private** or **protected** (§5.3). If such an access modifier is given, it comes between the name of the class and its value parameters. Example:

```
class C[T] private (x: T) { ... }
```


Annotations

The support for attributes has been extended and its syntax changed (§11). Attributes are now called *annotations*. The syntax has been changed to follow Java's conventions, e.g. `@attribute` instead of `[attribute]`. The old syntax is still available but will be deprecated in the future.

Annotations are now serialized so that they can be read by compile-time or run-time tools. Class `scala.Annotation` has two sub-traits which are used to indicate how annotations are retained. Instances of an annotation class inheriting from trait `scala.ClassfileAnnotation` will be stored in the generated class files. Instances of an annotation class inheriting from trait `scala.StaticAnnotation` will be visible to the Scala type-checker in every compilation unit where the annotated symbol is accessed.

Decidable subtyping

The implementation of subtyping has been changed to prevent infinite recursions. Termination of subtyping is now ensured by a new restriction of class graphs to be finitary (§5.1.5).

Case classes cannot be abstract

It is now explicitly ruled out that case classes can be abstract (§5.2). The specification was silent on this point before, but did not explain how abstract case classes were treated. The Scala compiler allowed the idiom.

New syntax for self aliases and self types

It is now possible to give an explicit alias name and/or type for the self reference **this** (§5.1). For instance, in

```
class C { self: D =>
  ...
}
```

the name `self` is introduced as an alias for **this** within `C` and the self type (§5.3) of `C` is assumed to be `D`. This construct is introduced now in order to replace eventually both the qualified `this` construct `C.this` and the **requires** clause in Scala.

Assignment Operators

It is now possible to combine operators with assignments (§6.12.4). Example:

```
var x: Int = 0
x += 1
```

Changes in Version 2.3.2 (23-Jan-2007)

Extractors

It is now possible to define patterns independently of case classes, using unapply methods in extractor objects (§8.1.7). Here is an example:

```
object Twice {
  def apply(x:Int): int = x*2
  def unapply(z:Int): Option[int] = if (z%2==0) Some(z/2) else None
}
val x = Twice(21)
x match { case Twice(n) => Console.println(n) } // prints 21
```

In the example, Twice is an extractor object with two methods:

- The apply method is used to build even numbers.
- The unapply method is used to decompose an even number; it is in a sense the reverse of apply. unapply methods return option types: Some(...) for a match that succeeds, None for a match that fails. Pattern variables are returned as the elements of Some. If there are several variables, they are grouped in a tuple.

In the second-to-last line, Twice's apply method is used to construct a number x. In the last line, x is tested against the pattern Twice(n). This pattern succeeds for even numbers and assigns to the variable n one half of the number that was tested. The pattern match makes use of the unapply method of object Twice. More details on extractors can be found in the paper “Matching Objects with Patterns” by Emir, Odersky and Williams.

Tuples

A new lightweight syntax for tuples has been introduced (§6.9). For any sequence of types T_1, \dots, T_n ,

$\{T_1, \dots, T_n\}$ is a shorthand for `Tuplen[T_1, \dots, T_n]`.

Analogously, for any sequence of expressions or patterns x_1, \dots, x_n ,

$\{x_1, \dots, x_n\}$ is a shorthand for `Tuplen(x_1, \dots, x_n)`.

Infix operators of greater arities

It is now possible to use methods which have more than one parameter as infix operators (§6.12). In this case, all method arguments are written as a normal parameter list in parentheses. Example:

```

class C {
  def +(x: Int, y: String) = ...
}
val c = new C
c + (1, "abc")

```

Deprecated attribute

A new standard attribute deprecated is available (§11). If a member definition is marked with this attribute, any reference to the member will cause a “deprecated” warning message to be emitted.

Changes in Version 2.3 (23-Nov-2006)

Procedures

A simplified syntax for functions returning `unit` has been introduced (§4.6.3). Scala now allows the following shorthands:

<code>def f(params)</code>	for	<code>def f(params): unit</code>
<code>def f(params) { ... }</code>	for	<code>def f(params): unit = { ... }</code>

Type Patterns

The syntax of types in patterns has been refined (§8.2). Scala now distinguishes between type variables (starting with a lower case letter) and types as type arguments in patterns. Type variables are bound in the pattern. Other type arguments are, as in previous versions, erased. The Scala compiler will now issue an “unchecked” warning at places where type erasure might compromise type-safety.

Standard Types

The recommended names for the two bottom classes in Scala’s type hierarchy have changed as follows:

<code>All</code>	<code>==></code>	<code>Nothing</code>
<code>AllRef</code>	<code>==></code>	<code>Null</code>

The old names are still available as type aliases.

Changes in Version 2.1.8 (23-Aug-2006)

Visibility Qualifier for protected

Protected members can now have a visibility qualifier (§5.2), e.g. **protected**[<qualifier>]. In particular, one can now simulate package protected access as in Java writing

```
protected[P] def X ...
```

where P would name the package containing X.

Relaxation of Private Access

Private members of a class can now be referenced from the companion module of the class and vice versa (§5.2)

Implicit Lookup

The lookup method for implicit definitions has been generalized (§7.2). When searching for an implicit definition matching a type *T*, now are considered

1. all identifiers accessible without prefix, and
2. all members of companion modules of classes associated with *T*.

(The second clause is more general than before). Here, a class is *associated* with a type *T* if it is referenced by some part of *T*, or if it is a base class of some part of *T*. For instance, to find implicit members corresponding to the type

```
HashSet[List[Int], String]
```

one would now look in the companion modules (aka static parts) of `HashSet`, `List`, `Int`, and `String`. Before, it was just the static part of `HashSet`.

Tightened Pattern Match

A typed pattern match with a singleton type `p.type` now tests whether the selector value is reference-equal to `p` (§8.1). Example:

```
val p = List(1, 2, 3)
val q = List(1, 2)
val r = q
r match {
  case _: p.type => Console.println("p")
  case _: q.type => Console.println("q")
}
```

This will match the second case and hence will print "q". Before, the singleton types were erased to List, and therefore the first case would have matched, which is non-sensical.

Changes in Version 2.1.7 (19-Jul-2006)

Multi-Line string literals

It is now possible to write multi-line string-literals enclosed in triple quotes (§1.3.5). Example:

```
"""this is a
   multi-line
   string literal"""
```

No escape substitutions except for unicode escapes are performed in such string literals.

Closure Syntax

The syntax of closures has been slightly restricted (§6.23). The form

```
x: T => E
```

is valid only when enclosed in braces, i.e. { x: T => E }. The following is illegal, because it might be read as the value x typed with the type T => E:

```
val f = x: T => E
```

Legal alternatives are:

```
val f = { x: T => E }
val f = (x: T) => E
```

Changes in Version 2.1.5 (24-May-2006)

Class Literals

There is a new syntax for class literals (§6.2): For any class type C, `classOf[C]` designates the run-time representation of C.

Changes in Version 2.0 (12-Mar-2006)

Scala in its second version is different in some details from the first version of the language. There have been several additions and some old idioms are no longer supported. This appendix summarizes the main changes.

New Keywords

The following three words are now reserved; they cannot be used as identifiers (§1.1)

`implicit` `match` `requires`

Newlines as Statement Separators

Newlines can now be used as statement separators in place of semicolons (§1.2)

Syntax Restrictions

There are some other situations where old constructs no longer work:

Pattern matching expressions. The `match` keyword now appears only as infix operator between a selector expression and a number of cases, as in:

```
expr match {
  case Some(x) => ...
  case None => ...
}
```

Variants such as `expr.match {...}` or just `match {...}` are no longer supported.

“With” in extends clauses. The idiom

```
class C with M { ... }
```

is no longer supported. A `with` connective is only allowed following an `extends` clause. For instance, the line above would have to be written

```
class C extends AnyRef with M { ... } .
```

However, assuming `M` is a trait (see 5.3.3), it is also legal to write

```
class C extends M { ... }
```

The latter expression is treated as equivalent to

```
class C extends S with M { ... }
```

where S is the superclass of M.

Regular Expression Patterns. The only form of regular expression pattern that is currently supported is a sequence pattern, which might end in a sequence wildcard `_*`. Example:

```
case List(1, 2, _) => ... // will match all lists starting with \code{1,2}.
```

It is at current not clear whether this is a permanent restriction. We are evaluating the possibility of re-introducing full regular expression patterns in Scala.

Selftype Annotations

The recommended syntax of selftype annotations has changed.

```
class C: T extends B { ... }
```

becomes

```
class C requires T extends B { ... }
```

That is, selftypes are now indicated by the new **requires** keyword. The old syntax is still available but is considered deprecated. Conversions

For-comprehensions

For-comprehensions (§6.19) now admit value and pattern definitions. Example:

```
for {
  val x <- List.range(1, 100)
  val y <- List.range(1, x)
  val z = x + y
  isPrime(z)
} yield Pair(x, y)
```

Note the definition `val z = x + y` as the third item in the for-comprehension.

Conversions

The rules for implicit conversions of methods to functions (§6.25) have been tightened. Previously, a parameterized method used as a value was always implicitly converted to a function. This could lead to unexpected results when method arguments were forgotten. Consider for instance the statement below:

```
show(x.toString)
```

where `show` is defined as follows:

```
def show(x: String) = Console.println(x) .
```

Most likely, the programmer forgot to supply an empty argument list `()` to `toString`. The previous Scala version would treat this code as a partially applied method, and expand it to:

```
show(() => x.toString())
```

As a result, the address of a closure would be printed instead of the value of `s`.

Scala version 2.0 will apply a conversion from partially applied method to function value only if the expected type of the expression is indeed a function type. For instance, the conversion would not be applied in the code above because the expected type of `show`'s parameter is `String`, not a function type.

The new convention disallows some previously legal code. Example:

```
def sum(f: int => double)(a: int, b: int): double =  
  if (a > b) 0 else f(a) + sum(f)(a + 1, b)  
  
val sumInts = sum(x => x) // error: missing arguments
```

The partial application of `sum` in the last line of the code above will not be converted to a function type. Instead, the compiler will produce an error message which states that arguments for method `sum` are missing. The problem can be fixed by providing an expected type for the partial application, for instance by annotating the definition of `sumInts` with its type:

```
val sumInts: (int, int) => double = sum(x => x) // OK
```

On the other hand, Scala version 2.0 now automatically applies methods with empty parameter lists to `()` argument lists when necessary. For instance, the `show` expression above will now be expanded to

```
show(x.toString()) .
```

Scala version 2.0 also relaxes the rules of overriding with respect to empty parameter lists. The revised definition of *matching members* (§5.1.3) makes it now possible to override a method with an explicit, but empty parameter list `()` with a parameterless method, and *vice versa*. For instance, the following class definition is now legal:

```
class C {  
  override def toString: String = ...  
}
```

Previously this definition would have been rejected, because the `toString` method as inherited from `java.lang.Object` takes an empty parameter list.

Class Parameters

A class parameter may now be prefixed by **val** or **var** (§5.3).

Private Qualifiers

Previously, Scala had three levels of visibility: *private*, *protected* and *public*. There was no way to restrict accesses to members of the current package, as in Java. Scala 2 now defines access qualifiers that let one express this level of visibility, among others. In the definition

```
private[C] def f(...)
```

access to `f` is restricted to all code within the class or package `C` (which must contain the definition of `f`) (§5.2)

Changes in the Mixin Model

The model which details mixin composition of classes has changed significantly. The main differences are:

1. We now distinguish between *traits* that are used as mixin classes and normal classes. The syntax of traits has been generalized from version 1.0, in that traits are now allowed to have mutable fields. However, as in version 1.0, traits may still do not have constructor parameters.
2. Member resolution and super accesses are now both defined in terms of a *class linearization*.
3. Scala's notion of method overloading has been generalized; in particular, it is now possible to have overloaded variants of the same method in a subclass and in a superclass, or in several different mixins. This makes method overloading in Scala conceptually the same as in Java.

The new mixin model is explained in more detail in §5.

Implicit Parameters

Views in Scala 1.0 have been replaced by the more general concept of implicit parameters (§7)

Flexible Typing of Pattern Matching

The new version of Scala implements more flexible typing rules when it comes to pattern matching over heterogeneous class hierarchies (§8.4). A *heterogeneous class hierarchy* is one where subclasses inherit a common superclass with different parameter types. With the new rules in Scala version 2.0 one can perform pattern

matches over such hierarchies with more precise typings that keep track of the information gained by comparing the types of a selector and a matching pattern (Example 8.4.1). This gives Scala capabilities analogous to guarded algebraic data types.